

GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067
Phone: (215) 547-1015

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **POTASSIUM ETHOXIDE 20-22% in ETHANOL-AKP641**

CHEMICAL NAME: POTASSIUM ETHOXIDE 20-22% in ETHANOL

SYNONYMS: POTASSIUM ETHYLATE; ETHANOL, POTASSIUM SALT

CHEMICAL FAMILY: METAL ALCOHOLATE

FORMULA: C₂H₅OK

HMIS CODES HEALTH: 3 FLAMMABILITY: 4 REACTIVITY: 1

INGREDIENTS

IDENTITY	CAS NO.	%	TLV	OSHA PEL
POTASSIUM ETHOXIDE	917-58-6	20-22	not established	not established
ETHANOL	64-17-5	78-80	1000ppm	1000ppm

PHYSICAL DATA

Boiling Point: 78° (initial, ethanol)
Specific Gravity: 0.894
Vapor Density, air =1: 1.59 (ethanol)
% volatiles: >80
Molecular Weight: 84.16
Appearance & Color: Clear solution

Melting Point: <0°C
Vapor Pressure, 25°: not determined
Solubility in water: reacts, then dissolves
Evaporation rate: NA
Other: N/A

FIRE & EXPLOSION DATA

Flash Point, COC: 21°C (70°F) Autoignition Temp. not determined
Flammability Limits-ethanol LEL: 3.3% UEL: 19%

Extinguishing Media: Dry chemical extinguisher, dry soda ash.

Special Fire Fighting Procedures: Protect against caustic vapors, smoke and water. Wear pressure demand self-contained breathing apparatus with full facepiece and full protective clothing.

Unusual Fire and Explosion Hazards: Irritating fumes and caustic vapors may develop when material is exposed to elevated temperatures or open flame.

-1-(AKP641)

ENVIRONMENTAL INFORMATION

Spill response: Ventilate area. Eliminate ignition sources. Absorb material into oil absorbent type clay, scoop into a dry metal container and cover loosely. Take to a chemical disposal area, then flush with a copious amount of water, collecting all caustic wastewater for proper disposal.

Recommended disposal: Treat quantities of 500 grams or less by flooding with water. Water solution will be caustic. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: Potassium ethoxide will cause immediate or delayed severe caustic burns to the eyes.

Skin contact: Will cause irritation and burns. Worker will notice a slippery feeling on washing.

Inhalation: Inhalation will cause sneezing, irritation and burns.

Oral Toxicity- rat, LD50: 548mg/kg (for 100% potassium ethoxide)

Inhalation Toxicity: not determined

SUGGESTED FIRST AID

General first-aid for contact follows treatment protocols for caustics.

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes, holding eyes open. Get medical attention.

SKIN: Immediately flush with water for at least fifteen minutes.

INHALATION: Move exposed individual to fresh air. Administer oxygen if needed. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Give a demulscent such as milk, olive oil, or margarine in small amounts, up to two or three tablespoons.

REACTIVITY DATA

Stability: Stable under nitrogen or argon in sealed containers.

Conditions to avoid: Material decomposes slowly in contact with moist air and rapidly in contact with water. Avoid contact with moist air, water, acids, alcohols, ketones, esters, carbon dioxide, halogens.

Hazardous decomposition products: Potassiumhydroxide, ethanol and caustic organic vapors.

-2-(AKP641)

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, a NIOSH approved Caustic organic vapor-type respirator should be worn.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. Long-sleeved fire-resistant lab uniform or coverall is recommended. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store under dry nitrogen or argon in sealed containers.

TRANSPORTATION

DOT SHIPPING NAME: FLAMMABLE LIQUID, N.O.S. (CONTAINS ETHANOL)

DOT HAZARD CLASS: 3

DOT LABELS: FLAMMABLE LIQUID

DOT ID No: UN1993

PG: II

Prepared by safety and environmental affairs

MSDS ISSUE DATE AKP641: 9/16/14

SUPERSEDES: none

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

-3-(AKP641)

© 2014 Gelest Inc. Morrisville, PA 19067