

Safety Data Sheet PSI-026
Date of issue: 02/05/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Physical state : Liquid

Substance name : POLY(DIMETHOXYSILOXANE)

Product code : PSI-026

Synonyms : METHYLSILICATE 51
Chemical family : SILICATE ESTER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Chemical intermediate

For research and industrial use only

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 4 H227 Eye Irrit. 2A H319

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H227 - Combustible liquid

H319 - Causes serious eye irritation

Precautionary statements (GHS-US)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P337+P313 - If eye irritation persists: Get medical advice/attention

P210 - Keep away from heat, open flames, sparks. - No smoking P370+P378 - In case of fire: Use water spray or fog, foam, carbon dioxide, dry chemical to

extinguish

P264 - Wash hands thoroughly after handling

P403+P235 - Keep in a cool place

P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Substance type : Mono-constituent

02/05/2015 EN (English US) SDS ID: **PSI-026** Page 1

Safety Data Sheet

Name : POLY(DIMETHOXYSILOXANE)

CAS No : 25498-02-6

Name	Product identifier	%	Classification (GHS-US)
Poly(dimethoxysiloxane)	(CAS No) 25498-02-6	> 95	Flam. Liq. 4, H227 Eye Irrit. 2A, H319
Methanol	(CAS No) 67-56-1		Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370 STOT SE 3, H336

Mixture

Not applicable

SECTION 4: First aid measures

Description of first aid measures

First-aid measures general Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water.

First-aid measures after eye contact Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact May cause skin irritation. Symptoms/injuries after eye contact Causes serious eye irritation.

Symptoms/injuries after ingestion Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system.

Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

SECTION 5: Firefighting measures

Extinguishing media

: Water spray. Water fog. Foam. Carbon dioxide. Dry chemical. Suitable extinguishing media

Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid. Vapors of methanol cause corneal injury and blindness. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open

flame

Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

Protection during firefighting Do not enter fire area without proper protective equipment, including respiratory protection. Fire fighters must wear positive pressure self-contained breathing apparatus. Avoid all eye and skin

contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

02/05/2015 EN (English US) SDS ID: PSI-026 2/8

Safety Data Sheet

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any

: Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Avoid all eye and skin contact and do not breathe vapor and mist. Use only in well ventilated areas. Provide good ventilation in process area to prevent accumulation of vapors. Take precautionary measures against static discharge. Use only non-sparking tools.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed.

Incompatible materials : Oxidizing agent.

Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methanol (67-56-1)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	260 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	325 mg/m³
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	260 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA IDLH	US IDLH (ppm)	6000 ppm

8.2. Exposure controls

рΗ

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be

available in the immediate vicinity of any potential exposure.

Hand protection : Neoprene or nitrile rubber gloves.

Eye protection : Chemical worker's goggles must be worn. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear liquid.

Molecular mass : 106.15 g/mol

Color : No data available

Odor : Characteristic. Antiseptic.

Odor threshold : No data available

Refractive index : No data available

02/05/2015 EN (English US) SDS ID: **PSI-026** 3/8

: No data available

Safety Data Sheet

Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available

Freezing point : <0°C Boiling point : > 220 °C Flash point > 61 °C

Auto-ignition temperature : No data available Decomposition temperature : No data available Combustible liquid Flammability (solid, gas) Vapor pressure No data available Relative vapor density at 20 °C No data available Relative density : 1.14 - 1.16

. < 2 %

Solubility Insoluble in water. Log Pow No data available Log Kow : No data available No data available Viscosity, kinematic Viscosity, dynamic No data available Explosive properties No data available Oxidizing properties : No data available **Explosive limits** : No data available

Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

VOC content

No additional information available

Chemical stability 10.2.

Stable.

10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air or with water liberating methanol.

Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Oxidizing agent.

Hazardous decomposition products

Methanol. Organic acid vapors. Silicon dioxide.

SECTION 11: Toxicological information

Information on toxicological effects

: Not classified Acute toxicity

Methanol (67-56-1)				
LD50 oral rat	6200 mg/kg			
LD50 dermal rabbit	20 g/kg			
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)			
ATE US (oral)	100.000 mg/kg body weight			
ATE US (dermal)	300.000 mg/kg body weight			
ATE US (vapors)	3.000 mg/l/4h			

Skin corrosion/irritation : Not classified

Serious eye damage/irritation Causes serious eye irritation.

> Initial symptoms of exposure may include a "scratchy" feeling in the eyes. A related material, silicon tetramethoxide, causes severe eye injuries, as well as necrosis of corneal cells, which

can progress long after exposure has ceased.

Respiratory or skin sensitization Not classified Germ cell mutagenicity Not classified Carcinogenicity Not classified Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) Not classified

02/05/2015 EN (English US) SDS ID: PSI-026 4/8

Safety Data Sheet

Specific target organ toxicity (repeated

exposure)

: Not classified

: Not classified Aspiration hazard

Potential Adverse human health effects and

symptoms

: Note: The hydrolysis product of polydimethoxysiloxane is methanol.

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact May cause skin irritation. Symptoms/injuries after eye contact Causes serious eye irritation.

Symptoms/injuries after ingestion Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms On contact with water this compound liberates methanol which is known to have a chronic

effect on the central nervous system.

Reason for classification : Expert judgment

SECTION 12: Ecological information

Toxicity

Methanol (67-56-1)				
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])			
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])			

Persistence and degradability

No additional information available

Bioaccumulative potential 12.3.

Methanol (67-56-1)			
BCF fish 1	< 10		
Log Pow	-0.77		

Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects This substance may be hazardous to the environment.

Effect on ozone layer No additional information available

Effect on the global warming No known ecological damage caused by this product.

SECTION 13: Disposal considerations

Waste treatment methods 13.1.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. **UN** number

NA1993 DOT NA no.

UN proper shipping name

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.

(POLY(DIMETHOXYSILOXANE))

Department of Transportation (DOT) Hazard

Classes

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

DOT Symbols

: D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN

requiring a technical name

Packing group (DOT) : III - Minor Danger

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) . 241

14.3. Additional information

Other information : No supplementary information available.

02/05/2015 SDS ID: PSI-026 EN (English US) 5/8

Safety Data Sheet

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

Methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

SARA Section 313 - Emission Reporting 1.0 %

Poly(dimethoxysiloxane) (25498-02-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

Methanol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Canadian DSL (Domestic Sustances List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Poisonous and Deleterious Substances Control Law

Listed on the Canadian IDL (Ingredient Disclosure List)

Poly(dimethoxysiloxane) (25498-02-6)

Listed on the Korean ECL (Existing Chemicals List)

15.3. US State regulations

POLY(DIMETHOXYSILOXANE)(25498-02-6)		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	No	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	

Methanol (67-56-1) U.S. - California -

Proposition 65 - Carcinogens List	Proposition 65 - Developmental Toxicity	Proposition 65 - Reproductive Toxicity - Female	Proposition 65 - Reproductive Toxicity - Male	(NSRL)
No	Yes	No	No	
Poly(dimethoxysiloxane)	(25498-02-6)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)

U.S. - California -

No

No significance risk level

U.S. - California -

Methanol (67-56-1)

No

U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)

U.S. - California -

- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Acute
- U.S. California SCAQMD Toxic Air Contaminants Non-Cancer Chronic
- U.S. California Toxic Air Contaminant List (AB 1807, AB 2728)

No

U.S. - Colorado - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues

No

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Connecticut Volatile Substances

02/05/2015 EN (English US) SDS ID: **PSI-026** 6/8

Safety Data Sheet

```
Methanol (67-56-1)
U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations
U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Emission Levels (ELs)
U.S. - Idaho - Occupational Exposure Limits - TWAs
U.S. - Illinois - Toxic Air Contaminants
U.S. - Louisiana - Reportable Quantity List for Pollutants
U.S. - Maine - Air Pollutants - Hazardous Air Pollutants
U.S. - Maine - Chemicals of High Concern
U.S. - Massachusetts - Allowable Ambient Limits (AALs)
U.S. - Massachusetts - Allowable Threshold Concentrations (ATCs)
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2
U.S. - Massachusetts - Right To Know List
U.S. - Massachusetts - Threshold Effects Exposure Limits (TELs)
U.S. - Massachusetts - Toxics Use Reduction Act
U.S. - Michigan - Occupational Exposure Limits - Skin Designations
U.S. - Michigan - Occupational Exposure Limits - STELs
U.S. - Michigan - Occupational Exposure Limits - TWAs
U.S. - Michigan - Polluting Materials List
U.S. - Minnesota - Chemicals of High Concern
U.S. - Minnesota - Groundwater Health Risk Limits
U.S. - Minnesota - Hazardous Substance List
U.S. - Minnesota - Permissible Exposure Limits - Skin Designations
U.S. - Minnesota - Permissible Exposure Limits - STELs
U.S. - Minnesota - Permissible Exposure Limits - TWAs
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-Hour
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual
U.S. - New Jersey - Discharge Prevention - List of Hazardous Substances
U.S. - New Jersey - Environmental Hazardous Substances List U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - New Jersey - Special Health Hazards Substances List
U.S. - New Jersey - Water Quality - Ground Water Quality Criteria
U.S. - New Jersey - Water Quality - Practical Quantitation Levels (PQLs)
U.S. - New York - Occupational Exposure Limits - Skin Designations U.S. - New York - Occupational Exposure Limits - TWAs
U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances
U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 1-Hour U.S. - North Dakota - Air Pollutants - Guideline Concentrations - 8-Hour
U.S. - North Dakota - Hazardous Wastes - Discarded Chemical Products, Off-Specification Species, Container and Spill Residues
U.S. - Oregon - Permissible Exposure Limits - TWAs
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - 1-Hour
U.S. - Rhode Island - Air Toxics - Acceptable Ambient Levels - Annual
U.S. - South Carolina - Toxic Air Pollutants - Maximum Allowable Concentrations
U.S. - South Carolina - Toxic Air Pollutants - Pollutant Categories
U.S. - Tennessee - Occupational Exposure Limits - Skin Designations
U.S. - Tennessee - Occupational Exposure Limits - STELs
U.S. - Tennessee - Occupational Exposure Limits - TWAs
U.S. - Texas - Effects Screening Levels - Long Term
U.S. - Texas - Effects Screening Levels - Short Term
U.S. - Vermont - Permissible Exposure Limits - Skin Designations
U.S. - Vermont - Permissible Exposure Limits - STELs
U.S. - Vermont - Permissible Exposure Limits - TWAs
U.S. - Washington - Dangerous Waste - Discarded Chemical Products List
U.S. - Washington - Permissible Exposure Limits - Skin Designations
U.S. - Washington - Permissible Exposure Limits - STELs
U.S. - Washington - Permissible Exposure Limits - TWAs
```

SECTION 16: Other information

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

02/05/2015 EN (English US) SDS ID: **PSI-026** 7/8

Safety Data Sheet

Full text of H-phrases::

tt of 11 philaded.	
Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H370	Causes damage to organs

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 2 Moderate Hazard
Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 02/05/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2014 Gelest Inc. Morrisville, PA 19067

02/05/2015 EN (English US) SDS ID: **PSI-026** 8/8