

2-[METHOXY(POLYETHYLENEOXY)6-9PROPYL]TRIMETHOXYSILANE, tech-90

Safety Data Sheet SIM6492.7

Date of issue: 05/08/2014

Revision date: 07/21/2015

Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Substance
Physical state	: Liquid
Substance name	: 2-[METHOXY(POLYETHYLENEOXY)6-9PROPYL]TRIMETHOXYSILANE, tech-90
Product code	: SIM6492.7
Formula	: CH ₃ O(C ₂ H ₄ O) ₆₋₉ (CH ₂) ₃ Si(OCH ₃) ₃
Synonyms	: TRIMETHOXYSILYLPROPYPOLYETHYLENEOXIDE METHYL ETHER; METHOXY(POLYETHYLENEOXY)PROPYLTRIMETHOXYSILANE
Chemical family	: ORGANOMETHOXYSILANE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Chemical intermediate For research and industrial use only
------------------------------	---

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road
Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 4 H227

Eye Irrit. 2A H319

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US)

: Warning

Hazard statements (GHS-US)

: H227 - Combustible liquid
H319 - Causes serious eye irritation

Precautionary statements (GHS-US)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection
P264 - Wash hands thoroughly after handling
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337+P313 - If eye irritation persists: Get medical advice/attention
P210 - Keep away from heat, open flames, sparks. - No smoking
P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish
P403+P235 - Keep in a cool place
P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

2-[METHOXY(POLYETHYLENEOXY)6-9PROPYL]TRIMETHOXYSILANE, tech-90

Safety Data Sheet

SECTION 3: Composition/information on ingredients

3.1. Substance

Substance type	: Mono-constituent
Name	: 2-[METHOXY(POLYETHYLENEOXY)6-9PROPYL]TRIMETHOXYSILANE, tech-90
CAS No	: 65994-07-2

Name	Product identifier	%	Classification (GHS-US)
Methoxy(polyethyleneoxy)propyltrimethoxysilane	(CAS No) 65994-07-2	> 95	Flam. Liq. 4, H227 Eye Irrit. 2A, H319
methanol	(CAS No) 67-56-1		Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370 STOT SE 3, H336

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
First-aid measures after skin contact	: Wash with plenty of soap and water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache. Nausea.
Symptoms/injuries after skin contact	: May cause skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea, vomiting, headache, visual effects including blindness.
Chronic symptoms	: On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision.

4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media	: None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Combustible liquid. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
-------------	---

5.3. Advice for firefighters

Firefighting instructions	: Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

2-[METHOXY(POLYETHYLENEOXY)6-9PROPYL]TRIMETHOXYSILANE, tech-90

Safety Data Sheet

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat, open flames, sparks. - No smoking.

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in process area to prevent accumulation of vapors. Take precautionary measures against static discharge. Use only in well ventilated areas.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep container tightly closed.

Incompatible materials : Moisture. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methanol (67-56-1)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	250 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA IDLH	US IDLH (ppm)	6000 ppm

8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection : Neoprene or nitrile rubber gloves.

Eye protection : Chemical goggles. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

2-[METHOXY(POLYETHYLENEOXY)6-9PROPYL]TRIMETHOXYSILANE, tech-90

Safety Data Sheet

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Molecular mass	: 459 - 591 g/mol
Color	: Straw.
Odor	: Mild.
Odor threshold	: No data available
Refractive index	: 1.403
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: -8 °C
Boiling point	: > 250 °C
Flash point	: 88 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Combustible liquid
Vapor pressure	: No data available
Relative vapor density at 20 °C	: > 1
Relative density	: 1.076
Solubility	: Soluble in water. Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 29 cSt
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Moisture. Water.

10.6. Hazardous decomposition products

Methanol. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

methanol (67-56-1)

LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)
ATE US (oral)	100.000 mg/kg body weight

2-[METHOXY(POLYETHYLENEOXY)6-9PROPYL]TRIMETHOXYSILANE, tech-90

Safety Data Sheet

methanol (67-56-1)	
ATE US (dermal)	300.000 mg/kg body weight
ATE US (vapors)	3.000 mg/l/4h
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache. Nausea.
Symptoms/injuries after skin contact	: May cause skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea, vomiting, headache, visual effects including blindness.
Chronic symptoms	: On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system. Methanol may affect the central nervous system resulting in persistent or recurring headaches or impaired vision.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

methanol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

methanol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects	: This substance may be hazardous to the environment.
Effect on ozone layer	: No additional information available
Effect on the global warming	: No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: May be incinerated. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

DOT NA no.	NA1993
------------	--------

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: COMBUSTIBLE LIQUID, N.O.S. (2-[METHOXY(POLYETHYLENEOXY)9-12PROPYL]TRIMETHOXYSILANE)
Department of Transportation (DOT) Hazard Classes	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

2-[METHOXY(POLYETHYLENEOXY)6-9PROPYL]TRIMETHOXYSILANE, tech-90

Safety Data Sheet

DOT Symbols	: D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name
Packing group (DOT)	: III - Minor Danger
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 241

14.3. Additional information

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Listed on United States SARA Section 313

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Methoxy(polyethyleneoxy)propyltrimethoxysilane (65994-07-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

methanol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Canadian DSL (Domestic Substances List)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

Methoxy(polyethyleneoxy)propyltrimethoxysilane (65994-07-2)

Listed on the Canadian DSL (Domestic Substances List)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

15.3. US State regulations

2-[METHOXY(POLYETHYLENEOXY)6-9PROPYL]TRIMETHOXYSILANE, tech-90(65994-07-2)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

methanol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	

2-[METHOXY(POLYETHYLENEOXY)6-9PROPYL]TRIMETHOXYSILANE, tech-90

Safety Data Sheet

Methoxy(polyethyleneoxy)propyltrimethoxysilane (65994-07-2)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	

SECTION 16: Other information

Abbreviations and acronyms : Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

Full text of H-phrases::

Acute Tox. 3 (Dermal)	Acute toxicity (dermal) Category 3
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapor) Category 3
Acute Tox. 3 (Oral)	Acute toxicity (oral) Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H227	Combustible liquid
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H370	Causes damage to organs

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
 Flammability : 2 Moderate Hazard
 Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 05/08/2014 Revision date: 07/21/2015 Version: 2.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2015 Gelest Inc. Morrisville, PA 19067