

# **GELEST, INC.**

11 East Steel Rd. Morrisville, PA 19067 Phone: (215) 547-1015

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **SODIUM TRIMETHYLSILANOLATE**, 96% - **SIS6988.0** 

CHEMICAL NAME: SODIUM TRIMETHYLSILANOLATE

SYNONYMS: SODIUM TRIMETHYLSILOXIDE; TRIMEHYLSILANOL, SODIUM SALT

CHEMICAL FAMILY: ORGANOSILANE

FORMULA: C<sub>3</sub>H<sub>9</sub>ONaSi

HMIS CODES HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 1

# **INGREDIENTS**

IDENTITY CAS NO. % TLV OSHA PEL

SODIUM TRIMETHYLSILANOLATE HEXAMETHYLDISILOXANE

18027-10-6 >95 not established not established not established

# PHYSICAL DATA

Boiling Point: NA Melting Point: (147-150°C)- degrades

Specific Gravity: not determined Vapor Pressure: not determined Vapor Density: NA Solubility in water: insoluble, reacts

% volatiles NA Evaporation rate: NA

Molecular Weight: 112.18 Other: NA Appearance & Color: Off white to tan solid, slight odor.

#### **FIRE & EXPLOSION DATA**

Flash Point, COC: > 65°C (>150°F) Autoignition Temp.: not determined

Flammability Limits: not determined

Combustible solid.

Extinguishing Media: Foam, carbon dioxide, dry chemical.

Special Fire Fighting Procedures: Avoid water spray as volatile organics will be generated. Avoid

eye and skin contact. Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Irritating fumes and caustic vapors may develop when

material is exposed to elevated temperatures or open flame.

Abbreviations: ND: Not Determined, No Data; NA: Not Apple (Section 2) Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemcial Abstract Service Registration Number Gelest, Inc. © 2008



#### **ENVIRONMENTAL INFORMATION**

Spill response: Ventilate area. Eliminate ignition sources. Scoop material into a dry metal container and cover loosely. Take to a chemical disposal area, then flush with a copious amount of water, collecting all caustic wastewater for proper disposal.

Recommended disposal: Treat quantities of 1000 grams or less by flooding with water. Water solution will be caustic. Follow all chemical pollution control regulations. For larger quantities, mix with water, neutralize with dilute hydrochloric acid, then separate non-aqueous liquid for incineration. Alternately, combine with neutral or basic organic streams and incinerate

#### **HEALTH HAZARD DATA**

Eye Contact: Sodium trimethylsilanolate will cause immediate or delayed severe caustic burns to the eyes.

Skin contact: Will cause irritation and burns. If skin and air are dry, powder on skin may not cause irritation or burns. Worker will notice a slippery feeling on washing. However, if moisture is present, the powder can cause severe caustic burns.

Inhalation: Inhalation will cause sneezing, irritation and burns.

Oral Toxicity: not determined Inhalation Toxicity: not determined

## SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes, holding eyes open. Get medical attention.

SKIN: Immediately shake or brush off any loose material, then flush with water for at least fifteen minutes.

INHALATION: Move exposed individual to fresh air. Administer oxygen if needed. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Give a demulscent such as milk, olive oil, or margarine in small amounts, up to two or three tablespoons.

# **REACTIVITY DATA**

Stability: Stable under nitrogen or argon in sealed containers.

Conditions to avoid: Material decomposes slowly in contact with moist air and rapidly in contact with water, possibly igniting. Avoid contact with moist air, water, acids, alcohols, ketones, esters, carbon dioxide, halogens.

Hazardous decomposition products: Sodium hydroxide, hexamethyldisiloxane and caustic organic vapors.

-2-(SIS6988.0)



#### SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, a NIOSH approved particulate filter-type

respirator should be worn.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. Long-sleeved fire-resistant lab uniform or coverall is recommended. An eyewash and emergency shower should be available. Launder clothing before reuse.

## OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store under dry nitrogen or argon in sealed containers.

## **TRANSPORTATION**

DOT SHIPPING NAME: CORROSIVE SOLID, BASIC, ORGANIC n.o.s.

(SODIUM TRIMETHYLSILANOLATE)

**DOT HAZARD CLASS: 8** 

DOT LABELS: 6.1

DOT ID No: 3262 PG: III

Prepared by safety and environmental affairs MSDS ISSUE DATE SIS6988.0: 7/23/13

SUPERSEDES: 1/29/13

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

-3-(SIS6988.0) © 2013 Gelest Inc. Morrisville, PA 19067