


WWW.GELEST.COM acrylates@gelest.com

BIMAX® DSF

Disodium fumarate CAS No. 17013-01-3 EINECS No. 2410877



Applications

This material is used in cleaning products such as laundry detergents, soaps, degreasers, spot removers, etc. Disodium fumarate has also been known to reduce ruminal methane when used as a feed additive and can be used in personal care as a buffering agent or a pH adjustor.

Typical Properties

 Purity, %
 100

 Moisture, %
 < 0.15</td>

 pH (10% in water)
 6.5-7.0

Physical Properties

Appearance Molecular weight Particle size, % through 20 mesh Solubility in water white powder 160.0 g/mol 100 soluble

Packaging

25-gallon fiber drum, containing 100 lbs each

Storage and Handling

Store at temperatures below 32°C, away from heat, light, and polymerization initiators. Wear goggles and gloves. Eye and skin contact, as well as inhalation, should be avoided. If contact occurs, wash affected area immediately with cold water. Consult the Safety Data Sheet.

This information is presented for your consideration in the belief that it is accurate and reliable; however, Bimax makes no guarantees or warranty, either expressed or implied, of the accuracy or the completeness of this information. The information in this data sheet is designed only as a guidance for safe handling, storage and use of the substance. It is not a specification, nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Individuals receiving this information are expected to use their own judgment in determining the relevancy for a particular circumstance. Accordingly, Bimax will not be responsible for damages of any kind resulting from the use of, or reliance upon, such information.

281 Industrial Road Glen Rock, Pennsylvania 17327, USA Tel: +1 717-227-1774 Fax: +1 717-227-1775