


BIMAX® AC

Acryloyl chloride
CAS No. 814-68-6
EINECS No. 2123990



Applications

This material is used extensively in the preparation of acrylate monomers and polymers. Its high reactivity makes it an excellent intermediate for pharmaceutical and specialized chemical synthesis.

Typical Properties

Purity, %	99
MEHQ, ppm	200

Physical Properties

Appearance	clear, light yellow liquid
Molecular weight	90.5 g/mol
Boiling range	74-76°C
Flash Point	14°C
Density (relative), 25°C	1.11 g/ml

Packaging

HDPP bottle, containing 4 kg each
HDPP pail, containing 30 kg each

Storage and Handling

Store tightly closed, in a cool, dry place, away from heat and ignition sources. Recommended storage temperature is $\leq -5^{\circ}\text{C}$. Wear goggles and gloves. Eye and skin contact, as well as inhalation, should be avoided. If contact occurs, wash affected area immediately with cold water. Consult the Safety Data Sheet.

This information is presented for your consideration in the belief that it is accurate and reliable; however, Bimax makes no guarantees or warranty, either expressed or implied, of the accuracy or the completeness of this information. The information in this data sheet is designed only as a guidance for safe handling, storage and use of the substance. It is not a specification, nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Individuals receiving this information are expected to use their own judgment in determining the relevancy for a particular circumstance. Accordingly, Bimax will not be responsible for damages of any kind resulting from the use of, or reliance upon, such information.

281 Industrial Road Glen Rock, Pennsylvania 17327, USA
Tel: +1 717-227-1774 Fax: +1 717-227-1775