


## BIMAX® DMPM

Bis-(2-methoxy-methylethyl) maleate  
CAS No. 102054-10-4  
EINECS No. Not applicable



### Applications

This material has applications in paper coatings and resins. It is also used as a stabilizer for silicone linings and release coatings.

#### Typical Properties

Purity, %	95
Color, APHA	< 100
Moisture, ppm	< 500
Acid, mgKOH/g	< 0.1

#### Physical Properties

Appearance	clear, light yellow liquid
Molecular weight	260.3 g/mol
Flash Point	157°C
Boiling point	272°C
Density (relative), 20°C	1.09 g/ml
Refractive index, 25°C	1.576

### Packaging

5-gallon pails, containing 18kg each  
55-gallon poly drums, containing 200kg each  
275-gallon IBCs, containing 900kg each

### Storage and Handling

Store in a dry place at temperatures below 32°C, away from heat and light. Wear goggles and gloves. Eye and skin contact, as well as inhalation, should be avoided. If contact occurs, wash affected area immediately with cold water. Consult the Safety Data Sheet.

This information is presented for your consideration in the belief that it is accurate and reliable; however, Bimax makes no guarantees or warranty, either expressed or implied, of the accuracy or the completeness of this information. The information in this data sheet is designed only as a guidance for safe handling, storage and use of the substance. It is not a specification, nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Individuals receiving this information are expected to use their own judgment in determining the relevancy for a particular circumstance. Accordingly, Bimax will not be responsible for damages of any kind resulting from the use of, or reliance upon, such information.