


BIMAX® TFEMA-T

2, 2, 2-Trifluoroethyl methacrylate
CAS No. 352-87-4
EINECS No. 2065253
Technical Grade



Applications

This material has applications in the manufacture of electrical components, as well as adhesives and binding agents. It also has uses in hair-styling compositions comprising of a combination of hard and soft latex film-forming polymers.

Typical Properties

Purity, %	> 99.0
Color, APHA	< 20
Moisture, %	< 0.10
MEHQ, ppm	80-100

Physical Properties

Appearance	clear, colorless liquid
Molecular weight	168.1 g/mol
Flash Point, closed cup	25°C
Density (relative), 20°C	1.1769 g/cm ³
Initial boiling point, 100 mmHg	59°C

Packaging

1-gallon HDPE bottles, containing 4 kg each
5-gallon poly pails, containing 20 kg each

Storage and Handling

Store at temperatures below 32°C, away from heat sources. Wear goggles and gloves. Eye and skin contact, as well as inhalation, should be avoided. If contact occurs, wash affected area immediately with cold water. Consult the Safety Data Sheet.

This information is presented for your consideration in the belief that it is accurate and reliable; however, Bimax makes no guarantees or warranty, either expressed or implied, of the accuracy or the completeness of this information. The information in this data sheet is designed only as a guidance for safe handling, storage and use of the substance. It is not a specification, nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Individuals receiving this information are expected to use their own judgment in determining the relevancy for a particular circumstance. Accordingly, Bimax will not be responsible for damages of any kind resulting from the use of, or reliance upon, such information.