

WWW.GELEST.COM acrylates@gelest.com

BIMAX® BEM-25/50

Behenylpolyethoxy (25) methacrylate CAS No. 125441-87-4 EINECS No. Not applicable

Applications

This product is an ethoxylated monomer solution used in associative thickeners, rheological additives, etc. because it can modify the surface activity of water-soluble polymers. It is an excellent nonionic surfactant, and unlike conventional surfactants it can be incorporated in the polymer backbone. Consequently, it can be used as a copolymerizable nonionic surfactant.

Typical Properties

Active content, %	51
Methacrylic acid, %	23
Water, %	25
рН	4
Viscosity, 25°C	450 cps

Physical Properties

Appearance Molecular weight clear liquid 1494 g/mol

Packaging

55-gallon poly drums, containing 200 kg each

Storage and Handling

Store in a dry place at temperatures below 25°C, away from heat and ignition sources. Wear goggles and gloves. Eye and skin contact, as well as inhalation, should be avoided. If contact occurs, wash affected area immediately with cold water. Consult the Safety Data Sheet.

This information is presented for your consideration in the belief that it is accurate and reliable; however, Bimax makes no guarantees or warranty, either expressed or implied, of the accuracy or the completeness of this information. The information in this data sheet is designed only as a guidance for safe handling, storage and use of the substance. It is not a specification, nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Individuals receiving this information are expected to use their own judgment in determining the relevancy for a particular circumstance. Accordingly, Bimax will not be responsible for damages of any kind resulting from the use of, or reliance upon, such information.

281 Industrial Road Glen Rock, Pennsylvania 17327, USA Tel: +1 717-227-1774 Fax: +1 717-227-1775