


BIMAX® AAEE

2-(2-Acryloylamidoethoxy)ethanol

CAS No. 89911-50-2

EINECS No. Not applicable



Applications

This material is supplied as a 50% solution in water and has applications in the manufacture of electrodes and sensors.

Typical Properties

Purity, %	> 94
pH	6.5-8.0
Water, %	50

Physical Properties

Appearance	clear liquid
Molecular weight	159.2 g/mol

Packaging

1-gallon bottles, containing 4 kg each

5-gallon poly pails, containing 18 kg each

Storage and Handling

Store at temperatures below 0°C, away from heat sources. Wear goggles and gloves. Eye and skin contact, as well as inhalation, should be avoided. If contact occurs, wash affected area immediately with cold water. Consult the Safety Data Sheet.

This information is presented for your consideration in the belief that it is accurate and reliable; however, Bimax makes no guarantees or warranty, either expressed or implied, of the accuracy or the completeness of this information. The information in this data sheet is designed only as a guidance for safe handling, storage and use of the substance. It is not a specification, nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Individuals receiving this information are expected to use their own judgment in determining the relevancy for a particular circumstance. Accordingly, Bimax will not be responsible for damages of any kind resulting from the use of, or reliance upon, such information.

281 Industrial Road Glen Rock, Pennsylvania 17327, USA

Tel: +1 717-227-1774 Fax: +1 717-227-1775