

Safety Data Sheet AKC167

Date of issue: 02/16/2015 Revision date: 11/29/2016 Version: 1.1

SECTION 1: Identification

1.1. Product identifier

Product name : CALCIUM METHOXYETHOXIDE, 20% in methoxyethanol

Product code : AKC167
Product form : Mixture
Physical state : Liquid
Formula : C6H14CaO4

Synonyms : CALCIUM DIMETHOXYETHOXIDE

Chemical family : METAL ALKOXIDE

1.2. Recommended use of the chemical and restrictions on use

Recommended use : Chemical intermediate

For research and industrial use only

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 3

Acute toxicity (dermal) Category 4

Acute toxicity (inhalation:dust,mist) Category 4

Skin corrosion/irritation Category 2

H315

Serious eye damage/eye irritation Category 2A

Reproductive toxicity Category 1B

H226

H312

H332

H315

H360

Full text of H statements: see section 16

Precautionary statements (GHS-US)

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



<u>(!)</u>



GHS02

GHS07

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor

H312+H332 - Harmful in contact with skin or if inhaled

H315 - Causes skin irritation

H319 - Causes serious eye irritation H360 - May damage fertility or the unborn child

: P201 - Obtain special instructions before use

P202 - Do not handle until all safety precautions have been read and understood P280 - Wear protective gloves/protective clothing/eye protection/face protection

P210 - Keep away from heat, open flames, sparks. - No smoking

P233 - Keep container tightly closed

P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P261 - Avoid breathing vapors

P264 - Wash hands thoroughly after handling P271 - Use only outdoors or in a well-ventilated area

P303 + P361 + P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse

Page 1

Print date: 11/29/2016 EN (English US) SDS ID: AKC167

Safety Data Sheet

skin with water/shower

P332 + P313 - If skin irritation occurs: Get medical advice/attention

P304 + P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P337 + P313 - If eye irritation persists: Get medical advice/attention P308 + P313 - If exposed or concerned: Get medical advice/attention P362 + P364 - Take off contaminated clothing and wash it before reuse

P370 + P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to

extinguish

P403 + P235 - Keep in a cool place

P405 - Store locked up

P501 - Dispose of contents/container to licensed waste disposal facility

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
2-Methoxyethanol	(CAS No) 109-86-4	> 75	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Repr. 1B, H360
Calcium methoxyethoxide	(CAS No) 28099-67-4	< 25	Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek

medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

physician.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

Chronic symptoms : Methoxyethanol, a hydrolysis product, is known to have a chronic effect on the central nervous

system.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when

material is exposed to elevated temperatures or open flame.

5.3. Advice for firefighters

Firefighting instructions : Use water spray to cool exposed surfaces. Exercise caution when fighting any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist.

Print date: 11/29/2016 EN (English US) SDS ID: **AKC167** 2/8

Safety Data Sheet

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Containers must be properly

grounded before beginning transfer. Provide good ventilation in process area to prevent accumulation of vapors. Take precautionary measures against static discharge. Use only non-

sparking tools.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Keep container tightly closed.
Incompatible materials : Moist air. Oxidizing agent. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

2-Methoxyethanol (109-86-4)			
ACGIH	ACGIH TWA (ppm)		0.1 ppm
OSHA	OSHA PEL (TWA) (mg/m³)		80 mg/m³
OSHA	OSHA PEL (TWA) (ppm)		25 ppm
IDLH	US IDLH (ppm)		200 ppm
NIOSH	NIOSH REL (TWA) (mg/m³)		0.3 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)		0.1 ppm

8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Emergency eye wash fountains and safety showers should be available in the immediate

vicinity of any potential exposure. Avoid all unnecessary exposure.

Hand protection : Neoprene or nitrile rubber gloves.

Eye protection : Chemical goggles. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: Liquid.Molecular mass: 190.25 g/molColor: dark brown.

Print date: 11/29/2016 EN (English US) SDS ID: **AKC167** 3/8

Safety Data Sheet

Odor : Mild.

Odor threshold : No data available
Refractive index : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available

Freezing point : < 0 °C Boiling point : 124 °C (initial) Flash point : 39 °C

Auto-ignition temperature : No data available Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapor

Vapor pressure : 6.2 mm Hg @ 20°C (methoxyethanol)

Relative vapor density at 20 °C : 2.5 - 2.7Relative density : 1.01VOC content : > 75 %

Solubility : Reacts with water. Log Pow : No data available : No data available Log Kow Viscosity, kinematic : No data available Viscosity, dynamic No data available Explosive properties No data available Oxidizing properties : No data available No data available **Explosion limits**

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Moist air. Oxidizing agent. Water.

10.6. Hazardous decomposition products

Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Dermal: Harmful in contact with skin. Inhalation:dust,mist: Harmful if inhaled.

CALCIUM METHOXYETHOXIDE, 20% in methoxyethanol (28099-67-4)		
ATE US (dermal)	1706.667 mg/kg body weight	
ATE US (dust, mist) 2.000 mg/l/4h		
2-Methoxyethanol (109-86-4)		
LD50 oral rat	2370 mg/kg	
LD50 dermal rabbit	1280 mg/kg	
LC50 inhalation rat (ppm)	1478 ppm (Exposure time: 7 h)	
ATE US (oral)	2370.000 mg/kg body weight	
ATE US (dermal)	1280.000 mg/kg body weight	
ATE US (gases)	4500.000 ppmV/4h	
ATE US (vapors)	11.000 mg/l/4h	
ATE US (dust, mist)	1.500 mg/l/4h	

Print date: 11/29/2016 EN (English US) SDS ID: **AKC167** 4/8

Safety Data Sheet

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

Reproductive toxicity : May damage fertility or the unborn child.

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

Chronic symptoms : Methoxyethanol, a hydrolysis product, is known to have a chronic effect on the central nervous

system.

Reason for classification : Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

2-Methoxyethanol (109-86-4)	
LC50 fish 1	10000 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
LC50 fish 2	9650 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

2-Methoxyethanol (109-86-4)		
Log Pow	-0.85		

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available

Effect on the global warming : No known effects from this product.

GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 1993 DOT NA no. UN1993

14.2. UN proper shipping name

Transport document description : UN1993 Flammable liquids, n.o.s. (CALCIUM METHOXYETHOXIDE, 20% in methoxyethanol),

3, III

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

(CALCIUM METHOXYETHOXIDE, 20% in methoxyethanol)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Packing group (DOT) : III - Minor Danger

Print date: 11/29/2016 EN (English US) SDS ID: **AKC167** 5/8

Safety Data Sheet

Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 : 242 DOT Packaging Bulk (49 CFR 173.xxx) DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

2-Methoxyethanol (109-86-4)				
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313				
EPA TSCA Regulatory Flag	S - S - indicates a substance that is identified in a proposed or final Significant New Uses Rule			
SARA Section 313 - Emission Reporting	1.0 %			
Calcium methoxyethoxide (28099-67-4)				

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

2-Methoxyethanol (109-86-4)	
Listed on the Canadian DSL (Domestic Substance	es List)
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Calcium methoxyethoxide (28099-67-4)	

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

2-Methoxyethanol (109-86-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Calcium methoxyethoxide (28099-67-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Print date: 11/29/2016 SDS ID: AKC167 EN (English US) 6/8

Safety Data Sheet

2-Methoxyethanol (109-86-4)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Japanese Pollutant Release and Transfer Register Law (PRTR Law)

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

2-Methoxyethanol (109-86-4)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	Yes	

2-Methoxyethanol (109-86-4)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

H226	Flammable liquid and vapor
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H360	May damage fertility or the unborn child

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling.

HMIS III Rating

Physical

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

aiven

Flammability : 3 Serious Hazard - Materials capable of ignition under almost all normal temperature

conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

100 F. as well as liquids with hash points between 73 F and 100 F. (Classes ID & IC)

 2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at normal temperature and pressure with low risk for explosion. Materials may react violently with

water or form peroxides upon exposure to air.

Prepared by safety and environmental affairs.

Date of issue: 02/16/2015 Revision date: 11/29/2016 Version: 1.1


SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2016 Gelest Inc. Morrisville, PA 19067

Print date: 11/29/2016 EN (English US) SDS ID: **AKC167** 7/8



Print date: 11/29/2016 EN (English US) SDS ID: **AKC167** 8/8