



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Physical state : Liquid
 Product name : POTASSIUM ISOPROPOXIDE, 18 - 20% in isopropanol
 Product code : AKP643
 Formula : C3H7KO
 Synonyms : POTASSIUM ISOPROPYLATE, POTASSIUM 2-PROPOXIDE
 Chemical family : METAL ALCOHOLATE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Chemical intermediate
 For research use only

1.3. Details of the supplier of the safety data sheet

GELEST, INC.
 11 East Steel Road
 Morrisville, PA 19067
USA
 T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST
info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2 H225
 Skin Corr. 1B H314
 Eye Dam. 1 H318
 STOT SE 3 H336
 Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02 GHS05 GHS07

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H225 - Highly flammable liquid and vapor
 H314 - Causes severe skin burns and eye damage
 H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US) :

P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P210 - Keep away from heat, open flames, sparks. - No smoking
 P240 - Ground/bond container and receiving equipment
 P241 - Use explosion-proof electrical equipment
 P242 - Use only non-sparking tools
 P243 - Take precautionary measures against static discharge
 P260 - Do not breathe vapors
 P261 - Avoid breathing vapors
 P264 - Wash hands thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area
 P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
 P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
 P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P310 - Immediately call a doctor

POTASSIUM ISOPROPOXIDE, 18 - 20% in isopropanol

Safety Data Sheet

P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use dry chemical, dry soda ash to extinguish
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Keep in a cool place
P405 - Store locked up
P321 - Specific treatment (see first aid instructions on this label)
P501 - Dispose of contents/container to licensed waste disposal facility

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Isopropanol	(CAS No) 67-63-0	78 - 84	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Eye Irrit. 2A, H319 STOT SE 3, H336
Potassium isopropoxide	(CAS No) 6831-82-9	16 - 22	Flam. Sol. 1, H228 Skin Corr. 1B, H314 Eye Dam. 1, H318

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage.

Symptoms/injuries after inhalation : May cause drowsiness or dizziness. Inhalation will cause sneezing, irritation and burns.

Symptoms/injuries after skin contact : Causes (severe) skin burns. Worker will notice a slippery feeling on washing.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical. Dry soda ash.

Unsuitable extinguishing media : Do not use straight streams.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Protect against caustic dust, smoke and water.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist. Wear pressure demand self-contained breathing apparatus with full facepiece and full protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

POTASSIUM ISOPROPOXIDE, 18 - 20% in isopropanol

Safety Data Sheet

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat, open flames, sparks. - No smoking.
Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.
Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
Storage conditions : Keep container tightly closed. Keep in a cool place. Store locked up. Store under dry nitrogen or argon in sealed containers.
Incompatible materials : Acids. Alcohols. Carbon dioxide. Esters. Halogens. Ketones. Moist air. Water.
Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Isopropanol (67-63-0)		
USA ACGIH	ACGIH TWA (ppm)	200 ppm
USA ACGIH	ACGIH STEL (ppm)	400 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	980 mg/m ³
USA NIOSH	NIOSH REL (TWA) (ppm)	400 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m ³)	1225 mg/m ³
USA NIOSH	NIOSH REL (STEL) (ppm)	500 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	980 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	400 ppm
USA IDLH	US IDLH (ppm)	2000 ppm (10% LEL)

8.2. Exposure controls

- Appropriate engineering controls : Provide local exhaust or general room ventilation.
Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection : Neoprene or nitrile rubber gloves.
Eye protection : Chemical goggles or face shield. Contact lenses should not be worn.
Skin and body protection : Wear suitable protective clothing. Long-sleeved fire-resistant lab uniform or coverall is recommended.

POTASSIUM ISOPROPOXIDE, 18 - 20% in isopropanol

Safety Data Sheet

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified caustic organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear solution.
Molecular mass	: 98.19 g/mol
Color	: Straw.
Odor	: No data available
Odor threshold	: No data available
Refractive index	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: < 0 °C
Freezing point	: No data available
Boiling point	: 82 °C initial (isopropanol)
Flash point	: 12 °C
Auto-ignition temperature	: 425 °C isopropanol
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Vapor pressure	: No data available
Relative vapor density at 20 °C	: > 2
Relative density	: 0.86
VOC content	: > 75 %
Solubility	: Reacts with water. Dissolves.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 2.5 - 12 vol % (lower; upper: isopropanol)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable under nitrogen or argon in sealed containers.

10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air and rapidly in contact with water.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Acids. Alcohols. Carbon dioxide. Esters. Halogens. Ketones. Moist air. Water.

10.6. Hazardous decomposition products

Potassium hydroxide. Caustic organic vapors. Isopropanol.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Isopropanol (67-63-0)	
LD50 oral rat	1870 mg/kg
LD50 dermal rabbit	4059 mg/kg
LC50 inhalation rat (mg/l)	72600 mg/m ³ (Exposure time: 4 h)

POTASSIUM ISOPROPOXIDE, 18 - 20% in isopropanol

Safety Data Sheet

Isopropanol (67-63-0)	
ATE US (oral)	1870.000 mg/kg body weight
ATE US (dermal)	4059.000 mg/kg body weight

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Isopropanol (67-63-0)	
IARC group	3 - Not classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness. Inhalation will cause sneezing, irritation and burns.
Symptoms/injuries after skin contact	: Causes (severe) skin burns. Worker will notice a slippery feeling on washing.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Isopropanol (67-63-0)	
LC50 fish 1	9640 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	11130 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Isopropanol (67-63-0)	
Log Pow	0.05 (at 25 °C)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects	: This substance may be hazardous to the environment.
Effect on ozone layer	: No additional information available
Effect on the global warming	: No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT)	: 2924
DOT NA no.	UN2924

14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Flammable liquids, corrosive, n.o.s. (POTASSIUM ISOPROPOXIDE, 18 - 20% in isopropanol)
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

POTASSIUM ISOPROPOXIDE, 18 - 20% in isopropanol

Safety Data Sheet

Hazard labels (DOT) : 3 - Flammable liquid
8 - Corrosive



DOT Symbols : G - Identifies PSN requiring a technical name
Packing group (DOT) : II - Medium Danger
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 243

14.3. Additional information

Emergency Response Guide (ERG) Number : 132

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 1 L
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 5 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

POTASSIUM ISOPROPOXIDE, 18 - 20% in isopropanol

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States

Isopropanol (67-63-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

EPA TSCA Regulatory Flag

T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA

SARA Section 313 - Emission Reporting

1.0 % (only if manufactured by the strong acid process, no supplier notification)

Potassium isopropoxide (6831-82-9)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

Isopropanol (67-63-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Canadian DSL (Domestic Substances List)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Japanese ISHL (Industrial Safety and Health Law)
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

Potassium isopropoxide (6831-82-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

POTASSIUM ISOPROPOXIDE, 18 - 20% in isopropanol

Safety Data Sheet

15.3. US State regulations

POTASSIUM ISOPROPOXIDE, 18 - 20% in isopropanol()				
U.S. - California - Proposition 65 - Carcinogens List		No		
U.S. - California - Proposition 65 - Developmental Toxicity		No		
U.S. - California - Proposition 65 - Reproductive Toxicity - Female		No		
U.S. - California - Proposition 65 - Reproductive Toxicity - Male		No		
Isopropanol (67-63-0)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	
Potassium isopropoxide (6831-82-9)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

SECTION 16: Other information

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

Full text of H-phrases::

H225	Highly flammable liquid and vapor
H228	Flammable solid
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability : 4 Severe Hazard
Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 02/29/2016 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2016 Gelest Inc. Morrisville, PA 19067