

**TANTALUM(V) n-BUTOXIDE**

Safety Data Sheet AKT805

Date of issue: 01/15/2016

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form	: Substance
Physical state	: Liquid
Substance name	: TANTALUM(V) n-BUTOXIDE
Product code	: AKT805
Formula	: C ₂₀ H ₄₅ O ₅ Ta
Synonyms	: PENTA-N-BUTOXYTANTALUM; TANTALUM PENTABUTANOLATE
Chemical family	: METAL ESTER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Chemical intermediate For research and industrial use only
------------------------------	---

1.3. Details of the supplier of the safety data sheet**GELEST, INC.**11 East Steel Road
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com**1.4. Emergency telephone number**

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GHS-US classification**

Flam. Liq. 4 H227

Skin Irrit. 2 H315

Eye Irrit. 2A H319

Full text of H statements : see section 16

2.2. Label elements**GHS-US labeling**

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US)

: Warning

Hazard statements (GHS-US)

: H227 - Combustible liquid
H315 - Causes skin irritation
H319 - Causes serious eye irritation

Precautionary statements (GHS-US)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection
P210 - Keep away from heat, open flames, sparks. - No smoking
P264 - Wash hands thoroughly after handling
P302+P352 - If on skin: Wash with plenty of soap and water
P332+P313 - If skin irritation occurs: Get medical advice/attention
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337+P313 - If eye irritation persists: Get medical advice/attention
P321 - Specific treatment (see first aid instructions on this label)
P362+P364 - Take off contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use water spray or fog, foam, carbon dioxide, dry chemical to extinguish
P403+P235 - Keep in a cool place
P501 - Dispose of contents/container to licensed waste disposal facility**2.3. Other hazards**

Other hazards not contributing to the

: Additional n-butanol may be formed by reaction with moisture and water. The US ACGIH

TANTALUM(V) n-BUTOXIDE

Safety Data Sheet

classification (TWA) for n-butanol is 20 ppm. The US OSHA PEL (TWA) for n-butanol is 100 ppm.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Substance type : Mono-constituent
Name : TANTALUM(V) n-BUTOXIDE
CAS No : 51094-78-1
EC no : 256-962-9

Name	Product identifier	%	GHS-US classification
Tantalum(V) n-butoxide	(CAS No) 51094-78-1	95 - 100	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Alcohol-resistant foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

TANTALUM(V) n-BUTOXIDE

Safety Data Sheet

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Provide good ventilation in process area to prevent accumulation of vapors. Use only non-sparking tools.
- Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container tightly closed. Keep in a cool place.
- Incompatible materials : Oxidizing agent.
- Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Tantalum(V) n-butoxide (51094-78-1)

USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³ Ta
----------	-------------------------------------	------------------------

8.2. Exposure controls

- Appropriate engineering controls : Provide local exhaust or general room ventilation.
- Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Hand protection : Neoprene or nitrile rubber gloves.
- Eye protection : Chemical goggles. Contact lenses should not be worn.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Liquid.
- Molecular mass : 546.53 g/mol
- Color : Pale yellow.
- Odor : Characteristic odor of n-butanol.
- Odor threshold : No data available
- Refractive index : 1.483
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : < 0 °C
- Freezing point : No data available
- Boiling point : 217 °C @ 0.15 mm Hg
- Flash point : 66 °C
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : Combustible liquid

TANTALUM(V) n-BUTOXIDE

Safety Data Sheet

Vapor pressure	: < 0.01 mm Hg @ 20 °C
Relative vapor density at 20 °C	: > 1
Relative density	: 1.31
VOC content	: < 5 %
Solubility	: Reacts with water. Organic solvent:Soluble: hexane
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: 1.4 - 11.2 vol % (lower; upper; based on n-butanol released by hydrolysis)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air and rapidly in contact with water liberating n-butanol.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

n-Butanol. Organic acid vapors. Tantalum oxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

TANTALUM(V) n-BUTOXIDE (51094-78-1)

Toxicity information	8000 mg/kg oral rat, LD50; Note: The hydrolysis products of tantalum butoxide are tantalum oxide and n-butanol. Tantalum oxide is reported to be moderately toxic.
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Material generates n-butanol on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue.
Symptoms/injuries after inhalation	: May cause irritation to the respiratory tract.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

TANTALUM(V) n-BUTOXIDE

Safety Data Sheet

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available
Effect on the global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

DOT NA no. NA1993

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.
(TANTALUM(V) n-BUTOXIDE)
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name
Packing group (DOT) : III - Minor Danger
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241

14.3. Additional information

Other information : No supplementary information available.
Special transport precautions : This product is Combustible as defined by the US Department of Transportation (DOT). It is regulated for transport in the US in container > 119 gallons. The product is not regulated for transport by the IATA, ADR/RID, ADNR or the IMDG regulations.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 220 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

Tantalum(V) n-butoxide (51094-78-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

Tantalum(V) n-butoxide (51094-78-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Canadian NDSL (Non-Domestic Substances List)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

TANTALUM(V) n-BUTOXIDE

Safety Data Sheet

15.3. US State regulations

TANTALUM(V) n-BUTOXIDE(51094-78-1)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

Tantalum(V) n-butoxide (51094-78-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

SECTION 16: Other information

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

Full text of H-phrases::

H227	Combustible liquid
H315	Causes skin irritation
H319	Causes serious eye irritation

HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Flammability : 2 Moderate Hazard
Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 01/15/2016 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2016 Gelest Inc. Morrisville, PA 19067