

**TANTALUM(V) ISOPROPOXIDE**

Safety Data Sheet AKT850

Date of issue: 01/15/2016

Version: 1.0

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form	: Substance
Physical state	: Solid
Substance name	: TANTALUM(V) ISOPROPOXIDE
Product code	: AKT813
Formula	: C15H35O5Ta
Synonyms	: PENTAIISOPROPOXYTANTALUM
Chemical family	: METAL ESTER

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture	: Chemical intermediate For research use only
------------------------------	--

**1.3. Details of the supplier of the safety data sheet****GELEST, INC.**11 East Steel Road  
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)**1.4. Emergency telephone number**


Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GHS-US classification**Flam. Sol. 2 H228  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319

Full text of H statements : see section 16

**2.2. Label elements****GHS-US labeling**

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Warning

Hazard statements (GHS-US)

: H228 - Flammable solid  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation

Precautionary statements (GHS-US)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P210 - Keep away from heat, open flames, sparks. - No smoking  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical equipment  
P264 - Wash hands thoroughly after handling  
P302+P352 - If on skin: Wash with plenty of soap and water  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P337+P313 - If eye irritation persists: Get medical advice/attention  
P321 - Specific treatment (see first aid instructions on this label)  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use water spray, alcohol resistant foam, carbon dioxide, dry chemical to extinguish**2.3. Other hazards**

Other hazards not contributing to the classification

: Additional isopropanol may be formed by reaction with moisture and water. The US ACGIH (TWA) for isopropanol is 200 ppm. The US OSHA PEL (TWA) for isopropanol is 400 ppm.

# TANTALUM(V) ISOPROPOXIDE

## Safety Data Sheet

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Substance type : Mono-constituent  
Name : TANTALUM(V) ISOPROPOXIDE  
CAS No : 16761-83-4

Name	Product identifier	%	GHS-US classification
Tantalum(V) isopropoxide	(CAS No) 16761-83-4	95 - 100	Flam. Sol. 2, H228 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

### 3.2. Mixture

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Alcohol-resistant foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable solid. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

### 5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid contact with skin and eyes. Do not breathe dust.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

# TANTALUM(V) ISOPROPOXIDE

## Safety Data Sheet

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Additional hazards when processed : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Precautions for safe handling : Avoid contact with skin and eyes. Avoid dust formation. Do not breathe dust. Ground/bond container and receiving equipment. Use only non-sparking tools. Provide local exhaust or general room ventilation to minimize exposure to dust.
- Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container tightly closed. Keep in a cool place.
- Incompatible materials : Oxidizing agent.
- Storage area : Store in a well-ventilated place. Store away from heat.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Tantalum(V) isopropoxide (16761-83-4)

USA ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> tantalum
-----------	--------------------------------	------------------------------

### 8.2. Exposure controls

- Appropriate engineering controls : Provide local exhaust or general room ventilation.
- Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Hand protection : Neoprene or nitrile rubber gloves.
- Eye protection : Chemical goggles. Contact lenses should not be worn.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified dust and mist (orange cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Physical state : Solid
- Appearance : Solid.
- Molecular mass : 476.39 g/mol
- Color : Pale yellow.
- Odor : Mild.
- Odor threshold : No data available
- Refractive index : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : 92 °C
- Freezing point : No data available
- Boiling point : 122 °C @ 0.1 mm Hg
- Flash point : > 65 °C
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Flammability (solid, gas) : Flammable solid
- Vapor pressure : 8 mm Hg @ 20 °C
- Relative vapor density at 20 °C : > 1
- Relative density : 1.31

# TANTALUM(V) ISOPROPOXIDE

## Safety Data Sheet

VOC content	: > 50 %
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air and rapidly in contact with water liberating isopropanol.

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Oxidizing agent.

### 10.6. Hazardous decomposition products

Isopropanol. Organic acid vapors. Tantalum oxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### TANTALUM(V) ISOPROPOXIDE (16761-83-4)

Toxicity information	8000 mg/kg oral rat, LD50; Note: The hydrolysis products of tantalum isopropoxide are tantalum oxide and isopropanol. Tantalum oxide is reported to be moderately toxic.
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: Material generates isopropanol on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue.
Symptoms/injuries after inhalation	: May cause irritation to the respiratory tract.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment

## SECTION 12: Ecological information

### 12.1. Toxicity

No additional information available

### 12.2. Persistence and degradability

No additional information available

# TANTALUM(V) ISOPROPOXIDE

## Safety Data Sheet

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on ozone layer : No additional information available  
Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.  
Waste disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations.  
Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

### 14.1. UN number

UN-No.(DOT) : 3181  
DOT NA no. : UN3181

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Metal salts of organic compounds, flammable, n.o.s.  
(TANTALUM(V) ISOPROPOXIDE)  
Class (DOT) : 4.1 - Class 4.1 - Flammable Solid 49 CFR 173.124  
Hazard labels (DOT) : 4.1 - Flammable solid



DOT Symbols : G - Identifies PSN requiring a technical name  
Packing group (DOT) : III - Minor Danger  
DOT Packaging Exceptions (49 CFR 173.xxx) : 151  
DOT Packaging Non Bulk (49 CFR 173.xxx) : 213  
DOT Packaging Bulk (49 CFR 173.xxx) : 240

### 14.3. Additional information

Emergency Response Guide (ERG) Number : 133  
Other information : No supplementary information available.

### Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded  
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

### Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 25 kg  
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 100 kg

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### TANTALUM(V) ISOPROPOXIDE (16761-83-4)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States

# TANTALUM(V) ISOPROPOXIDE

## Safety Data Sheet

### Tantalum(V) isopropoxide (16761-83-4)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

### 15.2. International regulations

No additional information available

### 15.3. US State regulations

#### TANTALUM(V) ISOPROPOXIDE(16761-83-4)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

#### Tantalum(V) isopropoxide (16761-83-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

## SECTION 16: Other information

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

Full text of H-phrases::

H228	Flammable solid
H315	Causes skin irritation
H319	Causes serious eye irritation

### HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given  
Flammability : 3 Serious Hazard  
Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 01/15/2016 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2016 Gelest Inc. Morrisville, PA 19067