



## Satin Feel Foundation with SiBrid® DE-12 & Silky Slip (SS) Treated Pigments

Gelest's Silky Slip (SS) pigments and SiBrid® DE-12 promote easier spreading and blending on skin while providing an exceptionally soft and moist afterfeel to liquid foundations. SiBrid® DE-12 DiEthicone is an excellent vehicle for wetting and dispersing pigments.

INCI Name	Ingredient	Supplier	Wt%
<b>PHASE A</b>			
Water	Deionized Water		49.10
Magnesium Sulfate			0.20
<b>PHASE B</b>			
Butylene Glycol			6.00
Benzoic Acid			0.20
<b>PHASE C</b>			
<b>Polydiethylsiloxane</b>	<b>SiBrid® DE-12</b>	<b>Gelest</b>	<b>5.00</b>
Cyclopentasiloxane	DC 245 Fluid	Dow Silicones	5.00
Lauryl PEG-9 Polydimethylsiloxoethyl Dimethicone	KF 6038	Shin-Etsu	3.00
Cyclopentasiloxane & C30-45 Alkyl Cetearyl Dimethicone Crosspolymer	Velvesil 125	Momentive	10.00
<b>PHASE D</b>			
Laureth-7	Rhodasurf L-7/90	Solvay	0.50
<b>PHASE E</b>			
<b>Polydiethylsiloxane</b>	<b>SiBrid® DE-12</b>	<b>Gelest</b>	<b>12.00</b>
<b>Titanium Dioxide (&amp; Stearyl Triethoxysilane</b>	<b>WIA-SSA</b>	<b>Gelest</b>	<b>8.00</b>
<b>Talc (&amp; Stearyl Triethoxysilane</b>	<b>TA7-SSA</b>	<b>Gelest</b>	<b>4.10</b>
<b>Iron Oxides (&amp; Stearyl Triethoxysilane</b>	<b>YIA-SSA</b>	<b>Gelest</b>	<b>1.20</b>
<b>Iron Oxides (&amp; Stearyl Triethoxysilane</b>	<b>RIA-SSA</b>	<b>Gelest</b>	<b>0.50</b>
<b>Iron Oxides (&amp; Stearyl Triethoxysilane</b>	<b>BIA-SSA</b>	<b>Gelest</b>	<b>0.20</b>
	<b>TOTAL</b>		<b>100</b>

### PROCEDURE:

- Mix Phase A under propeller blade. Premix Phase B while warming to dissolve.
- Add Phase B to Phase A and stir. Premix first three ingredients in Phase C. When uniform, add remaining ingredient and slowly homogenize.
- Add Phase D to Phase C and homogenize.
- Premill Phase E. Add Phase E to Phase CD and homogenize until dispersed.
- Add Phase AB to Phase CDE and continue homogenizing until emulsified.
- Increase speed and homogenize for additional 5 minutes.

Rev 2 (07232013)

Formula GCA2-22-1