



DIMETHYLISOPROPOXYALUMINUM

Safety Data Sheet OMAL025

Date of issue: 09/23/2016

Version: 1.0

SECTION 1: Identification

1.1. Product identifier

Product name	: DIMETHYLISOPROPOXYALUMINUM
Product code	: OMAL025
Product form	: Substance
Physical state	: Liquid
Formula	: C ₅ H ₁₃ AlO
Synonyms	: DMAI ALUMINUM, DIMETHYL(2-PROPANOLATO)- DIMETHYLALUMINUM ISOPROPOXIDE
Chemical family	: METAL ALKYL

1.2. Recommended use of the chemical and restrictions on use

Recommended use	: Chemical intermediate For research and industrial use only
-----------------	---

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road
Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture


GHS-US classification

Flammable liquids Category 2	H225
Substances and mixtures which in contact with water emit flammable gases Category 2	H261
Skin corrosion/irritation Category 1B	H314
Serious eye damage/eye irritation Category 1	H318
Specific target organ toxicity (single exposure) Category 3	H335
Full text of H statements : see section 16	

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapor
H261 - In contact with water releases flammable gases
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H335 - May cause respiratory irritation

Precautionary statements (GHS-US)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection
P210 - Keep away from heat, sparks, open flames. - No smoking
P223 - Do not allow contact with water
P231 + P232 - Handle under inert gas. Protect from moisture
P240 - Ground/Bond container and receiving equipment
P241 - Use explosion-proof electrical equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe vapors
P264 - Wash hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P301 + P330 + P331 - If swallowed: rinse mouth. Do NOT induce vomiting

DIMETHYLISOPROPOXYALUMINUM

Safety Data Sheet

P303 + P361 + P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
P304 + P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a doctor
P321 - Specific treatment (see first aid instructions on this label)
P335 + P334 - Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages
P363 - Wash contaminated clothing before reuse
P370 + P378 - In case of fire: Use dry chemical powder followed by sand or dolomite to extinguish
P402 + P404 - Store in a dry place. Store in a closed container
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P403 + P235 - Keep in a cool place
P405 - Store locked up
P501 - Dispose of contents/container to licensed waste disposal facility

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Substance type : Mono-constituent
Name : DIMETHYLISOPROPOXYALUMINUM
CAS No : 6063-89-4

Name	Product identifier	%	GHS-US classification
Dimethylisopropoxyaluminum	(CAS No) 6063-89-4	95 - 100	Flam. Liq. 2, H225 Water-react. 2, H261 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

3.2. Mixture

Not applicable

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.
First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.
First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage.
Symptoms/injuries after inhalation : May cause respiratory irritation. Direct respiratory contact is usually not possible, but will cause burns. Inhalation of combustion products can cause irritation.
Symptoms/injuries after skin contact : Causes (severe) skin burns.
Symptoms/injuries after eye contact : Causes serious eye damage.
Symptoms/injuries after ingestion : No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder followed by sand or dolomite.
Unsuitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor. In contact with water releases flammable gases.
Explosion hazard : Container explosion may occur during fire conditions. May form flammable/explosive vapor-air mixture.

DIMETHYLISOPROPOXYALUMINUM

Safety Data Sheet

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Stop release.

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Concentrate containment efforts to adjacent combustibles.
- Methods for cleaning up : Cover with dry chemical extinguishing powder, lime, sand or soda ash. Do not use water. Remove combustible materials in the vicinity of the spill. Allow time for decomposition or fire to burn out, then sweep material and transfer to a suitable container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from any possible contact with water, because of violent reaction and possible flash fire.
- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Provide good ventilation in process area to prevent accumulation of vapors. Protect from moisture. Handle under inert gas. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.
- Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
- Storage conditions : Keep container tightly closed. Keep in a cool place. Protect from moisture. Store in a dry place. Store locked up.
- Incompatible materials : Alkalis. Bromine. Chlorine. Metal salts. Oxidizing agent. Precious metals. Water.
- Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Dimethylisopropoxyaluminum (6063-89-4)		
ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ aluminum alkyls as Al
OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³ aluminum alkyls as Al

8.2. Exposure controls

- Appropriate engineering controls : Glove box or sealed system under inert atmosphere is required. Provide local exhaust or general room ventilation.
- Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
- Hand protection : Neoprene or nitrile rubber gloves.
- Eye protection : Full face shield with chemical workers goggles. Contact lenses should not be worn.

DIMETHYLISOPROPOXYALUMINUM

Safety Data Sheet

Skin and body protection	: Wear suitable protective clothing. Fire resistant laboratory jacket or apron should be worn.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid. Fumes in air.
Molecular mass	: 116.13 g/mol
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
Refractive index	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: < 10 °C
Freezing point	: No data available
Boiling point	: 186 °C
Flash point	: 5 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Vapor pressure	: 10 mm Hg @ 70°C
Relative vapor density at 20 °C	: > 1
Relative density	: 0.828
Solubility	: Reacts violently with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

10.3. Possibility of hazardous reactions

In contact with water releases flammable gases which may ignite spontaneously. Reacts when exposed to alkalis and protic materials such as water and alcohol.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Alkalis. Bromine. Chlorine. Metal salts. Oxidizing agent. Precious metals. Water.

10.6. Hazardous decomposition products

Aluminum oxides. Carbon monoxide. Formaldehyde. Hydrogen. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified

DIMETHYLISOPROPOXYALUMINUM

Safety Data Sheet

Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: Not classified May cause damage to organs through prolonged or repeated exposure
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: May cause respiratory irritation. Direct respiratory contact is usually not possible, but will cause burns. Inhalation of combustion products can cause irritation.
Symptoms/injuries after skin contact	: Causes (severe) skin burns.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: No information available.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects	: This substance may be hazardous to the environment.
Effect on ozone layer	: No additional information available
Effect on the global warming	: No known effects from this product.
GWPMix comment	: No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT)	: 3398
DOT NA no.	UN3398

14.2. UN proper shipping name

Transport document description	: UN3398 Organometallic substance, liquid, water-reactive (DIMETHYLISOPROPOXYALUMINUM), 4.3, II
Proper Shipping Name (DOT)	: Organometallic substance, liquid, water-reactive (DIMETHYLISOPROPOXYALUMINUM)
Class (DOT)	: 4.3 - Class 4.3 - Dangerous when wet material 49 CFR 173.124
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 4.3 - Dangerous when wet



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
---	-------

DIMETHYLISOPROPOXYALUMINUM

Safety Data Sheet

DOT Packaging Bulk (49 CFR 173.xxx) : 243
DOT Packaging Exceptions (49 CFR 173.xxx) : None
DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 135
Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : E - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length, but is prohibited from carriage on passenger vessels in which the limiting number of passengers is exceeded
DOT Vessel Stowage Other : 13 - Keep as dry as reasonably practicable, 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 1 L
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 5 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

DIMETHYLISOPROPOXYALUMINUM (6063-89-4)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States

Dimethylisopropoxyaluminum (6063-89-4)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Full text of H-phrases::

H225	Highly flammable liquid and vapor
H261	In contact with water releases flammable gases
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling.

DIMETHYLISOPROPOXYALUMINUM

Safety Data Sheet

HMIS III Rating

Health	: 4 Severe Hazard - Life-threatening, major or permanent damage may result from single or repeated overexposures
Flammability	: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)
Physical	: 2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at normal temperature and pressure with low risk for explosion. Materials may react violently with water or form peroxides upon exposure to air.

Prepared by safety and environmental affairs.

Date of issue: 09/23/2016 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2016 Gelest Inc. Morrisville, PA 19067

