



ETHYLALUMINUM DICHLORIDE, 1.8M in toluene (24-26 wgt%)

Safety Data Sheet OMAL033.7

Date of issue: 06/08/2015

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Physical state	: Liquid
Product name	: ETHYLALUMINUM DICHLORIDE, 1.8M in toluene (24-26 wgt%)
Product code	: OMAL033.7
Formula	: C ₂ H ₅ AlCl ₂
Synonyms	: EADC
Chemical family	: METAL ALKYL

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Chemical intermediate For research and industrial use only
------------------------------	---

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road
Morrisville, PA 19067
USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)


Flam. Liq. 2	H225
Water-react. 1	H260
Skin Corr. 1B	H314
Eye Dam. 1	H318
Repr. 2	H361
STOT SE 3	H336
STOT RE 2	H373
Aquatic Acute 3	H402

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H225 - Highly flammable liquid and vapor
H260 - In contact with water releases flammable gases which may ignite spontaneously
H314 - Causes severe skin burns and eye damage
H318 - Causes serious eye damage
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs (brain, liver) through prolonged or repeated exposure
H402 - Harmful to aquatic life

Precautionary statements (GHS-US)

: P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P210 - Keep away from heat, sparks, open flames. - No smoking
P223 - Do not allow contact with water
P231+P232 - Handle under inert gas. Protect from moisture
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical equipment

ETHYLALUMINUM DICHLORIDE, 1.8M in toluene (24-26 wgt%)

Safety Data Sheet

P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe vapors
P264 - Wash hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308+P313 - If exposed or concerned: Get medical advice/attention
P310 - Immediately call a POISON CENTER
P335+P334 - Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages
P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use dry chemical powder followed by sand or dolomite to extinguish
P402+P404 - Store in a dry place. Store in a closed container
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Keep in a cool place
P405 - Store locked up
P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Toluene	(CAS No) 108-88-3	73 - 76	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
Ethylaluminum dichloride	(CAS No) 563-43-9	24 - 26	Flam. Liq. 2, H225 Water-react. 1, H260 Skin Corr. 1B, H314 Eye Dam. 1, H318

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
First-aid measures after inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash with plenty of soap and water. Get immediate medical advice/attention.
First-aid measures after eye contact	: Immediately flush eyes thoroughly with water for at least 15 minutes. Get immediate medical advice/attention.
First-aid measures after ingestion	: Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: Causes severe skin burns and eye damage. Causes damage to organs.
Symptoms/injuries after inhalation	: May cause drowsiness or dizziness. Direct respiratory contact is usually not possible, but will cause burns. Inhalation of combustion products can cause irritation. The solvent, toluene, is mildly toxic by inhalation.
Symptoms/injuries after skin contact	: Causes (severe) skin burns.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: Presumed to be a poison.
Chronic symptoms	: The solvent, toluene affects liver and kidney function.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

ETHYLALUMINUM DICHLORIDE, 1.8M in toluene (24-26 wgt%)

Safety Data Sheet

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical powder followed by sand or dolomite.
Unsuitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Highly flammable liquid and vapor. Reacts with water to liberate flammable gas.
Explosion hazard : Container explosion may occur during fire conditions. May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

- Firefighting instructions : If material is ignited, allow to burn. Exercise caution when fighting any chemical fire.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Concentrate containment efforts to adjacent combustibles.
Methods for cleaning up : Cover with dry chemical extinguishing powder, lime, sand or soda ash. Do not use water. Remove combustible materials in the vicinity of the spill. Allow time for decomposition or fire to burn out, then sweep material and transfer to a suitable container for disposal.

6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from any possible contact with water, because of violent reaction and possible flash fire.
Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Protect from moisture. Handle under inert gas. Use only outdoors or in a well-ventilated area. Do not allow contact with water. Use only non-sparking tools. Ground/bond container and receiving equipment. Laboratory and production areas must be equipped with special fire-extinguishing media for organometallics.
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Take precautionary measures against static discharge.
Storage conditions : Store in sealed containers under nitrogen or argon with <10ppm oxygen. Keep container tightly closed. Store in a dry place. Protect from moisture.
Incompatible materials : Alkalis. Bromine. Chlorine. Metal salts. Oxidizing agent. Water.
Prohibitions on mixed storage : Flammable and combustible materials should not be stored in or near working areas for pyrophorics.
Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

- No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Ethylaluminum dichloride (563-43-9)

USA OSHA	OSHA PEL (TWA) (mg/m ³)	2 mg/m ³
----------	-------------------------------------	---------------------

ETHYLALUMINUM DICHLORIDE, 1.8M in toluene (24-26 wgt%)

Safety Data Sheet

Toluene (108-88-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	375 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m³)	560 mg/m³
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
USA IDLH	US IDLH (ppm)	500 ppm

8.2. Exposure controls

Appropriate engineering controls	: Glove box or sealed system under inert atmosphere is required. Provide local exhaust or general room ventilation.
Personal protective equipment	: Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Neoprene or nitrile rubber gloves.
Eye protection	: Full face shield with chemical workers goggles. Contact lenses should not be worn.
Skin and body protection	: Wear suitable protective clothing. Fire resistant laboratory jacket or apron should be worn.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid. Fumes in air.
Molecular mass	: 126.95 g/mol
Color	: No data available
Odor	: No data available
Odor threshold	: No data available
Refractive index	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: 32 °C (neat)
Freezing point	: No data available
Boiling point	: 203 °C
Flash point	: 4 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Vapor pressure	: 1 mm Hg 42°C
Relative vapor density at 20 °C	: > 1
Relative density	: 0.927
Solubility	: Reacts violently with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

ETHYLALUMINUM DICHLORIDE, 1.8M in toluene (24-26 wgt%)

Safety Data Sheet

10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

10.3. Possibility of hazardous reactions

Can ignite spontaneously in contact with air. In contact with water releases flammable gases.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Alkalis. Bromine. Chlorine. Metal salts. Oxidizing agent. Water.

10.6. Hazardous decomposition products

Hydrogen. Formaldehyde. Carbon monoxide. Aluminum oxides. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Toluene (108-88-3)	
LD50 oral rat	2600 mg/kg
LD50 dermal rabbit	12000 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Toluene (108-88-3)	
IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.

Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure) : May cause damage to organs (brain, liver) through prolonged or repeated exposure.
May cause damage to organs through prolonged or repeated exposure

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause drowsiness or dizziness. Direct respiratory contact is usually not possible, but will cause burns. Inhalation of combustion products can cause irritation. The solvent, toluene, is mildly toxic by inhalation.

Symptoms/injuries after skin contact : Causes (severe) skin burns.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : Presumed to be a poison.

Chronic symptoms : The solvent, toluene affects liver and kidney function.

SECTION 12: Ecological information

12.1. Toxicity

Toluene (108-88-3)	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Toluene (108-88-3)	
Log Pow	2.65

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on ozone layer : No additional information available

ETHYLALUMINUM DICHLORIDE, 1.8M in toluene (24-26 wgt%)

Safety Data Sheet

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations. This is a RCRA hazardous waste: 40 CFR 261.21 (i.e. ignitable) 40 CFR 261.23 (i.e. reactive).

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 3399

DOT NA no. : UN3399

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Organometallic substance, liquid, water-reactive, flammable
(ETHYLALUMINUM DICHLORIDE, in toluene)

Department of Transportation (DOT) Hazard Classes : 4.3 - Class 4.3 - Dangerous when wet material 49 CFR 173.124

Hazard labels (DOT) : 4.3 - Dangerous when wet
3 - Flammable liquid



DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : I - Great Danger

DOT Packaging Exceptions (49 CFR 173.xxx) : None

DOT Packaging Non Bulk (49 CFR 173.xxx) : 201

DOT Packaging Bulk (49 CFR 173.xxx) : 244

14.3. Additional information

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters", 52 - Stow "separated from" acids

Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 1 L

SECTION 15: Regulatory information

15.1. US Federal regulations

Ethylaluminum dichloride (563-43-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Toluene (108-88-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Listed on United States SARA Section 313

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

15.2. International regulations

ETHYLALUMINUM DICHLORIDE, 1.8M in toluene (24-26 wgt%)

Safety Data Sheet

Ethylaluminum dichloride (563-43-9)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Canadian DSL (Domestic Substances List)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Toluene (108-88-3)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Canadian DSL (Domestic Substances List)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

15.3. US State regulations

ETHYLALUMINUM DICHLORIDE, 1.8M in toluene (24-26 wgt%)(563-43-9)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

Ethylaluminum dichloride (563-43-9)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	

Toluene (108-88-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	Yes	No	

Toluene (108-88-3)

SECTION 16: Other information

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

Full text of H-phrases::

Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 2	Flammable liquids Category 2
Repr. 2	Reproductive toxicity Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B

ETHYLALUMINUM DICHLORIDE, 1.8M in toluene (24-26 wgt%)

Safety Data Sheet

Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
Water-react. 1	Substances and mixtures which in contact with water emit flammable gases Category 1
H225	Highly flammable liquid and vapor
H260	In contact with water releases flammable gases which may ignite spontaneously
H304	May be fatal if swallowed and enters airways
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H361	Suspected of damaging fertility or the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H402	Harmful to aquatic life

HMIS III Rating

Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	: 4 Severe Hazard
Physical	: 2 Moderate Hazard

Prepared by safety and environmental affairs.

Date of issue: 06/08/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2015 Gelest Inc. Morrisville, PA 19067