

Safety Data Sheet SIA0126.0
Date of issue: 08/23/2016 Version: 1.0

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture
Physical state : Liquid

Product name : 3-(N-ACETYL-4-HYDROXYPROLYLOXY)PROPYLTRIETHOXYSILANE, 25% in ethanol

Product code : SIA0126.0
Formula : C16H31NO7Si

Chemical family : ORGANOSILANE IN SOLVENT

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Chemical intermediate

For research use only

## 1.3. Details of the supplier of the safety data sheet

## GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

## 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

## **GHS-US classification**

Flam. Liq. 2 H225 Eye Irrit. 2A H319 STOT SE 3 H335

Full text of H statements : see section 16

## 2.2. Label elements

## **GHS-US** labeling

Hazard pictograms (GHS-US)





GHS02

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor

H319 - Causes serious eye irritation H335 - May cause respiratory irritation

Precautionary statements (GHS-US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection

P210 - Keep away from heat, open flames, sparks. - No smoking

P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P261 - Avoid breathing vapors

P264 - Wash hands thoroughly after handling P271 - Use only outdoors or in a well-ventilated area

P312 - Call a doctor if you feel unwell

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing

P337+P313 - If eye irritation persists: Get medical advice/attention

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

08/23/2016 EN (English US) SDS ID: **SIA0126.0** Page 1

Safety Data Sheet

P403+P235 - Keep in a cool place

P405 - Store locked up

P501 - Dispose of contents/container to licensed waste disposal facility

#### 2.3. Other hazards

Other hazards not contributing to the classification

: Overexposure to ethanol by skin absorption, inhalation or ingestion may have a narcotic effect (headache, nausea, drowsiness). Ethanol is metabolized to acetaldehyde and acetic acid which in large quantities result in metabolic acidosis, CNS depression and death due to respiratory arrest. This product contains ethanol which is classified as a carcinogen by IARC in alcoholic beverages.

## 2.4. Unknown acute toxicity (GHS US)

No data available

## **SECTION 3: Composition/Information on ingredients**

#### 3.1. Substance

Not applicable

#### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Ethanol	(CAS No) 64-17-5	75 - 80	Flam. Liq. 2, H225 Eye Irrit. 2A, H319
3-(N-Acetyl-4-hydroxyprolyloxy)propyltriethoxysilane	(CAS No) 1300591-79-0	20 - 25	Eye Irrit. 2A, H319 STOT SE 3, H335

# **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

First-aid measures general

: Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact

: Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact

Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion

: Never give anything by mouth to an unconscious person. Get medical advice/attention.

# 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : May cause skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion

: May be harmful if swallowed.

## 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

# **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when

material is exposed to elevated temperatures or open flame.

Explosion hazard : May form flammable/explosive vapor-air mixture.

## 5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

# 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

08/23/2016 EN (English US) SDS ID: **SIA0126.0** 2/7

Safety Data Sheet

#### 6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

## 6.3. Methods and material for containment and cleaning up

For containment

: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams

Methods for cleaning up

: Clean up any spills as soon as possible, using an absorbent material to collect it. Use only non-

sparking tools.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed

: Handle empty containers with care because residual vapors are flammable. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautions for safe handling

: Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.

Hygiene measures

: Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

# 7.2. Conditions for safe storage, including any incompatibilities

Technical measures

: Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.

Storage conditions

Keep container tightly closed. Keep in a cool place. Store locked up.

Incompatible materials

Acids. Alcohols. Oxidizing agent. Peroxides.

Storage area

: Store in a well-ventilated place. Store away from heat.

## 7.3. Specific end use(s)

No additional information available

## **SECTION 8: Exposure controls/personal protection**

# 8.1. Control parameters

Ethanol (64-17-5)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1900 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	3300 ppm (10% LEL)

## 8.2. Exposure controls

Appropriate engineering controls

: Provide local exhaust or general room ventilation.

Personal protective equipment

: Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection

: Neoprene or nitrile rubber gloves.

Eye protection

: Chemical goggles. Contact lenses should not be worn.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor - amine gas (brown cartridge) respirator.

# SECTION 9: Physical and chemical properties

# 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Molecular mass : 377.51 g/mol

08/23/2016 EN (English US) SDS ID: **SIA0126.0** 3/7

# Safety Data Sheet

Color : Straw.

Odor : Mild. Ethanol.

Odor threshold : No data available

Refractive index : No data available

pH : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Melting point : No data available

Freezing point : < 0 °C

Boiling point : 76 °C (initial, ethanol)

Flash point : 15 °C

Auto-ignition temperature : 423 °C (ethanol)

Decomposition temperature : No data available

Flammability (solid, gas) : Highly flammable liquid and vapor Vapor pressure : 42 mm Hg @ 20°C (ethanol)

Relative vapor density at 20 °C : > 1Relative density : 0.872VOC content : > 75 %

Solubility : Reacts with water.

Log Pow : No data available

Log Kow : No data available

Viscosity, kinematic : No data available

Viscosity, dynamic : No data available

Explosive properties : No data available

Oxidizing properties : No data available

Explosion limits : 3.3 - 19 vol % (lower-upper: ethanol)

# 9.2. Other information

No additional information available

# **SECTION 10: Stability and reactivity**

# 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

Stable when stored in sealed containers.

# 10.3. Possibility of hazardous reactions

No additional information available

# 10.4. Conditions to avoid

Heat. Sparks. Open flame.

# 10.5. Incompatible materials

Acids. Alcohols. Oxidizing agent. Peroxides.

## 10.6. Hazardous decomposition products

Organic acid vapors.

# SECTION 11: Toxicological information

# 11.1. Information on toxicological effects

Acute toxicity : Not classified

Ethanol (64-17-5)	
LD50 oral rat	7060 mg/kg
LC50 inhalation rat (mg/l)	124.7 mg/l/4h
LC50 inhalation rat (ppm)	20000 ppm 10 hrs.
LDLo oral rat	1400 mg/kg (Human)
ATE US (oral)	7060.000 mg/kg body weight
ATE US (vapors)	124.700 mg/l/4h
ATE US (dust, mist)	124.700 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

08/23/2016 EN (English US) SDS ID: **SIA0126.0** 4/7

Safety Data Sheet

Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

Ethanol (64-17-5)

IARC group 1 - Carcinogenic to humans

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : May cause respiratory irritation.

Specific target organ toxicity (repeated

exposure)

: Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause respiratory irritation.

Symptoms/injuries after skin contact : May cause skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

Reason for classification : Expert judgment

# **SECTION 12: Ecological information**

## 12.1. Toxicity

Ethanol (64-17-5)	
LC50 fish 1	> 10000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
LC50 fish 2	> 13400 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

## 12.2. Persistence and degradability

No additional information available

## 12.3. Bioaccumulative potential

Ethanol (64-17-5)				
Log Pow	-0.32			

## 12.4. Mobility in soil

No additional information available

# 12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on ozone layer : No additional information available Effect on the global warming : No known effects from this product.

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations.

Dispose of contents/container to licensed waste disposal facility.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

# **SECTION 14: Transport information**

## 14.1. UN number

UN-No.(DOT) : 1993 DOT NA no. UN1993

## 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquids, n.o.s.

(3-(N-ACETYL-4-HYDROXYPROLYLOXY)PROPYLTRIETHOXYSILANE, 25% in ethanol)

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid



08/23/2016 EN (English US) SDS ID: **SIA0126.0** 5/7

# Safety Data Sheet

DOT Symbols : G - Identifies PSN requiring a technical name

Packing group (DOT) : II - Medium Danger

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 202
DOT Packaging Bulk (49 CFR 173.xxx) : 242

#### 14.3. Additional information

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

#### Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this

section is exceeded

## Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

# **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

# 3-(N-ACETYL-4-HYDROXYPROLYLOXY)PROPYLTRIETHOXYSILANE, 25% in ethanol

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States

# Ethanol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

# 3-(N-Acetyl-4-hydroxyprolyloxy)propyltriethoxysilane (1300591-79-0)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2. International regulations

# Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Canadian DSL (Domestic Substances List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican National Inventory of Chemical Substances)

Listed on CICR (Turkish Inventory and Control of Chemicals)

# 3-(N-Acetyl-4-hydroxyprolyloxy)propyltriethoxysilane (1300591-79-0)

## 15.3. US State regulations

3-(N-ACETYL-4-HYDROXYPROLYLOXY)PROPYLTR	IETHOXYSILANE, 25% in ethanol()
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No

08/23/2016 EN (English US) SDS ID: **SIA0126.0** 6/7

Safety Data Sheet

Ethanol (64-17-5)				
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	
		Female	Male	
Yes	Yes	No	No	
3-(N-Acetyl-4-hydroxy	prolyloxy)propyltriethoxysilane	(1300591-79-0)		
U.S California -	U.S California -	U.S California -	U.S California -	Non-significant risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	
_		Female	Male	
		I emale	iviale	

#### Ethanol (64-17-5)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

# **SECTION 16: Other information**

Appreviations and actoriyms	. Abbreviations. Not Determined, No Data, NA. Not Applicable, LD. Lethal Dose, LC. Lethal
	Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm:
	millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV:
	threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and
	Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology

Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation

and Development.

Full text of H-phrases::

H225	Highly flammable liquid and vapor	
H319	Causes serious eye irritation	
H335	May cause respiratory irritation	

## **HMIS III Rating**

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 3 Serious Hazard
Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 08/23/2016 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2016 Gelest Inc. Morrisville, PA 19067

08/23/2016 EN (English US) SDS ID: **SIA0126.0** 7/7