

Safety Data Sheet SIC2464.1 Date of issue: 12/10/2015 Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product form : Substance Physical state : Liquid

Substance name : 3-CYCLOHEXENYLTRIMETHOXYSILANE

Product code · SIC2464 1 Formula : C9H18O3Si

Synonyms : 3-(TRIMETHOXYSILYL)CYCLOHEXENE

: ORGANOMETHOXYSILANE Chemical family

Relevant identified uses of the substance or mixture and uses advised against

: Chemical intermediate Use of the substance/mixture

For research use only

Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazards identification

Classification of the substance or mixture

GHS-US classification

Flam. Liq. 4 H227 Eye Irrit. 2A H319

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H227 - Combustible liquid

H319 - Causes serious eye irritation

P280 - Wear protective gloves/protective clothing/eye protection/face protection Precautionary statements (GHS-US)

P210 - Keep away from heat, open flames, sparks. - No smoking

P264 - Wash hands thoroughly after handling

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P337+P313 - If eye irritation persists: Get medical advice/attention

P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish

P403+P235 - Keep in a cool place

P501 - Dispose of contents/container to licensed waste disposal facility.

2.3. Other hazards

Other hazards not contributing to the

classification

: Additional methanol may be formed by reaction with moisture and water. The US OSHA PEL

(TWA) for methanol is 200 ppm.

24 **Unknown acute toxicity (GHS US)**

No data available

SDS ID: SIC2464.1 12/10/2015 EN (English US) Page 1

Safety Data Sheet

SECTION 3: Composition/Information on ingredients

3.1. Substance

Substance type : Mono-constituent

Name : 3-CYCLOHEXENYLTRIMETHOXYSILANE

CAS No : 21619-76-1

Name	Product identifier	%	GHS-US classification
3-Cyclohexenyltrimethoxysilane	(CAS No) 21619-76-1	95 -	Flam. Liq. 4, H227
		100	Eye Irrit. 2A, H319

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek

medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : May cause skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

Chronic symptoms : Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision. On contact with water this compound liberates methanol which is known to

have a chronic effect on the central nervous system.

4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form methanol. The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid. Irritating fumes and organic acid vapors may develop when material is

exposed to elevated temperatures or open flame.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

12/10/2015 EN (English US) SDS ID: **SIC2464.1** 2/6

Safety Data Sheet

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with

proper protection. For further information refer to section 8: "Exposure controls/personal

protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and

receiving equipment. Provide good ventilation in process area to prevent accumulation of vapors. Use only non-sparking tools.

Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Keep in a cool place.

Incompatible materials : Alcohols. Amines. Oxidizing agent.

Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

Hygiene measures

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Emergency eye wash fountains and safety showers should be available in the immediate

vicinity of any potential exposure. Avoid all unnecessary exposure.

Hand protection : Neoprene or nitrile rubber gloves.

Eye protection : Chemical goggles. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. NIOSH-certified organic vapor (black cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: LiquidAppearance: Clear liquid.Molecular mass: 202.32 g/molColor: Straw.Odor: Mild.

Odor threshold : No data available
Refractive index : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available

Freezing point : $< 0 \, ^{\circ} \text{C}$ Boiling point : $> 205 \, ^{\circ} \text{C}$ Flash point : $> 60 \, ^{\circ} \text{C}$

Auto-ignition temperature : No data available

12/10/2015 EN (English US) SDS ID: **SIC2464.1** 3/6

Safety Data Sheet

Decomposition temperature : No data available Flammability (solid, gas) : Combustible liquid Vapor pressure : < 5 mm Hg @ 25°C

Relative vapor density at 20 °C : >1 Relative density

Solubility Reacts with water. Log Pow : No data available Log Kow No data available Viscosity, kinematic No data available No data available Viscosity, dynamic : No data available Explosive properties Oxidizing properties No data available **Explosion limits** No data available

Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

Chemical stability 10.2.

Stable in sealed containers stored under a dry inert atmosphere.

Possibility of hazardous reactions

Reacts with water and moisture in air, liberating methanol.

Conditions to avoid 10.4.

Heat. Sparks. Open flame.

10.5. Incompatible materials

Alcohols. Amines. Oxidizing agent.

10.6. **Hazardous decomposition products**

Methanol. Organic acid vapors.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity : Not classified Skin corrosion/irritation : Not classified

Serious eye damage/irritation Causes serious eye irritation.

Respiratory or skin sensitization Not classified Germ cell mutagenicity Not classified Carcinogenicity Not classified Reproductive toxicity Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

This material liberates small amounts of methanol on contact with moisture. Material generates methanol on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue.

Symptoms/injuries after inhalation May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : May cause skin irritation. Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes

nausea, vomiting, headache, visual effects including blindness.

: Methanol may effect the central nervous system resulting in persistent or recurring headaches Chronic symptoms

or impaired vision. On contact with water this compound liberates methanol which is known to have a chronic effect on the central nervous system.

Reason for classification : Expert judgment

12/10/2015 SDS ID: SIC2464.1 EN (English US) 4/6

Safety Data Sheet

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations.

Dispose of contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

DOT NA no. NA1993

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.

(3-CYCLOHEXENYLTRIMETHOXYSILANE)

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN

requiring a technical name

Packing group (DOT) : III - Minor Danger

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241

14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : This product is Combustible as defined by the US Department of Transportation (DOT). It is

regulated for transport in the US in container > 119 gallons. The product is not regulated for

transport by the IATA, ADR/RID, ADNR or the IMDG regulations.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

3-CYCLOHEXENYLTRIMETHOXYSILANE (21619-76-1)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR

720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

12/10/2015 EN (English US) SDS ID: **SIC2464.1** 5/6

Safety Data Sheet

3-Cyclohexenyltrimethoxysilane (21619-76-1)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

No additional information available

15.3. US State regulations

3-CYCLOHEXENYLTRIMETHOXYSILANE(21619-76-1)		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	No	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	

3-Cyclohexenyltrimethoxysilane (21619-76-1)

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

SECTION 16: Other information

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

Full text of H-phrases::

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
H227	Combustible liquid
H319	Causes serious eye irritation

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 2 Moderate Hazard Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 12/10/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2015 Gelest Inc. Morrisville, PA 19067

12/10/2015 EN (English US) SDS ID: **SIC2464.1** 6/6