

DICHLOROSILANE, 25% in xylene

Safety Data Sheet SID3368.6

Date of issue: 02/02/2016

Revision date: 06/16/2016

Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form	: Mixture
Physical state	: Liquid
Product name	: DICHLOROSILANE, 25% in xylene
Product code	: SID3368.6
Formula	: H ₂ Cl ₂ Si
Synonyms	: SILICOMETHYLENE CHLORIDE
Chemical family	: CHLOROSILANE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Chemical intermediate For research and industrial use only
------------------------------	---

1.3. Details of the supplier of the safety data sheet**GELEST, INC.**11 East Steel Road
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com**1.4. Emergency telephone number**

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GHS-US classification**

Flam. Liq. 1	H224
Acute Tox. 2 (Inhalation:vapour)	H330
Skin Corr. 1A	H314
Eye Dam. 1	H318
STOT SE 3	H335
STOT RE 2	H373
Aquatic Acute 1	H400

Full text of H statements : see section 16

2.2. Label elements**GHS-US labeling**

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

: H224 - Extremely flammable liquid and vapor
 H314 - Causes severe skin burns and eye damage
 H330 - Fatal if inhaled
 H335 - May cause respiratory irritation
 H373 - May cause damage to organs through prolonged or repeated exposure
 H400 - Very toxic to aquatic life

Precautionary statements (GHS-US)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P210 - Keep away from heat, sparks, open flames. - No smoking
 P310 - Immediately call a doctor
 P240 - Ground/Bond container and receiving equipment
 P241 - Use explosion-proof electrical equipment
 P242 - Use only non-sparking tools
 P243 - Take precautionary measures against static discharge
 P260 - Do not breathe vapors
 P264 - Wash hands thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area
 P273 - Avoid release to the environment

DICHLOROSILANE, 25% in xylene

Safety Data Sheet

P284 - In case of inadequate ventilation wear respiratory protection
P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P314 - Get medical advice/attention if you feel unwell
P320 - Specific treatment is urgent (see first aid instructions on this label)
P363 - Wash contaminated clothing before reuse
P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical to extinguish
P391 - Collect spillage
P403+P233 - Store in a well-ventilated place. Keep container tightly closed
P403+P235 - Keep in a cool place
P405 - Store locked up
P501 - Dispose of contents/container to licensed waste disposal facility

2.3. Other hazards

Other hazards not contributing to the classification : NOTE: Material may form a siloxane polymer on the skin, eyes or in the lungs. Hydrogen chloride may be formed by reaction with water and moisture in air. The US OSHA PEL (TWA) for hydrogen chloride is 5 ppm.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Dichlorosilane	(CAS No) 4109-96-0	75 - 80	Flam. Gas 1, H220 Liquefied gas, H280 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335
Xylene	(CAS No) 1330-20-7	20 - 25	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 1, H400

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.

First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage. May cause damage to organs through prolonged or repeated exposure.

Symptoms/injuries after inhalation : Fatal if inhaled. May cause respiratory irritation. Danger of serious damage to health by prolonged exposure through inhalation.

Symptoms/injuries after skin contact : Causes (severe) skin burns.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

DICHLOROSILANE, 25% in xylene

Safety Data Sheet

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide. Dry chemical. Use of high expansion foam (100:1) is recommended to cover flames.
- Unsuitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable liquid and vapor. Irritating fumes of hydrogen chloride and organic acid vapors may develop when material is exposed to water or open flame.
- Explosion hazard : May form flammable/explosive vapor-air mixture. Explosions of partially hydrolyzed dichlorosilane dispersed on high surface area media have been reported.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use only dry media to extinguish flames. Water spray or fog should only be used to knock down hydrogen chloride vapors in areas downwind from the fire. In case of fire: Stop leak if safe to do so.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

- Protective equipment : Wear protective equipment as described in Section 8.
- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
- Emergency procedures : Stop release.

6.2. Environmental precautions

- Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
- Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Collect spillage. Use only non-sparking tools.

6.4. Reference to other sections

- See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Vapors can ignite spontaneously if heated. (See Autoignition Temperature).
- Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Open carefully. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.
- Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
- Storage conditions : Keep container tightly closed. Store in sealed containers under dry inert atmosphere. Containers can generate pressure during storage. Keep in a cool place. Store locked up.
- Incompatible materials : Acids. Alcohols. Oxidizing agent. Moisture. Water.
- Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

- No additional information available

DICHLOROSILANE, 25% in xylene

Safety Data Sheet

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Xylene (1330-20-7)		
USA ACGIH	ACGIH TWA (ppm)	100 ppm
USA ACGIH	ACGIH STEL (ppm)	150 ppm
USA OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm

8.2. Exposure controls

Appropriate engineering controls	: Provide local exhaust or general room ventilation.
Personal protective equipment	: Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Neoprene or nitrile rubber gloves.
Eye protection	: Chemical goggles or face shield. (Viton recommended). Contact lenses should not be worn.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear liquid.
Molecular mass	: 101.01 g/mol
Color	: Straw.
Odor	: Acrid. Similar to hydrogen chloride.
Odor threshold	: No data available
Refractive index	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: 40
Melting point	: No data available
Freezing point	: -128 °C
Boiling point	: 8.3 °C (initial)
Flash point	: -13 °C
Auto-ignition temperature	: 55 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable liquid and vapor
Vapor pressure	: No data available
Relative vapor density at 20 °C	: > 1
Relative density	: 0.94
VOC content	: > 75 %
Solubility	: Reacts violently with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers stored under a dry inert atmosphere.

DICHLOROSILANE, 25% in xylene

Safety Data Sheet

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating hydrogen chloride. Platinum, platinum and iron salts and other Lewis acids can cause generation of flammable hydrogen gas in the presence of moisture. Forms impact sensitive explosive mixtures with potassium permanganate.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Alcohols. Acids. Moisture. Oxidizing agent. Water.

10.6. Hazardous decomposition products

Hydrogen chloride. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Inhalation:vapour: Fatal if inhaled.

DICHLOROSILANE, 25% in xylene	
ATE US (vapors)	0.625
Xylene (1330-20-7)	
LD50 oral rat	3500 mg/kg ; 4300 mg/kg
LD50 dermal rabbit	1700 mg/kg
LC50 inhalation rat (mg/l)	29.08 mg/l/4h
ATE US (oral)	3500.000 mg/kg body weight
ATE US (dermal)	1700.000 mg/kg body weight
ATE US (vapors)	29.080 mg/l/4h
ATE US (dust, mist)	29.080 mg/l/4h
Additional information	LCLo Inhalation man: 10,000ppm/6H
Dichlorosilane (4109-96-0)	
LC50 inhalation mouse	144 ppm/4h
LC50 inhalation rat	215 ppm
ATE US (gases)	100.000 ppmV/4h
ATE US (vapors)	0.500 mg/l/4h
ATE US (dust, mist)	0.050 mg/l/4h
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

Xylene (1330-20-7)	
IARC group	3 - Not classifiable
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation.
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Fatal if inhaled. May cause respiratory irritation. Danger of serious damage to health by prolonged exposure through inhalation.
Symptoms/injuries after skin contact	: Causes (severe) skin burns.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: May be harmful if swallowed.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Very toxic to aquatic life.

Xylene (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)

DICHLOROSILANE, 25% in xylene

Safety Data Sheet

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Xylene (1330-20-7)	
BCF fish 1	0.6 - 15
Log Pow	2.77 - 3.15

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on ozone layer : No additional information available
Effect on the global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information : Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 2988
DOT NA no. : UN2988

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Chlorosilanes, water-reactive, flammable, corrosive, n.o.s.
(DICHLOROSILANE, 25% in xylene)
Class (DOT) : 4.3 - Class 4.3 - Dangerous when wet material 49 CFR 173.124
Hazard labels (DOT) : 4.3 - Dangerous when wet
3 - Flammable liquid
8 - Corrosive



Packing group (DOT) : I - Great Danger
DOT Packaging Exceptions (49 CFR 173.xxx) : None
DOT Packaging Non Bulk (49 CFR 173.xxx) : 201
DOT Packaging Bulk (49 CFR 173.xxx) : 244

14.3. Additional information

Emergency Response Guide (ERG) Number : 139
Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger vessels in which the limiting number of passengers is exceeded
DOT Vessel Stowage Other : 21 - Segregation same as for flammable liquids, 28 - Stow "away from" flammable liquids, 40 - Stow "clear of living quarters", 49 - Stow "away from" corrosives, 100 - Stow "away from" flammable solids

Air transport

DOT Quantity Limitations Passenger aircraft/rail : Forbidden
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : Forbidden
CFR 175.75)

DICHLOROSILANE, 25% in xylene

Safety Data Sheet

SECTION 15: Regulatory information

15.1. US Federal regulations

Xylene (1330-20-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

Dichlorosilane (4109-96-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 302 Threshold Planning Quantity (TPQ)	10000 lb
---	----------

15.2. International regulations

Xylene (1330-20-7)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Canadian DSL (Domestic Substances List)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Japanese Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

Dichlorosilane (4109-96-0)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on the Canadian DSL (Domestic Substances List)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)

15.3. US State regulations

DICHLOROSILANE, 25% in xylene()

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

Xylene (1330-20-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Dichlorosilane (4109-96-0)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

Xylene (1330-20-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

Dichlorosilane (4109-96-0)

U.S. - New Jersey - Right to Know Hazardous Substance List

DICHLOROSILANE, 25% in xylene

Safety Data Sheet

Dichlorosilane (4109-96-0)

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

Full text of H-phrases::

H220	Extremely flammable gas
H224	Extremely flammable liquid and vapor
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H335	May cause respiratory irritation
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability : 4 Severe Hazard
Physical : 2 Moderate Hazard

Prepared by safety and environmental affairs.

Date of issue: 02/02/2016

Revision date: 06/16/2016

Version: 1.1

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2016 Gelest Inc. Morrisville, PA 19067