

## (2-DIETHYLPHOSPHATOETHYL)METHYLDIETHOXYSILANE, tech-95

### Safety Data Sheet SID3411.0

Date of issue: 12/24/2015

Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product form	: Substance
Physical state	: Liquid
Substance name	: (2-DIETHYLPHOSPHATOETHYL)METHYLDIETHOXYSILANE, tech-95
Product code	: SID3411.0
Formula	: C11H27O5PSi
Synonyms	: DIETHOXYPHOSPHORYLETHYLMETHYLDIETHOXYSILANE; DIETHYL [2-(DIETHOXYMETHYLSILYL)ETHYL]PHOSPHONATE
Chemical family	: ORGANOETHOXYSILANE

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Chemical intermediate For research and industrial use only
------------------------------	---

### 1.3. Details of the supplier of the safety data sheet

**GELEST, INC.**  
 11 East Steel Road  
 Morrisville, PA 19067  
**USA**  
 T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST  
[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)

### 1.4. Emergency telephone number

Emergency number : CHEMTRAC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### GHS-US classification

Flam. Liq. 4 H227  
 Skin Irrit. 2 H315  
 Eye Irrit. 2A H319

Full text of H-phrases: see section 16

### 2.2. Label elements

#### GHS-US labeling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US)	: Warning
Hazard statements (GHS-US)	: H227 - Combustible liquid H315 - Causes skin irritation H319 - Causes serious eye irritation
Precautionary statements (GHS-US)	: P280 - Wear protective gloves/protective clothing/eye protection/face protection P210 - Keep away from heat, open flames, sparks. - No smoking P264 - Wash hands thoroughly after handling P302+P352 - If on skin: Wash with plenty of soap and water P332+P313 - If skin irritation occurs: Get medical advice/attention P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P337+P313 - If eye irritation persists: Get medical advice/attention P321 - Specific treatment (see first aid instructions on this label) P362+P364 - Take off contaminated clothing and wash it before reuse P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish P403+P235 - Keep in a cool place P501 - Dispose of contents/container to licensed waste disposal facility.

### 2.3. Other hazards

Other hazards not contributing to the classification : Additional ethanol may be formed by reaction with moisture and water. The hydrolysis product of this compound is ethanol. Overexposure to ethanol by skin absorption, inhalation or

# (2-DIETHYLPHOSPHATOETHYL)METHYLDIETHOXYSILANE, tech-95

## Safety Data Sheet

ingestion may have a narcotic effect (headache, nausea, drowsiness). Ethanol is metabolized to acetaldehyde and acetic acid which in large quantities result in metabolic acidosis, CNS depression and death due to respiratory arrest. The US OSHA PEL (TWA) for ethanol is 1000 ppm. This product contains ethanol which is classified as a carcinogen by IARC in alcoholic beverages.

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Substance type : Mono-constituent  
Name : (2-DIETHYLPHOSPHATOETHYL)METHYLDIETHOXYSILANE, tech-95  
CAS No : 18048-06-1

Name	Product identifier	%	GHS-US classification
(2-Diethylphosphatoethyl)methyldiethoxysilane	(CAS No) 18048-06-1	95 - 100	Flam. Liq. 4, H227 Skin Irrit. 2, H315 Eye Irrit. 2A, H319

### 3.2. Mixture

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

Chronic symptoms : On contact with water this compound liberates ethanol which is known to have a chronic effect on the central nervous system.

### 4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form ethanol.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

### 5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

# (2-DIETHYLPHOSPHATOETHYL)METHYLDIETHOXYSILANE, tech-95

## Safety Data Sheet

### 6.1.2. For emergency responders

#### Protective equipment

: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

#### For containment

: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

#### Methods for cleaning up

: Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Additional hazards when processed

: Keep away from heat, open flames, sparks. - No smoking.

#### Precautions for safe handling

: Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Provide good ventilation in process area to prevent accumulation of vapors. Use only non-sparking tools.

#### Hygiene measures

: Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage conditions

: Keep container tightly closed. Keep in a cool place.

#### Incompatible materials

: Moisture. Water.

#### Storage area

: Store in a well-ventilated place. Store away from heat.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

No additional information available

### 8.2. Exposure controls

#### Appropriate engineering controls

: Provide local exhaust or general room ventilation.

#### Personal protective equipment

: Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Hand protection

: Neoprene or nitrile rubber gloves.

#### Eye protection

: Chemical goggles. Contact lenses should not be worn.

#### Skin and body protection

: Wear suitable protective clothing.

#### Respiratory protection

: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

: Liquid

#### Appearance

: Clear liquid.

#### Molecular mass

: 298.39 g/mol

#### Color

: Straw.

#### Odor

: Mild.

#### Odor threshold

: No data available

#### Refractive index

: 1.427

#### pH

: No data available

#### Relative evaporation rate (butyl acetate=1)

: No data available

#### Melting point

: No data available

#### Freezing point

: < 0 °C

#### Boiling point

: 124 °C @ 2 mm Hg

#### Flash point

: > 65 °C

# (2-DIETHYLPHOSPHATOETHYL)METHYLDIETHOXYSILANE, tech-95

## Safety Data Sheet

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Combustible liquid
Vapor pressure	: No data available
Relative vapor density at 20 °C	: > 1
Relative density	: 1.02
Solubility	: Soluble in water. Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable in sealed containers.

### 10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating ethanol.

### 10.4. Conditions to avoid

Heat. Sparks. Open flame.

### 10.5. Incompatible materials

Moisture. Water.

### 10.6. Hazardous decomposition products

Ethanol. Organic acid vapors.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### (2-Diethylphosphatoethyl)methyldiethoxysilane (18048-06-1)

LD50 oral rat	1070 µl/kg
LD50 dermal rabbit	6350 µl/kg

Skin corrosion/irritation : Causes skin irritation.

Skin Irritation - rabbit: 10 uL/24H: moderate irritation effect

Serious eye damage/irritation : Causes serious eye irritation.

Eye Irritation - rabbit: 5 uL: severe irritation effect

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : This compound liberates ethanol on contact with moisture. Material generates ethanol on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue.

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

# (2-DIETHYLPHOSPHATOETHYL)METHYLDIETHOXYSILANE, tech-95

## Safety Data Sheet

Chronic symptoms : On contact with water this compound liberates ethanol which is known to have a chronic effect on the central nervous system.

### SECTION 12: Ecological information

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

#### 14.1. UN number

DOT NA no. : NA1993

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : COMBUSTIBLE LIQUID, N.O.S.

((2-DIETHYLPHOSPHATOETHYL)METHYLDIETHOXYSILANE)

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN requiring a technical name

Packing group (DOT) : III - Minor Danger

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Packaging Non Bulk (49 CFR 173.xxx) : 203

DOT Packaging Bulk (49 CFR 173.xxx) : 241

#### 14.3. Additional information

Other information : No supplementary information available.

Special transport precautions : This product is Combustible as defined by the US Department of Transportation (DOT). It is regulated for transport in the US in container > 119 gallons. The product is not regulated for transport by the IATA, ADR/RID, ADNR or the IMDG regulations.

#### Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

#### Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L  
(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### (2-Diethylphosphatoethyl)methyldiethoxysilane (18048-06-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

# (2-DIETHYLPHOSPHATOETHYL)METHYLDIETHOXYSILANE, tech-95

## Safety Data Sheet

### (2-Diethylphosphatoethyl)methyldiethoxysilane (18048-06-1)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### 15.3. US State regulations

#### (2-DIETHYLPHOSPHATOETHYL)METHYLDIETHOXYSILANE, tech-95(18048-06-1)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

#### (2-Diethylphosphatoethyl)methyldiethoxysilane (18048-06-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

## SECTION 16: Other information

### Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

### Full text of H-phrases::

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
H227	Combustible liquid
H315	Causes skin irritation
H319	Causes serious eye irritation

### HMIS III Rating

Health	: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability	: 2 Moderate Hazard
Physical	: 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 12/24/2015

Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2015 Gelest Inc. Morrisville, PA 19067