

Safety Data Sheet SIH5905.0

Date of issue: 01/23/2015 Revision date: 04/18/2017 Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Product name : HEXACHLORODISILANE

Product code : SIH5905.0
Product form : Substance
Physical state : Liquid
Formula : CI6Si2
Synonyms : HCDS

DISILANE HEXACHLORIDE

Chemical family : CHLOROSILANE

1.2. Recommended use of the chemical and restrictions on use

Recommended use : Chemical intermediate

For research and industrial use only

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 4

Skin corrosion/irritation Category 1B

Serious eye damage/eye irritation Category 1

Specific target organ toxicity (single exposure) Category 3

H325

H327

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS05

05 GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H227 - Combustible liquid

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage H335 - May cause respiratory irritation

Precautionary statements (GHS-US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection

P210 - Keep away from heat, open flames, sparks. - No smoking

P260 - Do not breathe vapors

P264 - Wash hands thoroughly after handling P271 - Use only outdoors or in a well-ventilated area

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a doctor

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical to

extinguish

Print date: 04/18/2017 EN (English US) SDS ID: **SIH5905.0** Page 1

Safety Data Sheet

P403+P233 - Store in a well-ventilated place. Keep container tightly closed

P403+P235 - Keep in a cool place

P405 - Store locked up

P501 - Dispose of contents/container to licensed waste disposal facility. P321 - Specific treatment (see first aid instructions on this label)

2.3. Hazards not otherwise classified (HNOC)

Other hazards not contributing to the classification

: NOTE: Material may form a siloxane polymer on the skin, eyes or in the lungs. Hydrogen chloride may be formed by reaction with water and moisture in air. The US OSHA PEL (TWA) for hydrogen chloride is 5 ppm.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Mono-constituent
Name : HEXACHLORODISILANE

CAS-No. : 13465-77-5

Name	Product identifier	%	GHS-US classification
Hexachlorodisilane	(CAS-No.) 13465-77-5	97 - 100	Flam. Liq. 4, H227 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

4.1. Description of first aid measures

First-aid measures general

- : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.
- First-aid measures after inhalation
- Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention.
- First-aid measures after skin contact
- : Wash with plenty of soap and water. Get immediate medical advice/attention.
- First-aid measures after eye contact
- Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
- First-aid measures after ingestion
- : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Causes (severe) skin burns.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

- : Alcohol-resistant foam. Carbon dioxide. Dry chemical. Use of high expansion foam (100:1) is recommended to cover flames.
- Unsuitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

Fire hazard

: Combustible liquid. Irritating fumes of hydrogen chloride and organic acid vapors may develop when material is exposed to water or open flame.

Explosion hazard

When heated at elevated temperatures (>150°C) hexachlorodisilane ignites in air. The following information is provided to assist if hexachlorodisilane is present in a fire situation. On long term storage several incidents of shock sensitive detonations have been reported. In all cases material was stored greater than 1 year and evidence of package seal deterioration and partial hydrolysis were observed. Possible explanations for the shock sensitivity are low level contamination with pentachlorodisilane or the formation of hydridosilanes by HCl addition to the disilane or peroxide formation. Polymeric hydrolysates or gels frequently are associated with shock sensitive behavior.

Print date: 04/18/2017 EN (English US) SDS ID: **SIH5905.0** 2/7

Safety Data Sheet

5.3. Advice for firefighters

Firefighting instructions : Use only dry media to extinguish flames. Water spray or fog should only be used to knock

down hydrogen chloride vapors in areas downwind from the fire. Exercise caution when fighting

any chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with

proper protection. For further information refer to section 8: "Exposure controls/personal

protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Use only non-

sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and

receiving equipment. Provide good ventilation in process area to prevent accumulation of vapors. Use only non-sparking tools.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Store in sealed corrosion resistant containers. Inspect containers

regularly for integrity. May form explosive byproducts on extended storage. It is recommended that bottles be stored in a dry inert environment and that in no case should material be stored

for greater than one year. Keep in a cool place. Store locked up.

Incompatible materials : Acids. Alcohols. Oxidizing agent.

Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be

available in the immediate vicinity of any potential exposure.

Hand protection : Neoprene or nitrile rubber gloves.

Eye protection : Chemical goggles or face shield. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge)

respirator.

Print date: 04/18/2017 EN (English US) SDS ID: **SIH5905.0** 3/7

Safety Data Sheet

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Molecular mass : 268.89 g/mol
Color : Straw.

Odor : Acrid. Similar to hydrogen chloride.

Odor threshold : No data available

Refractive index : 1.475

pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available

Freezing point : < -1 °C

Boiling point : 144 - 146 °C

Flash point : 78 °C

Auto-ignition temperature : 320 °C

Decomposition temperature : No data available
Flammability (solid, gas) : Combustible liquid
Vapor pressure : 110 mm Hg @ 85°C

Relative vapor density at 20 $^{\circ}$ C : > 5 Relative density : 1.562 VOC content : 100 $^{\circ}$

Solubility : Reacts violently with water.

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available

Explosion limits : 7 - 70 vol % (lower; upper)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed corrosion resistant containers stored under a dry inert atmosphere.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating hydrogen chloride.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Acids. Alcohols. Oxidizing agent.

10.6. Hazardous decomposition products

Hydrogen chloride. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified

Print date: 04/18/2017 EN (English US) SDS ID: SIH5905.0 4/7

Safety Data Sheet

Carcinogenicity : Not classified

None of the components in this product at concentrations >0.1% are listed by IARC, NTP,

OSHA or ACGIH as a carcinogen.

Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause respiratory irritation.

Symptoms/effects after skin contact : Causes (severe) skin burns.

Symptoms/effects after eye contact : Causes serious eye damage.

Symptoms/effects after ingestion : May be harmful if swallowed.

Reason for classification : Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on ozone layer : No additional information available

Effect on the global warming : No known effects from this product.

GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 2987 DOT NA no. UN2987

14.2. UN proper shipping name

Transport document description : UN2987 Chlorosilanes, corrosive, n.o.s. (HEXACHLORODISILANE), 8, II

Proper Shipping Name (DOT) : Chlorosilanes, corrosive, n.o.s.

(HEXACHLORODISILANE)

Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136

Packing group (DOT) : II - Medium Danger Hazard labels (DOT) : 8 - Corrosive



DOT Packaging Non Bulk (49 CFR 173.xxx) : 206
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Packaging Exceptions (49 CFR 173.xxx) : None

Print date: 04/18/2017 EN (English US) SDS ID: SIH5905.0 5/7

Safety Data Sheet

14.3. Additional information

Emergency Response Guide (ERG) Number : 156

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : C - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Air transport

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

Hexachlorodisilane (13465-77-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Hexachlorodisilane (13465-77-5)

Listed on the Canadian NDSL (Non-Domestic Substances List)

EU-Regulations

Hexachlorodisilane (13465-77-5)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Hexachlorodisilane (13465-77-5)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

15.3. US State regulations

No additional information available

SECTION 16: Other information

Full text of H-phrases::

H227	Combustible liquid	
H314	Causes severe skin burns and eye damage	
H318	Causes serious eye damage	
H335	May cause respiratory irritation	

Abbreviations and acronyms

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling.

Hazard Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Print date: 04/18/2017 EN (English US) SDS ID: **SIH5905.0** 6/7

Safety Data Sheet

Flammability

 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 F and boiling points above 100 F. as well as liquids with flash points between 73 F and 100 F. (Classes IB & IC)

Physical

: 2 Moderate Hazard - Materials that are unstable and may undergo violent chemical changes at normal temperature and pressure with low risk for explosion. Materials may react violently with water or form peroxides upon exposure to air.

Prepared by safety and environmental affairs.


Date of issue: 01/23/2015 Revision date: 04/18/2017 Version: 2.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2017 Gelest Inc. Morrisville, PA 19067



Print date: 04/18/2017 EN (English US) SDS ID: SIH5905.0 7/7