

**3-ISOCYANATOPROPYLMETHYLDIETHOXSILANE, 95%**

Safety Data Sheet SII6454.45

Date of issue: 01/29/2016

Version: 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Product form	: Substance
Physical state	: Liquid
Substance name	: 3-ISOCYANATOPROPYLMETHYLDIETHOXSILANE, 95%
Product code	: SII6454.45
Formula	: C ₉ H ₁₉ NO ₃ Si
Synonyms	: METHYLDIETHOXSILYLPROPYLISOCYANATE; 3-(DIETHOXSILYL)PROPYL ISOCYANATE
Chemical family	: ORGANOETHOXSILANE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture	: Chemical intermediate For research use only
------------------------------	--

1.3. Details of the supplier of the safety data sheet**GELEST, INC.**

11 East Steel Road
Morrisville, PA 19067
USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com**1.4. Emergency telephone number**

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****GHS-US classification**

Skin Corr. 1C H314
Eye Dam. 1 H318

Full text of H statements : see section 16

2.2. Label elements**GHS-US labeling**

Hazard pictograms (GHS-US)



GHS05

Signal word (GHS-US)	: Danger
Hazard statements (GHS-US)	: H314 - Causes severe skin burns and eye damage
Precautionary statements (GHS-US)	: P280 - Wear protective gloves/protective clothing/eye protection/face protection P260 - Do not breathe vapors P264 - Wash hands thoroughly after handling P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P310 - Immediately call a doctor P321 - Specific treatment (see first aid instructions on this label) P363 - Wash contaminated clothing before reuse P405 - Store locked up P501 - Dispose of contents/container to licensed waste disposal facility

2.3. Other hazards

Other hazards not contributing to the classification	: Additional ethanol may be formed by reaction with moisture and water. The hydrolysis product of this compound is ethanol. Overexposure to ethanol by skin absorption, inhalation or ingestion may have a narcotic effect (headache, nausea, drowsiness). Ethanol is metabolized to acetaldehyde and acetic acid which in large quantities result in metabolic acidosis, CNS
--	---

3-ISOCYANATOPROPYLMETHYLDIETHOXSILANE, 95%

Safety Data Sheet

depression and death due to respiratory arrest. The US OSHA PEL (TWA) for ethanol is 1000 ppm. This product contains ethanol which is classified as a carcinogen by IARC in alcoholic beverages.

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Substance type : Mono-constituent
Name : 3-ISOCYANATOPROPYLMETHYLDIETHOXSILANE, 95%
CAS No : 33491-28-0

Name	Product identifier	%	GHS-US classification
3-Isocyanatopropylmethyldiethoxysilane	(CAS No) 33491-28-0	95 - 100	Skin Corr. 1C, H314 Eye Dam. 1, H318

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes severe skin burns and eye damage.

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : Causes (severe) skin burns. Skin contact may cause sensitization or an allergic reaction.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : May be harmful if swallowed.

Chronic symptoms : On contact with water this compound liberates ethanol which is known to have a chronic effect on the central nervous system.

4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form ethanol.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

Reactivity : Can react exothermically with amines.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

3-ISOCYANATOPROPYLMETHYLDIETHOXSILANE, 95%

Safety Data Sheet

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in process area to prevent accumulation of vapors.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep container tightly closed. Keep in a cool place. Store locked up.

Incompatible materials : Amines. Moisture. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection : Neoprene or nitrile rubber gloves.

Eye protection : Chemical goggles or face shield. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor - gas (yellow cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear liquid.

Molecular mass : 217.34 g/mol

Color : Straw.

Odor : Mild.

Odor threshold : No data available

Refractive index : No data available

pH : No data available

Relative evaporation rate (butyl acetate=1) : < 1

Melting point : No data available

Freezing point : < 0 °C

Boiling point : 110 - 115 °C @ 10 mm Hg

Flash point : > 65 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

3-ISOCYANATOPROPYLMETHYLDIETHOXYSIANE, 95%

Safety Data Sheet

Vapor pressure	: < 1 mm Hg @ 20°C
Relative vapor density at 20 °C	: > 1
Relative density	: No data available
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Can react exothermically with amines.

10.2. Chemical stability

Stable in sealed containers.

10.3. Possibility of hazardous reactions

Reacts with water and moisture in air, liberating ethanol. Hazardous polymerization may occur at temperatures exceeding 150°C.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

Amines. Moisture. Water.

10.6. Hazardous decomposition products

Ethanol. Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: This compound liberates ethanol on contact with moisture. Material generates ethanol on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue.
Symptoms/injuries after inhalation	: May cause irritation to the respiratory tract.
Symptoms/injuries after skin contact	: Causes (severe) skin burns. Skin contact may cause sensitization or an allergic reaction.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: May be harmful if swallowed.
Chronic symptoms	: On contact with water this compound liberates ethanol which is known to have a chronic effect on the central nervous system.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

3-ISOCYANATOPROPYLMETHYLDIETHOXSILANE, 95%

Safety Data Sheet

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.
Effect on ozone layer : No additional information available
Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.
Waste disposal recommendations : May be incinerated. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 1760
DOT NA no. UN1760

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Corrosive liquids, n.o.s.
(3-ISOCYANATOPROPYLMETHYLDIETHOXSILANE)
Class (DOT) : 8 - Class 8 - Corrosive material 49 CFR 173.136
Hazard labels (DOT) : 8 - Corrosive



DOT Symbols : G - Identifies PSN requiring a technical name
Packing group (DOT) : III - Minor Danger
DOT Packaging Exceptions (49 CFR 173.xxx) : 154
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 241

14.3. Additional information

Emergency Response Guide (ERG) Number : 154
Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 : 60 L
CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

3-ISOCYANATOPROPYLMETHYLDIETHOXSILANE, 95% (33491-28-0)

TSCA Exemption/Exclusion	CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States
--------------------------	--

3-ISOCYANATOPROPYLMETHYLDIETHOXSILANE, 95%

Safety Data Sheet

3-Isocyanatopropylmethyldiethoxysilane (33491-28-0)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

3-Isocyanatopropylmethyldiethoxysilane (33491-28-0)

Listed on the Japanese ISHL (Industrial Safety and Health Law)

15.3. US State regulations

3-ISOCYANATOPROPYLMETHYLDIETHOXSILANE, 95%(33491-28-0)

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

3-Isocyanatopropylmethyldiethoxysilane (33491-28-0)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

SECTION 16: Other information

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

Full text of H-phrases::

H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability : 2 Moderate Hazard
Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 01/29/2016 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2016 Gelest Inc. Morrisville, PA 19067