

Safety Data Sheet SIN6597.07

Date of issue: 01/13/2015 Revision date: 04/17/2017 Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Product name : NEOPENTASILANE
Product code : SIN6597.07
Product form : Substance
Physical state : Liquid
Formula : H12Si5

Synonyms : TETRASILYLSILANE

2,2-DISILYLTRISILANE

Chemical family : SILANE

1.2. Recommended use of the chemical and restrictions on use

Recommended use : Chemical intermediate For research use only

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 2
Pyrophoric liquids Category 1
Skin corrosion/irritation Category 1A
Serious eye damage/eye irritation Category 1
Specific target organ toxicity (single exposure) Category 3
H335

Full text of H statements: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)







GHS02

GHS05

GHS07

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor

H250 - Catches fire spontaneously if exposed to air H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage H335 - May cause respiratory irritation

Precautionary statements (GHS-US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection

P260 - Do not breathe vapors P310 - Immediately call a doctor

P264 - Wash hands thoroughly after handling

P210 - Keep away from heat, open flames, sparks. - No smoking

P222 - Do not allow contact with air

P240 - Ground/Bond container and receiving equipment P241 - Use explosion-proof electrical equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P370+P378 - In case of fire: Use alcohol resistant foam, carbon dioxide, dry chemical to

extinguish

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

Print date: 04/17/2017 EN (English US) SDS ID: **SIN6597.07** Page 1

Safety Data Sheet

P302+P334 - If on skin: Immerse in cool water/wrap with wet bandages

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P363 - Wash contaminated clothing before reuse

P233 - Keep container tightly closed

P271 - Use only outdoors or in a well-ventilated area

P403+P235 - Keep in a cool place

P405 - Store locked up

P422 - Store contents under dry inert atmosphere

P501 - Dispose of contents/container to licensed waste disposal facility.

P321 - Specific treatment (see first aid instructions on this label)

P312 - Call a doctor if you feel unwell

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Multi-constituent

Name : NEOPENTASILANE

CAS-No. : 15947-57-6

Name	Product identifier	%	GHS-US classification
Neopentasilane	(CAS-No.) 15947-57-6	98 - 100	Flam. Liq. 2, H225 Pyr. Liq. 1, H250 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335
Isotetrasilane	(CAS-No.) 13597-87-0	0 - 2	Flam. Liq. 2, H225 Pyr. Liq. 1, H250 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately

call a poison center or doctor/physician.

First-aid measures after skin contact : Immerse in cool water/wrap in wet bandages. Wash with plenty of soap and water. Get

immediate medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Immediately call a poison center or

doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Causes severe skin burns and eye damage.

Symptoms/effects after inhalation : May cause respiratory irritation. Overexposure may cause: Severe. Tissue damage.

Symptoms/effects after skin contact : Causes (severe) skin burns.

Symptoms/effects after eye contact : Causes serious eye damage. At levels below the flammability limit, silane is expected to affect

the eyes by absorption and deposition of silicon dioxide, causing severe irritation and possible

corneal damage.

Symptoms/effects after ingestion : May be harmful if swallowed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

Print date: 04/17/2017 EN (English US) SDS ID: SIN6597.07 2/7

Safety Data Sheet

SECTION 5: Firefighting measures

Extinguishing media

Suitable extinguishing media

: If unable to stop the flow of gas, neopentasilane should be allowed to burn until consumed. Secondary fires may be extinguished with alcohol resistant foam, carbon dioxide, dry chemical. Use of high expansion foam (100:1) is recommended to cover flames.

Unsuitable extinguishing media : Water.

Special hazards arising from the substance or mixture

Fire hazard

: Catches fire spontaneously if exposed to air. Highly flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when material is exposed to water or open flame.

Advice for firefighters

Firefighting instructions

: Neopentasilane should be allowed to burn until consumed. Excessive pressure may develop in gas cylinders exposed to fire-heated may explode on contact with air. Cool cylinders and surroundings with water from a suitable distance. Exercise caution when fighting any chemical fire. In case of fire: Stop leak if safe to do so.

Protection during firefighting

Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist.

Other information : NEOPENTASILANE will spontaneously ignite on contact with air. Pyrophoric liquid and gas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment

: Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment

: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".

Emergency procedures : Stop leak if safe to do so.

6.2 **Environmental precautions**

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and material for containment and cleaning up 6.3.

Methods for cleaning up

: Stop flow of gas if possible. Evacuate area. The potential exists for spontaneous ignition and explosion. Allow vapors to disperse. Ventilate area.

Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

Precautions for safe handling

Additional hazards when processed

: Catches fire spontaneously if exposed to air. Handle empty containers with care because residual vapors are flammable.

Precautions for safe handling

Containers must be properly grounded before beginning transfer. Handle only in sealed purged systems. Prevent reverse flow. Provide good ventilation in process area to prevent accumulation of vapors. Do not allow contact with air. Do not breathe vapors. Systems utilizing silane that do not involve complete consumption of silane should be equipped with burn boxes. See- Book of SEMI Standards, Facilities Standards and Safety Guidelines, Mountain View, CA, Semiconductor Equipment and Materials Int'l. 1993.

Hygiene measures

Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Conditions for safe storage, including any incompatibilities

Technical measures

: Store contents under dry inert atmosphere.

Storage conditions

: Keep container tightly closed. Store in sealed cylinders in isolated area.

Incompatible materials

: Acids. Alcohols. Oxidizing agent. Water.

Storage area Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. **Control parameters**

Isotetrasilane (13597-87-0)		
ACGIH	ACGIH TWA (ppm)	5 ppm (silane)

SDS ID: SIN6597.07 Print date: 04/17/2017 EN (English US) 3/7

Safety Data Sheet

Neopentasilane (15947-57-6)		
ACGIH	ACGIH TWA (ppm)	5 ppm (silane)

8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be

available in the immediate vicinity of any potential exposure.

Hand protection : Neoprene or nitrile rubber gloves.

Eye protection : Chemical goggles or face shield. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge)

respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear. Pyrophoric liquid.

152.52 g/mol Molecular mass Color Colorless Odor Disagreeable. Odor threshold No data available Refractive index No data available рΗ No data available Relative evaporation rate (butyl acetate=1) No data available Melting point No data available

Freezing point : < 0 °C

Boiling point : 132 - 134 °C

Flash point : < -40 °C

Auto-ignition temperature : < 50 °C

Decomposition temperature : No data available

Flammability (solid, gas) : Catches fire spontaneously if exposed to air, Highly flammable liquid and vapor

Vapor pressure : 15 mm Hg @ 25°C

Relative vapor density at 20 °C : > 1Relative density : 0.793VOC content : 100 %

Solubility : Insoluble in water. Reacts with water.

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosion limits : < 2 vol % (LEL)

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed cylinders stored under a dry inert atmosphere.

10.3. Possibility of hazardous reactions

Reacts with oxygen in air, igniting spontaneously. Mixtures with mercury explode when shaken in the presence of air. Platinum, platinum and iron salts and other Lewis acids can cause generation of flammable hydrogen gas.

Print date: 04/17/2017 EN (English US) SDS ID: SIN6597.07 4/7

Safety Data Sheet

10.4. Conditions to avoid

Open flame. Heat. Sparks. Do not allow contact with air.

10.5. Incompatible materials

Acids. Alcohols. Oxidizing agent. Water.

10.6. Hazardous decomposition products

Silicon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitization : Not classified Germ cell mutagenicity : Not classified Carcinogenicity : Not classified

None of the components in this product at concentrations >0.1% are listed by IARC, NTP,

OSHA or ACGIH as a carcinogen.

Reproductive toxicity : Not classified

STOT-single exposure : May cause respiratory irritation.

STOT-repeated exposure : Not classified
Aspiration hazard : Not classified

Symptoms/effects after inhalation : May cause respiratory irritation. Overexposure may cause: Severe. Tissue damage.

Symptoms/effects after skin contact : Causes (severe) skin burns.

Symptoms/effects after eye contact : Causes serious eye damage. At levels below the flammability limit, silane is expected to affect

the eyes by absorption and deposition of silicon dioxide, causing severe irritation and possible corneal damage.

comear damage.

Symptoms/effects after ingestion : May be harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on ozone layer : No additional information available

Effect on the global warming : No known effects from this product.

GWPmix comment : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 3194

Print date: 04/17/2017 EN (English US) SDS ID: SIN6597.07 5/7

Safety Data Sheet

DOT NA no. UN3194

14.2. UN proper shipping name

Transport document description : UN3194 Pyrophoric liquid, inorganic, n.o.s. (NEOPENTASILANE), 4.2, I

Proper Shipping Name (DOT) : Pyrophoric liquid, inorganic, n.o.s.

(NEOPENTASILANE)

Class (DOT) : 4.2 - Class 4.2 - Spontaneously combustible material 49 CFR 173.124

Packing group (DOT) : I - Great Danger

Hazard labels (DOT) : 4.2 - Spontaneously combustible



DOT Packaging Non Bulk (49 CFR 173.xxx) : 181

DOT Packaging Bulk (49 CFR 173.xxx) : 244

DOT Packaging Exceptions (49 CFR 173.xxx) : None

DOT Symbols : G - Identifies PSN requiring a technical name

14.3. Additional information

Emergency Response Guide (ERG) Number : 135

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel

carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 13 - Keep as dry as reasonably practicable,78 - Stow "separated longitudinally by an

intervening complete compartment or hold from" explosives

Air transport

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : Forbidden

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

NEOPE	EN I ASILAN	NE (1594	(-5/-6)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

Isotetrasilane (13597-87-0)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Neopentasilane (15947-57-6)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

Print date: 04/17/2017 EN (English US) SDS ID: SIN6597.07 6/7

Safety Data Sheet

SECTION 16: Other information

Full text of H-phrases::

H225	Highly flammable liquid and vapor
H250	Catches fire spontaneously if exposed to air
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling.

Hazard Rating

Physical

: 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is Health

: 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below

Flammability 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)

> : 3 Serious Hazard - Materials that may form explosive mixtures with water and are capable of detonation or explosive reaction in the presence of a strong initiating source. Materials may polymerize, decompose, self-react, or undergo other chemical change at normal temperature and pressure with moderate risk of explosion

Prepared by safety and environmental affairs.

Date of issue: 01/13/2015 Revision date: 04/17/2017 Version: 2.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2017 Gelest Inc. Morrisville, PA 19067

SDS ID: SIN6597.07 Print date: 04/17/2017 EN (English US) 7/7