

3-(N-STYRYLMETHYL-2-AMINOETHYLAMINO)PROPYL TRIMETHOXYSILANE, 40% in methanol

Safety Data Sheet SIS6993.0

Date of issue: 08/28/2015

Revision date: 10/14/2016

Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Product name	: 3-(N-STYRYLMETHYL-2-AMINOETHYLAMINO)PROPYL TRIMETHOXYSILANE, 40% in methanol
Product code	: SIS6993.0
Product form	: Mixture
Physical state	: Liquid
Formula	: C17H30N2O3Si
Synonyms	: VINYLBENZYL(TRIMETHOXYSILYL)PROPYLETHANEDIAMINE
Chemical family	: ORGANOSILANE IN SOLVENT

1.2. Recommended use of the chemical and restrictions on use

Recommended use	: Chemical intermediate For research and industrial use only
-----------------	---

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road
Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number	: CHEMTRAC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 2	H225
Acute toxicity (oral) Category 3	H301
Acute toxicity (dermal) Category 3	H311
Acute toxicity (inhalation:vapor) Category 3	H331
Skin corrosion/irritation Category 2	H315
Serious eye damage/eye irritation Category 1	H318
Specific target organ toxicity (single exposure) Category 1	H370
Specific target organ toxicity (single exposure) Category 3	H336

Full text of H statements : see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)



Signal word (GHS-US)

: Danger

Hazard statements (GHS-US)

- : H225 - Highly flammable liquid and vapor
- H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled
- H315 - Causes skin irritation
- H318 - Causes serious eye damage
- H336 - May cause drowsiness or dizziness
- H370 - Causes damage to organs

Precautionary statements (GHS-US)

- : P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P307 + P311 - If exposed: Call a poison center/doctor
- P210 - Keep away from heat, sparks, open flames, hot surfaces. - No smoking
- P240 - Ground/Bond container and receiving equipment
- P241 - Use explosion-proof electrical equipment
- P242 - Use only non-sparking tools
- P243 - Take precautionary measures against static discharge
- P260 - Do not breathe vapors
- P261 - Avoid breathing vapors

3-(N-STYRYLMETHYL-2-AMINOETHYLAMINO)PROPYL TRIMETHOXYSILANE, 40% in methanol

Safety Data Sheet

P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P330 - Rinse mouth
P301 + P310 - If swallowed: Immediately call a POISON CENTER
P303 + P361 + P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P304 + P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P310 - Immediately call a POISON CENTER
P321 - Specific treatment (see first aid instructions on this label)
P362 + P364 - Take off contaminated clothing and wash it before reuse
P363 - Wash contaminated clothing before reuse
P370 + P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P403 + P235 - Keep in a cool place
P405 - Store locked up
P501 - Dispose of contents/container to licensed waste disposal facility

2.3. Hazards not otherwise classified (HNOC)

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
Methanol	(CAS No) 67-56-1	>= 60	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation:vapour), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370 STOT SE 3, H336
3-(N-Styrylmethyl-2-aminoethylamino)propyltrimethoxysilane	(CAS No) 94516-44-6	< 40	Skin Irrit. 2, H315 Eye Irrit. 2A, H319

Full text of hazard classes and H-statements : see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a poison center or doctor/physician.

First-aid measures after skin contact : Remove/take off immediately all contaminated clothing. Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Causes damage to organs.

Symptoms/injuries after inhalation : Toxic if inhaled. Danger of serious damage to health by prolonged exposure through inhalation. May cause drowsiness or dizziness. Overexposure may cause: Nausea. Headache. Visual disturbances. Cough.

Symptoms/injuries after skin contact : Toxic in contact with skin. Causes skin irritation. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

Symptoms/injuries after eye contact : Causes serious eye damage.

3-(N-STYRYLMETHYL-2-AMINOETHYLAMINO)PROPYL TRIMETHOXYSILANE, 40% in methanol

Safety Data Sheet

Symptoms/injuries after ingestion	: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard. Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea, vomiting, headache, visual effects including blindness.
Chronic symptoms	: Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision. The solvent, methanol, probably determines toxicity. Ingestion of methanol can cause blindness and death.

4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: The combination of visual disturbances, metabolic acidosis and formic acid in urine is evidence of methanol poisoning. The therapeutic intravenous administration of ethanol (10 mls/hour) allows methanol to be preferentially oxidized and reduces production of methanol metabolites. Acidosis must be treated with intravenous administration of sodium bicarbonate and methanol elimination may be increased by hemodialysis, as indicated. Treatment should be based on blood methanol levels and acid-base balance.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Foam. Carbon dioxide. Dry chemical.
Unsuitable extinguishing media	: Do not use straight streams.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.
Explosion hazard	: May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions	: Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Eliminate every possible source of ignition. Use special care to avoid static electric charges.
6.1.1. For non-emergency personnel	
Protective equipment	: Wear protective equipment as described in Section 8.

Emergency procedures

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	--

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment	: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.
Methods for cleaning up	: Clean up any spills as soon as possible, using an absorbent material to collect it. Use only non-sparking tools.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Handle empty containers with care because residual vapors are flammable. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Precautions for safe handling	: Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Provide good ventilation in process area to prevent accumulation of vapors. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.
Hygiene measures	: Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.
Storage conditions	: Keep container tightly closed. Store in sealed containers in the dark below 10°C. Store locked up. Keep in a cool place.

3-(N-STYRYLMETHYL-2-AMINOETHYLAMINO)PROPYL TRIMETHOXYSILANE, 40% in methanol

Safety Data Sheet

Incompatible materials : Acids. Alcohols. Oxidizing agent. Peroxides.
Storage area : Store in a well-ventilated place. Store away from heat.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methanol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
IDLH	US IDLH (ppm)	6000 ppm
NIOSH	NIOSH REL (TWA) (mg/m ³)	260 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	325 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm

8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.
Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Hand protection : Neoprene or nitrile rubber gloves.
Eye protection : Chemical goggles or face shield. Contact lenses should not be worn.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified combination organic vapor - amine gas (brown cartridge) respirator.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Molecular mass	: 338.52 g/mol
Color	: Straw. Amber.
Odor	: Mild. Amine. Ammonia-like.
Odor threshold	: No data available
Refractive index	: 1.39
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: < 0 °C
Boiling point	: 65 °C (initial, methanol)
Flash point	: 11 °C
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Highly flammable liquid and vapor
Vapor pressure	: 95 mm Hg @ 25°C
Relative vapor density at 20 °C	: > 1
Relative density	: 0.871
VOC content	: < 40 %
Solubility	: Partially. Soluble in water. Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available

3-(N-STYRYLMETHYL-2-AMINOETHYLAMINO)PROPYL TRIMETHOXYSILANE, 40% in methanol

Safety Data Sheet

Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed containers stored in the dark below 10°C.

10.3. Possibility of hazardous reactions

Non-hazardous polymerization can occur.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Acids. Alcohols. Oxidizing agent. Peroxides.

10.6. Hazardous decomposition products

Organic acid vapors.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Toxic if swallowed. Dermal: Toxic in contact with skin. Inhalation:vapour: Toxic if inhaled.

3-(N-STYRYLMETHYL-2-AMINOETHYLAMINO)PROPYL TRIMETHOXYSILANE, 40% in methanol	
ATE US (oral)	166.667 mg/kg body weight
ATE US (dermal)	500.000 mg/kg body weight
ATE US (vapors)	5.000 mg/l/4h

Methanol (67-56-1)

LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)
ATE US (oral)	100.000 mg/kg body weight
ATE US (dermal)	300.000 mg/kg body weight
ATE US (vapors)	3.000 mg/l/4h

Skin corrosion/irritation

: Causes skin irritation.

Serious eye damage/irritation

: Causes serious eye damage.

Respiratory or skin sensitization

: Not classified

Germ cell mutagenicity

: Not classified

Carcinogenicity

: Not classified
None of the components in this product at concentrations >0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen

Reproductive toxicity

: Not classified

Specific target organ toxicity (single exposure)

: Causes damage to organs. May cause drowsiness or dizziness.

Specific target organ toxicity (repeated exposure)

: Not classified

Aspiration hazard

: Not classified

Symptoms/injuries after inhalation

: Toxic if inhaled. Danger of serious damage to health by prolonged exposure through inhalation. May cause drowsiness or dizziness. Overexposure may cause: Nausea. Headache. Visual disturbances. Cough.

Symptoms/injuries after skin contact

: Toxic in contact with skin. Causes skin irritation. Repeated exposure to this material can result in absorption through skin causing significant health hazard.

Symptoms/injuries after eye contact

: Causes serious eye damage.

Symptoms/injuries after ingestion

: Toxic if swallowed. Swallowing a small quantity of this material will result in serious health hazard. Oral toxicity is associated with methanol, the solvent and a hydrolysis product which causes nausea, vomiting, headache, visual effects including blindness.

3-(N-STYRYLMETHYL-2-AMINOETHYLAMINO)PROPYL TRIMETHOXYSILANE, 40% in methanol

Safety Data Sheet

Chronic symptoms	: Methanol may effect the central nervous system resulting in persistent or recurring headaches or impaired vision. The solvent, methanol, probably determines toxicity. Ingestion of methanol can cause blindness and death.
Reason for classification	: Expert judgment

SECTION 12: Ecological information

12.1. Toxicity

Methanol (67-56-1)	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

Methanol (67-56-1)	
BCF fish 1	< 10
Log Pow	-0.77

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Other adverse effects	: This substance may be hazardous to the environment.
Effect on ozone layer	: No additional information available
Effect on the global warming	: No known effects from this product.
GWPmix comment	: No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT)	: 1230
DOT NA no.	UN1230

14.2. UN proper shipping name

Transport document description	: UN1230 Methanol (METHANOL SOLUTION), 3 (6.1), II
Proper Shipping Name (DOT)	: Methanol (METHANOL SOLUTION)
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: II - Medium Danger
Hazard labels (DOT)	: 3 - Flammable liquid 6.1 - Poison



DOT Packaging Non Bulk (49 CFR 173.xxx)	: 202
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Symbols	: + - Fixes (cannot be altered) proper shipping name, hazard class, and packing group,I - Proper shipping name appropriate for international and domestic transportation

3-(N-STYRYLMETHYL-2-AMINOETHYLAMINO)PROPYL TRIMETHOXYSILANE, 40% in methanol

Safety Data Sheet

14.3. Additional information

Emergency Response Guide (ERG) Number : 131
Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded
DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 1 L
(49 CFR 173.27)
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L

SECTION 15: Regulatory information

15.1. US Federal regulations

Methanol (67-56-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

SARA Section 313 - Emission Reporting 1.0 %

3-(N-Styrylmethyl-2-aminoethylamino)propyltrimethoxysilane (94516-44-6)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

Methanol (67-56-1)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 1 Subdivision B - Toxic material causing immediate and serious toxic effects Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	---

EU-Regulations

Methanol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

National regulations

Methanol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory
Listed on the Korean ECL (Existing Chemicals List)
Listed on NZIoC (New Zealand Inventory of Chemicals)
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)
Japanese Poisonous and Deleterious Substances Control Law
Listed on the Canadian IDL (Ingredient Disclosure List)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

Methanol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	Yes	No	No	

3-(N-STYRYLMETHYL-2-AMINOETHYLAMINO)PROPYL TRIMETHOXYSILANE, 40% in methanol

Safety Data Sheet

Methanol (67-56-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases::

H225	Highly flammable liquid and vapor
H301	Toxic if swallowed
H311	Toxic in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H336	May cause drowsiness or dizziness
H370	Causes damage to organs

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development; GHS: The Globally Harmonized System of Classification and Labelling.

HMIS III Rating

Health
Flammability
Physical

- : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
- : 4 Severe Hazard - Flammable gases, or very volatile flammable liquids with flash points below 73 F, and boiling points below 100 F. Materials may ignite spontaneously with air. (Class IA)
- : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Prepared by safety and environmental affairs.

Date of issue: 08/28/2015

Revision date: 10/14/2016

Version: 2.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2016 Gelest Inc. Morrisville, PA 19067