

GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067
Phone: (215) 547-1015

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **ZIRCONIUM DIMETHACRYLATE DIBUTOXIDE 25% - AKZ949**

CHEMICAL NAME: ZIRCONIUM DIMETHACRYLATE DIBUTOXIDE

SYNONYMS: DI-n-BUTOXYZIRCONIUM DIMETHACRYLATE

CHEMICAL FAMILY: ZIRCONIUM ALKOXIDE

FORMULA: C₁₆H₂₈O₆Zr

HMIS CODES HEALTH: 3 FLAMMABILITY: 4 REACTIVITY: 1

INGREDIENTS

IDENTITY	CAS NO.	%	TLV	OSHA
ZIRCONIUM DIMETHACRYLATE DIBUTOXIDE	not found	<30	not established	
n-BUTANOL	71-36-3	>35	(Zr = TWA: 5mg/m ³)	5mg/m ³
TOLUENE	108-88-3	>25	TWA: 50ppm (skin) 100ppm	100ppm 200ppm

PHYSICAL DATA

Boiling Point: 111° - initial (toluene)	Melting Point: not determined
Specific Gravity: not determined	Vapor Pressure @ 20°: <10mm
Vapor Density: 2.6 (n-butanol)	Solubility in water: reacts
% volatiles: >20%	Evaporation rate: NA
Molecular Weight: 379.55	
Appearance & Color: Light amber liquid, characteristic odor	

FIRE & EXPLOSION DATA

Flash Point, COC: 29°C (84°F) Autoignition Temp.: not determined
Flammability Limits-(n-butanol) LEL: 1.4% UEL: 11.2%

Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical.
Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.
Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

-1-(AKZ949)

ENVIRONMENTAL INFORMATION

Spill response: Sweep material and transfer to a suitable container for disposal.

Recommended Disposal: Absorb onto clay or vermiculite. Dispose of as solid waste. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

NOTE: Material may form zirconium oxides or zirconate polymers on the skin, eyes or in the lungs. Prolonged exposure to zirconium compounds can induce formation of granulomatous lesions in the lungs or on the skin. n-Butanol is metabolized to butanoic acid and 3-hydroxybutanoic acid which may result in ketosis or ketoacidosis.

Eye Contact: Will cause immediate or delayed severe eye irritation.

Skin contact: May produce irritation or contact dermatitis. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation may irritate the respiratory tract.

Oral Toxicity: not determined
Chronic Toxicity: not determined

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Administer oxygen if needed. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

REACTIVITY DATA

Stability: Stable

Conditions to avoid: Material decomposes slowly in contact with water.

Hazardous decomposition products: Organic acid vapors, butanol and zirconium oxide fumes.

-2-(AKZ949)

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, NIOSH approved dust and mist respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research use only.

Storage and Handling: Store in sealed containers.

TRANSPORTATION

DOT SHIPPING NAME: FLAMMABLE LIQUID, N.O.S (CONTAINS n-BUTANOL)

DOT HAZARD CLASS: 3

DOT LABEL: FLAMMABLE LIQUID

DOT ID No: UN1993

PG III

Prepared by safety and environmental affairs

ISSUE DATE AKZ949: 3/17/03

SUPERSEDES: 9/28/01

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.