

**STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE**

Safety Data Sheet DSRTI50

Date of issue: 10/09/2015

Version: 1.0

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form	: Mixture
Physical state	: Liquid
Product name	: STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE
Product code	: DSRTI50
Formula	: SrTi(OR) <sub>x</sub>
Synonyms	: STRONTIUM TITANIUM; DOUBLE METAL ALKOXIDE OF STRONTIUM AND TITANIUM; STRONTIUM TITANIUM ALKOXIDE
Chemical family	: METAL ALKOXIDE

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture	: Chemical intermediate For research use only
------------------------------	--

**1.3. Details of the supplier of the safety data sheet****GELEST, INC.**11 East Steel Road  
Morrisville, PA 19067**USA**

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

[info@gelest.com](mailto:info@gelest.com) - [www.gelest.com](http://www.gelest.com)**1.4. Emergency telephone number**

Emergency number	: CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)
------------------	---

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****GHS-US classification**Flam. Liq. 3 H226  
Skin Irrit. 2 H315  
Eye Irrit. 2A H319  
STOT SE 3 H336

Full text of H-phrases: see section 16

**2.2. Label elements****GHS-US labeling**

Hazard pictograms (GHS-US)



GHS02

GHS07

Signal word (GHS-US)

: Warning

Hazard statements (GHS-US)

: H226 - Flammable liquid and vapor  
H315 - Causes skin irritation  
H319 - Causes serious eye irritation  
H336 - May cause drowsiness or dizziness

Precautionary statements (GHS-US)

: P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P210 - Keep away from heat, open flames, sparks. - No smoking  
P240 - Ground/bond container and receiving equipment  
P241 - Use explosion-proof electrical equipment  
P242 - Use only non-sparking tools  
P243 - Take precautionary measures against static discharge  
P261 - Avoid breathing vapors  
P264 - Wash hands thoroughly after handling  
P271 - Use only outdoors or in a well-ventilated area  
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse skin with water/shower  
P332+P313 - If skin irritation occurs: Get medical advice/attention  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

# STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE

## Safety Data Sheet

P337+P313 - If eye irritation persists: Get medical advice/attention  
P312 - Call a doctor if you feel unwell  
P321 - Specific treatment (see first aid instructions on this label)  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish  
P403+P233 - Store in a well-ventilated place. Keep container tightly closed  
P403+P235 - Keep in a cool place  
P405 - Store locked up  
P501 - Dispose of contents/container to licensed waste disposal facility.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

No data available

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	GHS-US classification
Methoxypropanol	(CAS No) 107-98-2	75 - 80	Flam. Liq. 3, H226 Eye Irrit. 2A, H319 STOT SE 3, H336
n-Butanol	(CAS No) 71-36-3	20 - 25	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Strontium *	(CAS No) Trade Secret	6.4 - 6.6	Not classified
Titanium*	(CAS No) Trade Secret	3.5 - 3.6	Not classified

\*The specific chemical identity, CAS number and/or exact concentration is withheld as a trade secret per applicable regulations and statutes.

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause drowsiness or dizziness. May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : Causes skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : May be harmful if swallowed.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Do not use straight streams.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

### 5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray to cool exposed surfaces.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

# STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE

## Safety Data Sheet

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate ignition sources. Use special care to avoid static electric charges.

##### 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : For further information refer to section 8: "Exposure controls/personal protection". Equip cleanup crew with proper protection. Do not attempt to take action without suitable protective equipment.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or shovel spills into appropriate container for disposal. Use only non-sparking tools.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Use only outdoors or in a well-ventilated area. Use only non-sparking tools.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof electrical equipment.

Storage conditions : Keep container tightly closed. Keep in a cool place. Store locked up.

Incompatible materials : Oxidizing agent. Water.

Storage area : Store in a well-ventilated place. Store away from heat.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Methoxypropanol (107-98-2)		
USA ACGIH	ACGIH TWA (ppm)	50 ppm
USA ACGIH	ACGIH STEL (ppm)	100 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	360 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
USA NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	540 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
n-Butanol (71-36-3)		
USA ACGIH	ACGIH TWA (ppm)	20 ppm
USA NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
USA NIOSH	NIOSH REL (ceiling) (ppm)	50 ppm
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA IDLH	US IDLH (ppm)	1400 ppm (10% LEL)

# STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE

## Safety Data Sheet

### 8.2. Exposure controls

Appropriate engineering controls	: Provide local exhaust or general room ventilation.
Personal protective equipment	: Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.
Hand protection	: Neoprene or nitrile rubber gloves.
Eye protection	: Chemical goggles. Contact lenses should not be worn.
Skin and body protection	: Wear suitable protective clothing.
Respiratory protection	: Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. NIOSH-certified organic vapor (black cartridge) respirator.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Straw. Dark.
Odor	: Mild.
Odor threshold	: No data available
Refractive index	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: < 0 °C
Boiling point	: 117 °C initial
Flash point	: 39 °C
Auto-ignition temperature	: 365 °C n-butanol)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Flammable liquid and vapor
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 0.95 - 1
VOC content	: > 25 %
Solubility	: Reacts with water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosion limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Stable in sealed containers.

### 10.3. Possibility of hazardous reactions

Moisture or water will slowly decompose product.

### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

### 10.5. Incompatible materials

Oxidizing agent. Water.

### 10.6. Hazardous decomposition products

Strontium oxides. Organic acid vapors. Titanium oxides.

# STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE

## Safety Data Sheet

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>Methoxypropanol (107-98-2)</b>	
LC50 inhalation rat (mg/l)	> 6 mg/l/4h
<b>n-Butanol (71-36-3)</b>	
LD50 oral rat	700 mg/kg
LD50 dermal rabbit	3402 mg/kg
LC50 inhalation rat (ppm)	> 8000 ppm/4h
ATE US (oral)	700.000 mg/kg body weight
ATE US (dermal)	3402.000 mg/kg body weight

Skin corrosion/irritation : Causes skin irritation.  
Serious eye damage/irritation : Causes serious eye irritation.  
Respiratory or skin sensitization : Not classified  
Germ cell mutagenicity : Not classified  
Carcinogenicity : Not classified  
Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : May cause drowsiness or dizziness.  
Specific target organ toxicity (repeated exposure) : Not classified  
Aspiration hazard : Not classified  
Symptoms/injuries after inhalation : May cause drowsiness or dizziness. May cause irritation to the respiratory tract.  
Symptoms/injuries after skin contact : Causes skin irritation.  
Symptoms/injuries after eye contact : Causes serious eye irritation.  
Symptoms/injuries after ingestion : May be harmful if swallowed.  
Reason for classification : Expert judgment

### SECTION 12: Ecological information

#### 12.1. Toxicity

<b>Methoxypropanol (107-98-2)</b>	
LC50 fish 1	20.8 g/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23300 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>n-Butanol (71-36-3)</b>	
LC50 fish 1	1730 - 1910 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	1983 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	1740 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 2	1897 - 2072 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

<b>Methoxypropanol (107-98-2)</b>	
BCF fish 1	< 2
Log Pow	-0.437
<b>n-Butanol (71-36-3)</b>	
BCF fish 1	0.64
Log Pow	0.785 (at 25 °C)

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.  
Effect on ozone layer : No additional information available  
Effect on the global warming : No known ecological damage caused by this product.

# STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE

## Safety Data Sheet

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Sewage disposal recommendations	: Do not dispose of waste into sewer.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to licensed waste disposal facility.
Additional information	: Handle empty containers with care because residual vapors are flammable.
Ecology - waste materials	: Avoid release to the environment.

### SECTION 14: Transport information

#### 14.1. UN number

UN-No.(DOT)	: 1993
DOT NA no.	UN1993

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT)	: Flammable liquids, n.o.s. (STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE)
Transport hazard class(es) (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid



DOT Symbols	: G - Identifies PSN requiring a technical name
Packing group (DOT)	: III - Minor Danger
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242

#### 14.3. Additional information

Other information	: No supplementary information available.
-------------------	---

#### Transport by sea

DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
-----------------------------	---

#### Air transport

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L

### SECTION 15: Regulatory information

#### 15.1. US Federal regulations

##### STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE

TSCA Exemption/Exclusion	CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.
--------------------------	---

##### Methoxypropanol (107-98-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

##### n-Butanol (71-36-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory  
Subject to reporting requirements of United States SARA Section 313

EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA. Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.
--------------------------	--

SARA Section 313 - Emission Reporting	1.0 %
---------------------------------------	-------

#### 15.2. International regulations

# STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE

## Safety Data Sheet

### Methoxypropanol (107-98-2)

Listed on the AICS (Australian Inventory of Chemical Substances)  
 Listed on the Canadian DSL (Domestic Substances List)  
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Listed on the Korean ECL (Existing Chemicals List)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Listed on the Canadian IDL (Ingredient Disclosure List)  
 Listed on INSQ (Mexican national Inventory of Chemical Substances)  
 Listed on Turkish inventory of chemical

### n-Butanol (71-36-3)

Listed on the AICS (Australian Inventory of Chemical Substances)  
 Listed on the Canadian DSL (Domestic Substances List)  
 Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
 Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)  
 Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
 Listed on the Japanese ISHL (Industrial Safety and Health Law)  
 Listed on the Korean ECL (Existing Chemicals List)  
 Listed on NZIoC (New Zealand Inventory of Chemicals)  
 Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
 Listed on the Canadian IDL (Ingredient Disclosure List)  
 Listed on INSQ (Mexican national Inventory of Chemical Substances)  
 Listed on Turkish inventory of chemical

### 15.3. US State regulations

#### STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE()

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

#### Methoxypropanol (107-98-2)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### n-Butanol (71-36-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### Titanium

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### Strontium

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### n-Butanol (71-36-3)

# STRONTIUM TITANIUM DOUBLE METAL ALKOXIDE

## Safety Data Sheet

### SECTION 16: Other information

#### Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemical Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

#### Full text of H-phrases::

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

#### HMIS III Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur  
Flammability : 3 Serious Hazard  
Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 10/09/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

*The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.*

© 2015 Gelest Inc. Morrisville, PA 19067