GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067 Phone: (215) 547-1015

MATERIAL SAFETY DATA SHEET EMERGENCY TELEPHONE CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: TANTALUM PENTABROMIDE - INTA070				
CHEMICAL NAME: TANTALUM PENTABROMIDE				
SYNONYMS: PENTABROMOTANTALUM; TANTALUM V BROMIDE				
CHEMICAL FAMILY: INORGANIC HALIDE				
FORMULA: TaBr ₅				
HMIS CODES	HEALTH: 3	FLAMMABILITY: 0	REACTIVITY: 1	

INGREDIENTS

IDENTITY TANTALUM PENTABROMIDE CAS NO. 13451-11-1 % TLV >95 not established

PHYSICAL DATA

Boiling Point: 348-9°C Specific Gravity: 4.67 Vapor Density (air=1): >1 % volatiles N/A Molecular Weight: 580.49 Appearance & Color: Orange Melting Point: 265° Vapor Pressure, 215°: 10mm Solubility in water: reacts Evaporation rate: N/A Other: N/A

Appearance & Color: Orange crystalline solid with acrid odor of hydrogen bromide.

FIRE & EXPLOSION DATA

Flash Point, COC: Not Flammable Autoignition Temp.: NA Flammability Limits- LEL: NA UEL: NA

Extinguishing Media: NA

Special Fire Fighting Procedures: (Note, since tantalum bromide is not flammable, precautions refer to mixtures with flammable materials.) Avoid eye and skin contact. Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Irritating fumes and acid vapors may develop when material is exposed to elevated temperatures or open flame.

-1-(INTA070)

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemcial Abstract Service Registration Number Gelest, Inc. © 2008

ENVIRONMENTAL INFORMATION

Spill response: May be hazardous to aquatic life if released to open waters. Cover spill with absorbent material. Transfer to a suitable container for disposal.

Recommended Disposal: Dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: Will cause immediate or delayed severe damage to eye tissue.

Skin contact: Will produce tissue damage or irritation or contact dermatitis which may be delayed several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects. Prolonged absorption of bromides may produce skin rashes, running nose, headache, mucous membrane irritation, anemia, loss of weight and depression.

Inhalation: Inhalation of vapors or particulates of tantalum halides will irritate the respiratory tract. Overexposure may produce coughing, headache and nausea. Inhalation of large amounts is expected to cause necrosis of tracheal epithelium, bronchitis and interstitial pneumonia.

Oral Toxicity: Not determined.

Acute Toxicity: Not determined

Chronic Toxicity: There are no known chronic effects related to this compound.

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water. *Note to physician:* Reacts with water to form hydrobromic acid, consequently treatment for acid burns may be considered.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

REACTIVITY DATA

Stability: Stable

Incompatibility (materials to avoid): Reacts with water and moisture in air liberating hydrogen bromide.

Hazardous decomposition products: Acid vapors, hydrogen bromide -2-(INTA070)

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemcial Abstract Service Registration Number Gelest, Inc. © 2008

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended. Respiratory Protection: If exposure exceeds TLV air-supplied or acid gas respirator. Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses. Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store in sealed containers. Avoid contact with water.

TRANSPORTATION				
DOT SHIPPING NAME: CORROSIVE S	SOLD, N.O.S. (TANTALUM PENTABROMIDE)			
DOT HAZARD CLASS: 8 DOT LABEL: CORROSIVE DOT ID No: UN1759	PG: III			
Prepared by safety and environmental a	affairs ISSUE DATE INTA070: 4/7/03 SUPERSEDES: 6/11/99			

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.

-3-(INTA070)

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemcial Abstract Service Registration Number Gelest, Inc. © 2008