

**GELEST, INC.**

11 East Steel Rd. Morrisville, PA 19067  
Phone: (215) 547-1015

MATERIAL SAFETY  
DATA SHEET

EMERGENCY TELEPHONE  
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **TRIIISOBUTYLALUMINUM - OMAL082**

CHEMICAL NAME: TRIISOBUTYLALUMINUM

SYNONYMS: TRIS(2-METHYLBUTYL)ALUMINUM

CHEMICAL FAMILY: METAL ALKYL

FORMULA: C<sub>12</sub>H<sub>27</sub>Al

HMIS CODES HEALTH: 4 FLAMMABILITY: 4 REACTIVITY: 2

**INGREDIENTS**

IDENTITY	CAS NO.	%	TLV	OSHA PEL
TRIIISOBUTYLALUMINUM	100-99-2	>95	not established	not established (PEL and TLV for aluminum alkyls as Al: 2mg/m <sup>3</sup> )

**PHYSICAL DATA**

Boiling Point: 73°C @ 5mm

Specific Gravity: 0.78

Vapor Density (air =1): >1

% volatiles: NA

Molecular Weight: 199.83

Appearance & Color: Clear liquid, fumes and ignites in air

Melting Point: 4°C

Vapor Pressure: <1mm

Solubility in water: reacts violently

Evaporation rate: NA

Other: NA

**FIRE & EXPLOSION DATA**

**Can spontaneously ignite on contact with air. Pyrophoric liquid and gas.**

Flash Point, COC: -1°C (-18°F)

Autoignition Temp.: -40°C - PYROPHORIC

Flammability Limits: not determined

Extinguishing Media: Dry chemical powder followed by sand or dolomite. Do not use water.

Special Fire Fighting Procedures: If material is ignited, allow to burn. Concentrate containment efforts to adjacent combustibles. Avoid eye and skin contact. Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Container explosion may occur during fire conditions.

-1-(OMAL082)

## ENVIRONMENTAL INFORMATION

Spill response: Cover with dry chemical extinguishing powder, lime, sand or soda ash. Do not use water. Remove sources of ignition. Remove combustible materials in the vicinity of the spill. Allow time for decomposition or fire to burn out, then sweep material and transfer to a suitable container for disposal.

Recommended Disposal: Incinerate. Follow all chemical pollution control regulations. This is a RCRA hazardous waste: 40 CFR 261.21 (i.e. ignitable) 40 CFR 261.23 (i.e. reactive)

## HEALTH HAZARD DATA

Eye Contact: Will cause immediate or delayed severe burns to the eyes.

Skin contact: Will cause irritation and burns.

Inhalation: Direct respiratory contact is usually not possible, but will cause burns. Inhalation of combustion products can cause irritation

Oral Toxicity: Not determined

Chronic Toxicity: There are no known chronic effects related to this compound.

Chronic Toxicity: not determined

## SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Administer oxygen if needed. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. To conscious individual give one full cup of water to dilute ingested material. Get medical attention.

## REACTIVITY DATA

Stability: Stable in sealed containers under dry inert atmosphere. The product can generate small amounts of hydrogen when exposed to alkalis and protic materials such as water and alcohol.

Decomposes at temperatures >140°C.

Conditions to avoid: Store away from alkalis, oxidizers, metal salts, precious metals, chlorine, bromine.

Hazardous decomposition products: Hydrogen, formaldehyde, carbon monoxide, organic acid vapors and aluminum oxides, isobutylene.

-2-(OMAL082)

## SPECIAL PROTECTION INFORMATION

Ventilation: Glove box or sealed system under inert atmosphere is required. Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, NIOSH approved organic vapor respirator.

Eye and Face Protection: Full face shield with chemical workers goggles.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. Fire resistant laboratory jacket or apron. An eyewash and emergency shower should be available. Launder clothing before reuse.

## OTHER PRECAUTIONS

For research and industrial use only. Only personnel fully trained in the handling of pyrophoric materials should be permitted to work with this material.

Storage and Handling: Store in sealed containers.

Laboratory and production areas must be equipped with special fire-extinguishing media for pyrophorics. Flammable and combustible materials should not be stored in or near working areas for pyrophorics.

## TRANSPORTATION

DOT SHIPPING NAME: ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE

(TRIISOBUTYLALUMINUM)

DOT HAZARD CLASS: 4.2 SUB: 4.3

DOT LABEL: Spontaneously Combustible

DOT ID No: UN3394 PG: I

Air transport and UPS forbidden.

Prepared by safety and environmental affairs MSDS ISSUE DATE: OMAL082: 4/10/14  
SUPERSEDES: 9/30/08

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

-3-(OMAL082)

© 2014 Gelest Inc. Morrisville, PA 19067