

**GELEST, INC.**

11 East Steel Rd. Morrisville, PA 19067  
Phone: (215) 547-1015

MATERIAL SAFETY  
DATA SHEET

EMERGENCY TELEPHONE  
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **TRIIISOBUTYLALUMINUM, 0.7M in heptane - OMAL082.2**

CHEMICAL NAME: TRIISOBUTYLALUMINUM, 0.7M in heptane

SYNONYMS: TRIISOBUTYLALANE

CHEMICAL FAMILY: METAL ALKYL

FORMULA: C<sub>12</sub>H<sub>27</sub>Al

HMIS CODES HEALTH: 3 FLAMMABILITY: 4 REACTIVITY: 1

**INGREDIENTS**

IDENTITY	CAS NO.	%	TLV	OSHA PEL
TRIIISOBUTYLALUMINUM	100-99-2	18-22	2mg/m <sup>3</sup>	2mg/m <sup>3</sup>
HEPTANE	142-82-5	78-82	400ppm	400ppm (STEL: 500ppm)

**PHYSICAL DATA**

Boiling Point: 98° - initial (heptane)

for pure compound: 73°C @ 5mm (neat) Melting Point: 4°C (neat)

Specific Gravity: 0.688

Vapor Pressure: <1mm

Vapor Density (air =1): >1

Solubility in water: reacts violently

% volatiles: NA

Evaporation rate: NA

Molecular Weight: 198.33

Other: NA

Appearance & Color: Clear liquid, fumes in air

**FIRE & EXPLOSION DATA**

**If heated, can spontaneously ignite on contact with air.**

Flash Point, CC: -4°C (25°F)

Autoignition Temp.: <150°C

Flammability Limits: not determined

Extinguishing Media: Dry chemical powder followed by sand or dolomite. Do not use water.

Special Fire Fighting Procedures: If material is ignited, allow to burn. Concentrate containment efforts to adjacent combustibles. Avoid eye and skin contact. Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Container explosion may occur during fire conditions.

-1-(OMAL082.2)

## ENVIRONMENTAL INFORMATION

Spill response: Cover with dry chemical extinguishing powder, lime, sand or soda ash. Do not use water. Remove sources of ignition. Remove combustible materials in the vicinity of the spill. Allow time for decomposition or fire to burn out, then sweep material and transfer to a suitable container for disposal.

Recommended Disposal: Incinerate. Follow all chemical pollution control regulations. This is a RCRA hazardous waste: 40 CFR 261.21 (i.e. ignitable) 40 CFR 261.23 (1.e. reactive)

## HEALTH HAZARD DATA

Eye Contact: Will cause immediate or delayed severe burns to the eyes.

Skin contact: Will cause irritation and burns.

Inhalation: Direct respiratory contact is usually not possible, but will cause burns. Inhalation of combustion products can cause irritation. Vapor inhalation of heptane may lead to impairment of coordination mental alertness, and reaction times, leading to accident proneness. Exposure to levels around 500ppm leads to narcotic effects including nausea, headache and mental confusion. Particulates or vapor of the contained resin will irritate the respiratory tract. Overexposure may produce coughing, headache and nausea.

Oral Toxicity: Not determined - presumed to be a poison.

Chronic Toxicity: There are no known chronic effects related to this compound. Target organs presumed to be brain and liver.

### SUGGESTED FIRST AID

**EYES:** In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

**SKIN:** Flush with water, then wash with soap and water.

**INHALATION:** Move exposed individual to fresh air. Administer oxygen if needed. Call a physician.

**INGESTION:** Never give fluids or induce vomiting if patient is unconscious or having convulsions. To conscious individual give one full cup of water to dilute ingested material. Get medical attention.

## REACTIVITY DATA

Stability: Stable in sealed containers under dry inert atmosphere. The product can generate small amounts of hydrogen when exposed to alkalis and protic materials such as water and alcohol.

Conditions to avoid: Store away from alkalis, oxidizers, metal salts, water, chlorine, bromine

Hazardous decomposition products: Hydrogen, formaldehyde, carbon monoxide, organic acid vapors and aluminum oxides.

-2-(OMAL082.2)

## SPECIAL PROTECTION INFORMATION

Ventilation: Glove box or sealed system under inert atmosphere is required. Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, NIOSH approved organic vapor respirator.

Eye and Face Protection: Full face shield with chemical workers goggles.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. Fire resistant laboratory jacket or apron should be worn. An eyewash and emergency shower located away from the point of use should be available. Launder clothing before reuse.

## OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store in sealed containers under nitrogen or argon with <10ppm oxygen.

Laboratory and production areas must be equipped with special fire-extinguishing media for pyrophorics. Flammable and combustible materials should not be stored in or near working areas for pyrophorics.

## TRANSPORTATION

DOT SHIPPING NAME: ORGANOMETALLIC SUBSTANCE, LIQUID, WATER-REACTIVE, FLAMMABLE, N.O.S. (TRIIISOBTYLALUMINUM)

DOT HAZARD CLASS: 4.3 SUB:3

DOT LABEL: DANGEROUS WHEN WET, FLAMMABLE LIQUID

DOT ID No: UN3399 PG: I

Air transport and UPS forbidden.

Prepared by safety and environmental affairs      MSDS ISSUE DATE: OMAL082.2: 1/12/15  
SUPERSEDES: none

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

-3-(OMAL082.2)

© 2015 Gelest Inc. Morrisville, PA 19067