

GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067
Phone: (215) 547-1015

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **LEAD TITANATE - PBL6465**

CHEMICAL NAME: LEAD TITANATE

SYNONYMS: LEAD TITANIUM OXIDE

CHEMICAL FAMILY: LEAD COMPOUND

FORMULA: O₃TiPb

HMIS CODES HEALTH: 2 FLAMMABILITY: 0 REACTIVITY: 0

INGREDIENTS

IDENTITY	CAS NO.	%	TLV
LEAD TITANATE	12060-00-3	>95	0.15 mg/m ³ as lead (PEL: 50 mg/m ³)

PHYSICAL DATA

Boiling Point: N/A

Specific Gravity: 7.52

Vapor Density: NA

% volatiles: <1

Molecular Weight: 303.09

Appearance & Color: Off-white to pale yellow powder

Melting Point: >700°

Vapor Pressure, 20°: <0.001mm

Solubility in water, NA

Evaporation rate: NA

Other: N/A

FIRE & EXPLOSION DATA

Flash Point, COC: not flammable Autoignition Temp.: not ignitable

Flammability Limits- LEL: NA UEL: NA

Extinguishing Media: Not combustible

Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe dust, particles or inhale vapors.

Unusual Fire and Explosion Hazards: None known.

-1-(PBL6465)

ENVIRONMENTAL INFORMATION

Spill response: May be hazardous to aquatic life if released to open waters. Sweep material and transfer to a suitable container for disposal.

Recommended Disposal: Dispose of as solid waste. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: May cause immediate or delayed severe eye irritation.

Skin contact: May produce irritation or contact dermatitis which may be delayed several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation of dust or particulates will irritate the respiratory tract.

Toxicity - ipr-rat, LD50: 2000 mg/kg

Chronic Toxicity: Exposure to dust or fumes of lead compounds is known to cause toxic effects. Lead is a cumulative poison.

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Administer oxygen if needed. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention. *Physician note: Diagnostic mobilization of lead with calcium EDTA may be useful in questionable cases.*

REACTIVITY DATA

Stability: Stable

Conditions to avoid: At high temperatures >300°C can liberate lead oxide fumes

Hazardous decomposition products: Lead oxide fumes.

-2-(PBL6465)

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, NIOSH approved dust and mist respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For industrial and research use only.

Storage and Handling: Store in sealed containers.

TRANSPORTATION

DOT SHIPPING NAME: None required

DOT HAZARD CLASS: None required

DOT LABEL: None required

DOT ID No: None required

OTHER APPLICABLE REGULATIONS

This product contains a lead compound which is subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and 40CFR 372.

Prepared by safety and environmental affairs ISSUE DATE PBL6465: 11/24/03
SUPERSEDES: 1/15/92

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.

-3-(PBL6465)