

# **GELEST, INC.**

11 East Steel Rd. Morrisville, PA 19067 Phone: (215) 547-1015

MATERIAL SAFETY DATA SHEET

EMERGENCY TELEPHONE CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **ALLYLDIMETHYL(DIISOPROPYLAMINO)SILANE - SIA0461.0** 

CHEMICAL NAME: ALLYLDIMETHYL(DIISOPROPYLAMINO)SILANE

SYNONYMS: ALLYL(DIISOPROPYLAMINO)DIMETHYLSILANE

CHEMICAL FAMILY: ORGANOSILANE

FORMULA: C<sub>11</sub>H<sub>25</sub>NSi

HMIS CODES HEALTH: 3 FLAMMABILITY: 2 REACTIVITY: 1

#### **INGREDIENTS**

IDENTITY CAS NO. % TLV

ALLYLDIMETHYL(DIISOPROPYLAMINO)SILANE 106948-24-7 >95 not determined (OSHA PEL for diisopropylamine, TWA: 10ppm)

# **PHYSICAL DATA**

Boiling Point: 79-81°C at 13mm Freezing Point: <0°C

Specific Gravity: 0.815 Vapor Pressure at 25°C: not determined

Vapor Density (air=1): >1 Solubility in water: reacts % volatiles: NA Evaporation rate: NA

Molecular Weight: 199.42 Other: NA

Appearance & Color: Clear to straw liquid with acrid amine odor

# **FIRE & EXPLOSION DATA**

Flash Point, COC: 62°C (144°F) Autoignition Temp.: not determined

Flammability Limits: not determined

Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical.

Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale

vapors.

Unusual Fire and Explosion Hazards: Irritating fumes of diisopropylamine and organic acid vapors may develop when material is exposed to water or open flame.

Abbreviations: ND: Not Determined, No Data; NA: Not Applīda (SIA0.461) ose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemcial Abstract Service Registration Number Gelest, Inc. © 2008



## **ENVIRONMENTAL INFORMATION**

Spill response: May be hazardous to aquatic life if released to open waters. Cover spill with absorbent material. Transfer to a suitable container for disposal.

Recommended Disposal: Hydrolyze material by mixing with water in a hood. Aqueous layer contains disopropylamine which should be neutralized with hydrochloric acid. Organic layer may be incinerated. Alternately, absorb onto clay or vermiculite and dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

## **HEALTH HAZARD DATA**

Eye Contact: Will cause immediate or delayed severe eye irritation.

Skin contact: May produce irritation or contact dermatitis which may be delayed several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation of vapors or particulates of may irritate the respiratory tract. Overexposure may produce coughing, headache and nausea.

Oral Toxicity: Not determined.

Chronic Toxicity: There are no known chronic effects related to this compound.

## SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having

convulsions. Get medical attention.

# **REACTIVITY DATA**

Stability: Stable in sealed containers stored under a dry inert atmosphere. Conditions to avoid: Combustible; avoid contact with heat, sparks or open flame. Incompatibility (materials to avoid): Reacts with water and moisture in air liberating diisopropylamine. Avoid contact with alcohols, acids, oxidizers. Hazardous decomposition products: Organic acid vapors, diisopropylamine.

-2-(SIA0461.0)



#### SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is recommended. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV air-supplied or combination organic vapor/amine gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

#### OTHER PRECAUTIONS

For research use only.

Storage and Handling: Store in sealed containers under a dry inert atmosphere of nitrogen or argon. All transfers should be maintained under a dry inert atmosphere of nitrogen or argon.

## TRANSPORTATION

DOT SHIPPING NAME: COMBUSTIBLE LIQUID, N.O.S.

DOT HAZARD CLASS: Not Regulated

**DOT LABEL: Not Required** DOT ID No: Not Required

Prepared by safety and environmental affairs ISSUE DATE SIA0461.0: 5/7/03 **SUPERSEDES: 10/15/98** 

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.

-3-(SIA0461.0)