

# GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067  
Phone: (215) 547-1015

MATERIAL SAFETY  
DATA SHEET

EMERGENCY TELEPHONE  
CHEMTREC: 1-800-424-9300

NAME ON LABEL: **[2-(CYCLOHEXENYL)ETHYL]DIMETHYLCHLOROSILANE - SIC2457.0**

CHEMICAL NAME: [2-(CYCLOHEXENYL)ETHYL]DIMETHYLCHLOROSILANE

SYNONYMS: (DIMETHYLCHLOROSILYLETHYL)CYCLOHEXENE

CHEMICAL FAMILY: ORGANOSILANE

FORMULA: C<sub>10</sub>H<sub>19</sub>ClSi

HMIS CODES HEALTH: 3 FLAMMABILITY: 2 REACTIVITY: 1

## INGREDIENTS

| IDENTITY                                    | CAS NO.   | %   | TLV | OSHA PEL                                   |
|---------------------------------------------|-----------|-----|-----|--------------------------------------------|
| [2-(CYCLOHEXENYL)ETHYL]DIMETHYLCHLOROSILANE | 5089-25-8 | >95 |     | not established<br>(ceiling for HCl: 5ppm) |

## PHYSICAL DATA

Boiling Point: 105-9°C at 10mm

Specific Gravity: 0.96

Vapor Density (air=1): >1

% volatiles: NA

Molecular Weight: 202.80

Appearance & Color: Clear to straw liquid with acrid odor

Freezing Point: <0°C

Vapor Pressure, 25°C: <1mm

Solubility in water: reacts

Evaporation rate: NA

Other: NA

## FIRE & EXPLOSION DATA

Flash Point, COC: 74°C (165°F)

Autoignition Temp.: not determined

Flammability Limits: not determined

Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical.

Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Irritating fumes of hydrochloric acid and organic acid vapors may develop when material is exposed to water or open flame.

-1-(SIC2457.0)

## ENVIRONMENTAL INFORMATION

Spill response: May be hazardous to aquatic life if released to open waters. Cover spill with absorbent material. Transfer to a suitable container for disposal.

Recommended Disposal: Hydrolyze material by mixing with water in a hood. Aqueous layer contains hydrochloric acid which should be neutralized. Organic layer may be incinerated. Alternately, absorb onto clay or vermiculite and dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

## HEALTH HAZARD DATA

Eye Contact: Will cause immediate or delayed severe eye irritation.

Skin contact: May produce irritation or contact dermatitis which may be delayed several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation of vapors or particulates of may irritate the respiratory tract. Overexposure may produce coughing, headache and nausea.

Oral Toxicity: not determined.

Chronic Toxicity: There are no known chronic effects related to this compound.

## SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

## REACTIVITY DATA

Stability: Stable in sealed containers stored under a dry inert atmosphere.

Conditions to avoid: Combustible; avoid contact with heat, sparks or open flame.

Incompatibility (materials to avoid): Reacts with water and moisture in air liberating hydrogen chloride. Avoid contact with alcohols, amines, oxidizers.

Hazardous decomposition products: Organic acid vapors, silicon dioxide.

-2-(SIC2457.0)

## SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV air-supplied or combination organic vapor acid gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

## OTHER PRECAUTIONS

For research use only.

Storage and Handling: Store in sealed containers.

## TRANSPORTATION

DOT SHIPPING NAME: CHLOROSILANES, N.O.S.  
(CYCLOHEXENYLETHYLDIMETHYLCHLOROSILANE)

DOT HAZARD CLASS: 8

DOT LABEL: CORROSIVE

DOT ID No: UN 2987

PG: II

Prepared by safety and environmental affairs

ISSUE DATE SIC2457.0: 6/9/03

SUPERSEDES: 8/18/98

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.

-3-(SIC2457.0)