

Safety Data Sheet SID3393.0
Date of issue: 09/21/2015 Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Substance
Physical state : Liquid

Substance name : DIETHOXYDICHLOROSILANE, tech-90

Product code : SID3393.0
Formula : C4H10Cl2O2Si

Synonyms : DIETHOXYSILYLDICHLORIDE; SILICON DICHLORIDE DIETHOXIDE

Chemical family : ORGANOCHLOROSILANE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Chemical intermediate

For research use only

#### 1.3. Details of the supplier of the safety data sheet

#### **GELEST, INC.**

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

## **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### Classification (GHS-US)

Flam. Liq. 3 H226 Skin Corr. 1B H314 Eye Dam. 1 H318

Full text of H-phrases: see section 16

## 2.2. Label elements

## **GHS-US** labeling

Hazard pictograms (GHS-US)





GHS02

gHS05

Signal word (GHS-US) : Dange

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

Precautionary statements (GHS-US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection

P210 - Keep away from heat, open flames, sparks. - No smoking

P233 - Keep container tightly closed

P240 - Ground/bond container and receiving equipment P241 - Use explosion-proof electrical equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P260 - Do not breathe vapors

P264 - Wash hands thoroughly after handling

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a doctor

P321 - Specific treatment (see first aid instructions on this label)

P363 - Wash contaminated clothing before reuse

P370+P378 - In case of fire: Use water spray or fog, foam, carbon dioxide, dry chemical to

09/21/2015 EN (English US) SDS ID: **SID3393.0** Page 1

## Safety Data Sheet

extinguish

P403+P235 - Keep in a cool place

P405 - Store locked up

P501 - Dispose of contents/container to licensed waste disposal facility.

#### 2.3. Other hazards

Other hazards not contributing to the classification

Hydrogen chloride may be formed by reaction with water and moisture in air. The US OSHA PEL (TWA) for hydrogen chloride is 5 ppm. Additional ethanol may be formed by reaction with moisture and water. The hydrolysis product of this compound is ethanol. Overexposure to ethanol by skin absorption, inhalation or ingestion may have a narcotic effect (headache, nausea, drowsiness). Ethanol is metabolized to acetaldehyde and acetic acid which in large quantities result in metabolic acidosis, CNS depression and death due to respiratory arrest. The US OSHA PEL (TWA) for ethanol is 1000 ppm. This product contains ethanol which is classified as a carcinogen by IARC in alcoholic beverages.

#### 2.4. Unknown acute toxicity (GHS US)

No data available

#### **SECTION 3: Composition/information on ingredients**

3.1. Substance

Substance type : Multi-constituent

Name : DIETHOXYDICHLOROSILANE, tech-90

CAS No : 4667-38-3

Name	Product identifier	%	Classification (GHS-US)
Diethoxydichlorosilane	(CAS No) 4667-38-3	85 - 100	Flam. Liq. 3, H226 Skin Corr. 1B, H314 Eye Dam. 1, H318
Triethoxychlorosilane	(CAS No) 4667-99-6	10 - 15	Flam. Liq. 3, H226 Skin Corr. 1B, H314 Eye Dam. 1, H318
Ethyl silicate	(CAS No) 78-10-4	0 - 5	Flam. Liq. 3, H226 Eye Irrit. 2A, H319 STOT SE 3, H335

#### 3.2. Mixture

Not applicable

## **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

First-aid measures general

- : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label. IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.
- First-aid measures after skin contact
- First-aid measures after eye contact
- : Wash with plenty of soap and water. Get immediate medical advice/attention.
- : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.
- First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

## 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries
Symptoms/injuries after inhalation

: Causes severe skin burns and eye damage.: May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : Causes (severe) skin burns.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : May be harmful if swallowed.

Chronic symptoms : On contact with water this compound liberates ethanol which is known to have a chronic effect on the central nervous system.

## 4.3. Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form ethanol.

#### **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : Water.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor. Irritating fumes of hydrochloric acid and organic acid vapors may develop when material is exposed to water or open flame.

09/21/2015 EN (English US) SDS ID: **SID3393.0** 2/8

## Safety Data Sheet

#### 5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed

containers.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Do not attempt to take action without suitable

protective equipment. For further information refer to section 8: "Exposure controls/personal

protection".

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal. Use only non-sparking tools.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Additional hazards when processed : Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in process area to prevent accumulation of vapors. Take precautionary measures against static

discharge. Ground/bond container and receiving equipment. Use only non-sparking tools.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof

electrical equipment.

Storage conditions : Keep container tightly closed. Keep in a cool place. Store locked up.

Incompatible materials : Oxidizing agent.

Storage area : Store in a well-ventilated place. Store away from heat.

## 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

## 8.1. Control parameters

Ethyl silicate (78-10-4)		
USA ACGIH	ACGIH TWA (ppm)	10 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	85 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	10 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	850 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	100 ppm
USA IDLH	US IDLH (ppm)	700 ppm

#### 8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be

available in the immediate vicinity of any potential exposure.

Hand protection : Neoprene or nitrile rubber gloves.

09/21/2015 EN (English US) SDS ID: **SID3393.0** 3/8

## Safety Data Sheet

Eye protection : Chemical goggles or face shield. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. NIOSH-certified combination organic vapor/acid gas (yellow cartridge)

respirator.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear liquid.

Molecular mass : 189.11 g/mol

Color : No data available

Odor : Characteristic. Acrid. Similar to hydrogen chloride.

Odor threshold : No data available
Refractive index : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available

Freezing point : < 0 °C Boiling point : 137 - 138 °C Flash point : < 65 °C

Auto-ignition temperature : No data available Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapor

Vapor pressure : No data available

Relative vapor density at 20 °C : > 1
Relative density
VOC content : 100 %

Solubility Reacts with water. Log Pow No data available No data available Log Kow No data available Viscosity, kinematic Viscosity, dynamic No data available No data available Explosive properties Oxidizing properties No data available : No data available **Explosion limits** 

#### 9.2. Other information

No additional information available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air or with water liberating ethanol. Reacts with water and moisture in air, liberating hydrogen chloride.

#### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

## 10.5. Incompatible materials

Oxidizing agent.

#### 10.6. Hazardous decomposition products

Ethanol. Hydrogen chloride. Organic acid vapors. Silicon dioxide.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

09/21/2015 EN (English US) SDS ID: **SID3393.0** 4/8

## Safety Data Sheet

Ethyl silicate (78-10-4)	
LD50 oral rat	6270 mg/kg
LDLo inhalation rat	1000 ppm/4h
ATE US (oral)	6270.000 mg/kg body weight
Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Causes serious eye damage.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Potential Adverse human health effects and symptoms	: This material slowly generates ethanol on contact with water and moisture in living tissues. Material generates ethanol on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue.
Symptoms/injuries after inhalation	: May cause irritation to the respiratory tract.
Symptoms/injuries after skin contact	: Causes (severe) skin burns.
Symptoms/injuries after eye contact	: Causes serious eye damage.
Symptoms/injuries after ingestion	: May be harmful if swallowed.
Chronic symptoms	: On contact with water this compound liberates ethanol which is known to have a chronic effect on the central nervous system.

## **SECTION 12: Ecological information**

### 12.1. Toxicity

Reason for classification

No additional information available

#### 12.2. Persistence and degradability

No additional information available

## 12.3. Bioaccumulative potential

No additional information available

#### 12.4. Mobility in soil

No additional information available

## 12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

: Expert judgment

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility.

Ecology - waste materials : Avoid release to the environment.

## **SECTION 14: Transport information**

#### 14.1. UN number

UN-No.(DOT) : 2986 DOT NA no. UN2986

## 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Chlorosilanes, corrosive, flammable, n.o.s.

(DIETHOXYDICHLOROSILANE)

Department of Transportation (DOT) Hazard

Classes

: 8 - Class 8 - Corrosive material 49 CFR 173.136

09/21/2015 EN (English US) SDS ID: **SID3393.0** 5/8

## Safety Data Sheet

Hazard labels (DOT) : 8 - Corrosive

3 - Flammable liquid



Packing group (DOT) : II - Medium Danger

DOT Packaging Exceptions (49 CFR 173.xxx) : None
DOT Packaging Non Bulk (49 CFR 173.xxx) : 206
DOT Packaging Bulk (49 CFR 173.xxx) : 243

#### 14.3. Additional information

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : C - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Air transport

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 30 L

CFR 175.75)

#### **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

## DIETHOXYDICHLOROSILANE, tech-90 (4667-38-3)

TSCA Exemption/Exclusion

CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r) is not permitted in the United States.

#### Diethoxydichlorosilane (4667-38-3)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

## Triethoxychlorosilane (4667-99-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Ethyl silicate (78-10-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

## Triethoxychlorosilane (4667-99-6)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

#### Ethyl silicate (78-10-4)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Canadian DSL (Domestic Sustances List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ISHL (Industrial Safety and Health Law)

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

Listed on INSQ (Mexican national Inventory of Chemical Substances)

Listed on Turkish inventory of chemical

#### 15.3. US State regulations

DIETHOXYDICHLOROSILANE, tech-90(4667-38-3)	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive	No

09/21/2015 EN (English US) SDS ID: **SID3393.0** 6/8

Safety Data Sheet

DIETHOXYDICHLOROSILANE, tech-90(4667-38-3)				
Toxicity - Female	, ,			
U.S California - Proposition 65 - Reproductive Toxicity - Male		No		
Diethoxydichlorosilane (46	667-38-3)			
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	
Triethoxychlorosilane (4667-99-6)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	
Ethyl silicate (78-10-4)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	No	No	No	

## **SECTION 16: Other information**

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

#### Full text of H-phrases::

7. C. I. P. II GOOD!	
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Skin Corr. 1B	Skin corrosion/irritation Category 1B
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation

## **HMIS III Rating**

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 3 Serious Hazard
Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 09/21/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom


 $According \ to \ Federal \ Register \ / \ Vol. \ 77, \ No. \ 58 \ / \ Monday, \ March \ 26, \ 2012 \ / \ Rules \ and \ Regulations$ 

09/21/2015 EN (English US) SDS ID: **SID3393.0** 7/8

Safety Data Sheet

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2015 Gelest Inc. Morrisville, PA 19067



09/21/2015 EN (English US) SDS ID: **SID3393.0** 8/8