

Safety Data Sheet SID4080.0
Date of issue: 08/13/2015 Version: 1.0

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Substance
Physical state : Liquid

Substance name : DIMETHYLDI-n-BUTOXYSILANE

Product code : SID4080.0
Formula : C10H24O2Si

Synonyms : DIMETHYLSILICONDI-n-BUTOXIDE; DIBUTOXY(DIMETHYL)SILANE

Chemical family : SILICATE ESTER

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Chemical intermediate

For research use only

### 1.3. Details of the supplier of the safety data sheet

## **GELEST, INC.**

11 East Steel Road Morrisville, PA 19067

**USA** 

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

## 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

## Classification (GHS-US)

Flam. Liq. 4 H227 Eye Irrit. 2A H319

Full text of H-phrases: see section 16

### 2.2. Label elements

#### **GHS-US** labeling

Hazard pictograms (GHS-US)



GHS07

Signal word (GHS-US) : Warning

Hazard statements (GHS-US) : H227 - Combustible liquid

H319 - Causes serious eye irritation

Precautionary statements (GHS-US) : P280 - Wear protective gloves/protective clothing/eye protection/face protection

P264 - Wash hands thoroughly after handling

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing P337+P313 - If eye irritation persists: Get medical advice/attention P210 - Keep away from heat, open flames, sparks. - No smoking

P370+P378 - In case of fire: Use water spray or fog, foam, carbon dioxide, dry chemical to

extinguish

P403+P235 - Keep in a cool place

P501 - Dispose of contents/container to licensed waste disposal facility.

#### 2.3. Other hazards

No additional information available

## 2.4. Unknown acute toxicity (GHS US)

No data available

08/13/2015 EN (English US) SDS ID: **SID4080.0** Page 1

# Safety Data Sheet

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Substance type : Multi-constituent

Name : DIMETHYLDI-n-BUTOXYSILANE

CAS No : 1591-02-2 EC no : 216-467-0

Name	Product identifier	%	Classification (GHS-US)
Dibutoxy(dimethyl)silane	(CAS No) 1591-02-2	> 95	Flam. Liq. 4, H227 Eye Irrit. 2A, H319
Dimethyl-n-butoxymethoxysilane	(CAS No) 87561-41-0	< 5	Eye Irrit. 2A, H319

## 3.2. Mixture

Not applicable

#### **SECTION 4: First aid measures**

# 4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek

medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water.

First-aid measures after eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : May cause skin irritation.

Symptoms/injuries after eye contact : Causes serious eye irritation.

Symptoms/injuries after ingestion : No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.

Unsuitable extinguishing media : None known.

## 5.2. Special hazards arising from the substance or mixture

Fire hazard : Combustible liquid. Irritating fumes and organic acid vapors may develop when material is

exposed to elevated temperatures or open flame.

## 5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

chemical fire.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Avoid all eye and skin contact and do not breathe vapor and mist.

## **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

## 6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

## 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal

protection".

## 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

08/13/2015 EN (English US) SDS ID: **SID4080.0** 2/6

# Safety Data Sheet

## 6.3. Methods and material for containment and cleaning up

For containment : Contain any spills with dikes or absorbents to prevent migration and entry into sewers or

streams

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal. Use only non-sparking tools.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Provide good ventilation in

process area to prevent accumulation of vapors. Take precautionary measures against static

discharge. Use only non-sparking tools.

Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or

smoking and when leaving work. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Keep container tightly closed.

Incompatible materials : Oxidizing agent.

Storage area : Store in a well-ventilated place. Store away from heat.

### 7.3. Specific end use(s)

No additional information available

## **SECTION 8: Exposure controls/personal protection**

## 8.1. Control parameters

Dibutoxy(dimethyl)silane (1591-02-2)				
USA OSHA	OSHA PEL (TWA) (ppm)		100 ppm n-butanol	

## 8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be

available in the immediate vicinity of any potential exposure.

Hand protection : Neoprene or nitrile rubber gloves.

Eye protection : Chemical goggles. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended. NIOSH-certified organic vapor (black cartridge) respirator.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Clear liquid.

Molecular mass : 204.38 g/mol

Color : No data available

Odor : Characteristic.

Odor threshold : No data available

Refractive index : 1.4058

pH : No data available Relative evaporation rate (butyl acetate=1) : No data available Melting point : No data available

Freezing point : < -80 °C

Boiling point : 82 °C @ 12 mm Hg

Flash point : 79 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Flammability (solid, gas) : Combustible liquid

Vapor pressure : < 2 mm Hg @ 20°C

Relative vapor density at 20 °C : > 1
Relative density : 0.834

08/13/2015 EN (English US) SDS ID: **SID4080.0** 3/6

# Safety Data Sheet

Solubility : Reacts with water. Log Pow : No data available Log Kow : No data available

Viscosity, kinematic : 2 cSt

Viscosity, dynamic No data available Explosive properties : No data available Oxidizing properties : No data available **Explosion limits** : No data available

#### Other information

No additional information available

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No additional information available

#### **Chemical stability** 10.2.

Stable.

#### 10.3. Possibility of hazardous reactions

Material decomposes slowly in contact with moist air or with water liberating n-butanol.

#### **Conditions to avoid**

Heat. Open flame. Sparks.

## Incompatible materials

Oxidizing agent.

## **Hazardous decomposition products**

n-Butanol. Organic acid vapors. Silicon dioxide.

## **SECTION 11: Toxicological information**

### Information on toxicological effects

Acute toxicity Not classified Not classified Skin corrosion/irritation

Serious eye damage/irritation Causes serious eye irritation.

Not classified Respiratory or skin sensitization Not classified Germ cell mutagenicity Carcinogenicity Not classified : Not classified Reproductive toxicity Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: This compound liberates n-butanol on contact with moisture. Material generates n-butanol on contact with water or moisture in skin, eyes and mucous membranes and has an irritating,

dehydrating effect on overexposed tissue.

May cause irritation to the respiratory tract. Symptoms/injuries after inhalation

Symptoms/injuries after skin contact May cause skin irritation. Symptoms/injuries after eye contact Causes serious eye irritation. Symptoms/injuries after ingestion : No information available.

Reason for classification : Expert judgment

## **SECTION 12: Ecological information**

#### 12.1. **Toxicity**

No additional information available

#### Persistence and degradability 12.2.

No additional information available

#### **Bioaccumulative potential** 12.3.

No additional information available

## **Mobility in soil**

No additional information available

08/13/2015 SDS ID: SID4080.0 EN (English US) 4/6

# Safety Data Sheet

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on ozone layer : No additional information available

: No known ecological damage caused by this product. Effect on the global warming

## **SECTION 13: Disposal considerations**

#### Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility.

Ecology - waste materials Avoid release to the environment.

## **SECTION 14: Transport information**

#### 14.1. **UN** number

DOT NA no. NA1993

#### 14.2. **UN** proper shipping name

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.

(DIMETHYLDI-n-BUTOXYSILANE)

Department of Transportation (DOT) Hazard

Classes

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

**DOT Symbols** : D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN

requiring a technical name

: III - Minor Danger Packing group (DOT)

DOT Packaging Exceptions (49 CFR 173.xxx) : 150 DOT Packaging Non Bulk (49 CFR 173.xxx) : 203 DOT Packaging Bulk (49 CFR 173.xxx) : 241

## 14.3. Additional information

No supplementary information available. Other information

## Transport by sea

A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a **DOT Vessel Stowage Location** 

passenger vessel.

## Air transport

DOT Quantity Limitations Passenger aircraft/rail : 60 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

## **SECTION 15: Regulatory information**

## 15.1. US Federal regulations

## **DIMETHYLDI-n-BUTOXYSILANE (1591-02-2)**

TSCA Exemption/Exclusion CAUTION: This material is supplied for research and development purposes subject to the R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the

exemption, including supervision by a "technically qualified individual" as defined by 40 CFR 720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r)

is not permitted in the United States.

## Dibutoxy(dimethyl)silane (1591-02-2)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

## Dimethyl-n-butoxymethoxysilane (87561-41-0)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

## 15.2. International regulations

## Dibutoxy(dimethyl)silane (1591-02-2)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

# Dimethyl-n-butoxymethoxysilane (87561-41-0)

SDS ID: SID4080.0 08/13/2015 EN (English US) 5/6

## Safety Data Sheet

## 15.3. US State regulations

DIMETHYLDI-n-BUTOXYSILANE(1591-02-2)		
U.S California - Proposition 65 - Carcinogens List	No	
U.S California - Proposition 65 - Developmental Toxicity	No	
U.S California - Proposition 65 - Reproductive Toxicity - Female	No	
U.S California - Proposition 65 - Reproductive Toxicity - Male	No	
Dilutural dimensional distriction (AFAA 00.0)		

#### Dibutoxy(dimethyl)silane (1591-02-2)

	U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Ī	No	No	No	No	

#### Dimethyl-n-butoxymethoxysilane (87561-41-0)

P	J.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Ν	lo	No	No	No	

## **SECTION 16: Other information**

Abbreviations and acronyms

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

### Full text of H-phrases::

Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 4	Flammable liquids Category 4
H227	Combustible liquid
H319	Causes serious eye irritation

## **HMIS III Rating**

Health : 2 Moderate Hazard - Temporary or minor injury may occur

Flammability : 2 Moderate Hazard Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.

Date of issue: 08/13/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2015 Gelest Inc. Morrisville, PA 19067

08/13/2015 EN (English US) SDS ID: **SID4080.0** 6/6