

# **GELEST, INC.**

11 East Steel Rd. Morrisville, PA 19067 Phone: (215) 547-1015

MATERIAL SAFETY DATA SHEET

EMERGENCY TELEPHONE CHEMTREC: 1-800-424-9300

NAME ON LABEL: 1,3-DIVINYL-1,3-DIPHENYL-1,3-DIMETHYLDISILAZANE - SID4607.0

CHEMICAL NAME: 1,3-DIVINYL-1,3-DIPHENYL-1,3-DIMETHYLDISILAZANE

SYNONYMS: BIS(VINYLPHENYLMETHYLSILYL)AMINE

CHEMICAL FAMILY: ORGANOSILANE

FORMULA: C<sub>18</sub>H<sub>23</sub>NSi<sub>2</sub>

HMIS CODES HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 1

## **INGREDIENTS**

IDENTITY CAS NO. % TLV

1,3-DIVINYL-1,3-DIPHENYL-1,3-DIMETHYLDISILAZANE

23038-10-0 >95 not established

## PHYSICAL DATA

Boiling Point: 118°C at 1mm Freezing Point: <0°C

Specific Gravity: 1.001 Vapor Pressure, 20°: <0.1mm Vapor Density (air =1): >1 Solubility in water: insoluble, reacts

% volatiles: NA Evaporation rate: NA

Molecular Weight: 309.56 Other: NA Appearance & Color: Clear liquid with ammonia odor.

### FIRE & EXPLOSION DATA

Flash Point, COC: 165°C (329°F) Autoignition Temp.: not determined

Flammability Limits: not determined

Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical.

Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale

vapors.

Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame. Liquid generates strong static charge when poured.

-1-(SID4607.0)

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemcial Abstract Service Registration Number Gelest. Inc. © 2008



#### **ENVIRONMENTAL INFORMATION**

Spill response: May be hazardous to aquatic life if released to open waters. Cover spill with absorbent material. Transfer to a suitable container for disposal.

Recommended Disposal: May be incinerated. Alternately, absorb onto clay or vermiculite and dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

### **HEALTH HAZARD DATA**

Reacts with moisture in living tissue to generate ammonia.

Eye Contact: Vapors may cause immediate or delayed severe eye irritation. Liquid will cause severe conjunctivitis and corneal damage

Skin contact: May produce irritation or contact dermatitis which may be delayed several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation of vapors or particulates will irritate the respiratory tract. Overexposure may produce coughing, headache and nausea.

Oral Toxicity: not determined

Chronic Toxicity: There are no known chronic effects related to this compound.

### SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having

convulsions. Get medical attention.

## **REACTIVITY DATA**

Stability: Stable in sealed containers in a cool place.

Conditions to avoid: Flammable; avoid contact with heat, sparks or open flame.

Incompatibility (materials to avoid): Reacts with water and moisture in air liberating ammonia. Avoid contact with peroxides, oxidizing agents, alcohols, acids.

Hazardous decomposition products: Organic Acid Vapors.

## -2-(SID4607.0)



### SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV air-supplied or combination organic vapor amine gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

#### OTHER PRECAUTIONS

The related compound, hexamethyldisilazane, is known to have an exceptional tendency to accumulate static charge. The user must take extreme care to dissipate static charge by grounding of all equipment involved in liquid transfer.

For research and industrial use only.

Storage and Handling: Store in sealed containers.

# **TRANSPORTATION**

DOT SHIPPING NAME: CHEMICALS, NOI

DOT HAZARD CLASS: Not Regulated

DOT LABELS: Not Required DOT ID No: Not Required

Prepared by safety and environmental affairs ISSUE

ISSUE DATE SID4607: 6/30/03 SUPERSEDES: 11/21/96

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.

-3-(SID4607.0)