

Safety Data Sheet SIM6515.0

Date of issue: 01/07/2015 Revision date: 10/26/2015 Version: 2.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Substance
Physical state : Gas

Substance name : METHYLSILANE
Product code : SIM6515.0
Formula : CH6Si

Synonyms : 1MS; SILYLMETHANE; MONOMETHYLSILANE; MONOSILYLMETHANE

Chemical family : ORGANOHYDRIDOSILANE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Chemical intermediate

For research and industrial use only

1.3. Details of the supplier of the safety data sheet

GELEST, INC.

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Gas 1 H220 Liquefied gas H280

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US)





GHS04

502

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H220 - Extremely flammable gas

H280 - Contains gas under pressure; may explode if heated

Precautionary statements (GHS-US) : P210 - Keep away from heat, open flames, sparks. - No smoking

P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely

P381 - Eliminate all ignition sources if safe to do so

P410+P403 - Protect from sunlight. Store in a well-ventilated place

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substance

Substance type : Mono-constituent
Name : METHYLSILANE
CAS No : 992-94-9
EC no : 213-598-5

10/26/2015 EN (English US) SDS ID: **SIM6515.0** Page 1

Safety Data Sheet

Name	Product identifier	%	GHS-US classification
Methylsilane	(CAS No) 992-94-9	97 - 100	Flam. Gas 1, H220 Liguefied gas, H280

3.2. Mixture

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not

available show packaging or label.

First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel

unwell, seek medical advice.

First-aid measures after skin contact : Wash with plenty of soap and water. Get medical advice/attention.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. Get medical advice/attention.

First-aid measures after ingestion : Never give anything by mouth to an unconscious person. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : May cause skin irritation.
Symptoms/injuries after eye contact : May cause eye irritation.
Symptoms/injuries after ingestion : No information available.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide. Dry chemical. Use of high expansion foam (100:1) is

recommended to cover flames.
Unsuitable extinguishing media : Water.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable gas. Irritating fumes and organic acid vapors may develop when material

is exposed to water or open flame.

Explosion hazard : Methylsilane has been reported to spontaneously ignite on contact with air. Contains gas under

pressure; may explode if heated.

5.3. Advice for firefighters

Firefighting instructions : Exercise caution when fighting any chemical fire. Eliminate all ignition sources if safe to do so.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Use only dry media to

extinguish flames.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Fire

fighters must wear positive pressure self-contained breathing apparatus. Avoid contact with

skin and eyes. Do not breathe gas.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Eliminate every possible source of ignition. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Protective equipment : Wear protective equipment as described in Section 8.

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with

proper protection. For further information refer to section 8: "Exposure controls/personal

protection".

Emergency procedures : Evacuate area. Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : The potential exists for spontaneous ignition and explosion. Allow vapors to disperse. Ventilate

area.

10/26/2015 EN (English US) SDS ID: **SIM6515.0** 2/6

Safety Data Sheet

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Extremely flammable gas. Handle empty containers with care because residual vapors are

flammable. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautions for safe handling : Avoid contact with skin and eyes. Do not breathe gas. Ground/bond container and receiving

equipment. Handle only in sealed purged systems.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands and other exposed areas with mild

soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof

electrical equipment.

Storage conditions : Keep container tightly closed. Protect from sunlight. Store in sealed cylinders in isolated area.

Incompatible materials : Acids. Alcohols. Oxidizing agent.

Storage area : Store in a well-ventilated place. Store away from heat.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Methylsilane (992-94-9)		
USA ACGIH	ACGIH TWA (ppm)	5 ppm for silane

8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Emergency eye wash fountains and safety showers should be available in the immediate

vicinity of any potential exposure. Avoid all unnecessary exposure.

Hand protection : Neoprene or nitrile rubber gloves.

Eye protection : Chemical goggles. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is

recommended.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Gas

Appearance : Colorless gas. Molecular mass : 46.14 g/mol Color : No data available No data available Odor Odor threshold No data available Refractive index : No data available : No data available pΗ Relative evaporation rate (butyl acetate=1) : No data available No data available Melting point

Freezing point : -157 °C Boiling point : -57 °C Flash point : -57 °C Critical temperature : 79.3 °C Auto-ignition temperature : 130 °C

Decomposition temperature : No data available

Flammability (solid, gas) : Extremely flammable gas

Vapor pressure : 14 atm @ 21°C; 241 mm Hg @ -80°C

Relative vapor density at 20 °C : 1.6

Relative density : 0.628

VOC content : 100 %

Solubility : Reacts with water.

10/26/2015 EN (English US) SDS ID: **SIM6515.0** 3/6

Safety Data Sheet

Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosion limits : No data available

9.2. Other information

Gas group : Liquefied gas

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable in sealed cylinders stored under a dry inert atmosphere.

10.3. Possibility of hazardous reactions

Reacts with oxygen in air, may ignite spontaneously. Mixtures with mercury explode when shaken in the presence of air. Platinum, platinum and iron salts and other Lewis acids can cause generation of flammable hydrogen gas in the presence of moisture.

10.4. Conditions to avoid

Heat. Sparks. Open flame.

10.5. Incompatible materials

Acids. Alcohols. Oxidizing agent.

10.6. Hazardous decomposition products

Organic acid vapors. Silicon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified

None of the components in this product at concentrations >0.1% are listed by IARC, NTP,

OSHA or ACGIH as a carcinogen.

Reproductive toxicity : Not classified Specific target organ toxicity (single exposure) : Not classified Specific target organ toxicity (repeated : Not classified

exposure)

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause irritation to the respiratory tract.

Symptoms/injuries after skin contact : May cause skin irritation.
Symptoms/injuries after eye contact : May cause eye irritation.
Symptoms/injuries after ingestion : No information available.

SECTION 12: Ecological information

12.1. Toxicity

No additional information available

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

10/26/2015 EN (English US) SDS ID: **SIM6515.0** 4/6

Safety Data Sheet

12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Sewage disposal recommendations : Do not dispose of waste into sewer.

Waste disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

14.1. UN number

UN-No.(DOT) : 3161 DOT NA no. UN3161

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Liquefied gas, flammable, n.o.s.

(METHYLSILANE)

Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115

Hazard labels (DOT) : 2.1 - Flammable gas



DOT Symbols : G - Identifies PSN requiring a technical name

DOT Packaging Exceptions (49 CFR 173.xxx) : 306

DOT Packaging Non Bulk (49 CFR 173.xxx) : 304

DOT Packaging Bulk (49 CFR 173.xxx) : 314;315

14.3. Additional information

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : D - The material must be stowed "on deck only" on a cargo vessel and on a passenger vessel

carrying a number of passengers limited to not more than the larger of 25 passengers or one passenger per each 3 m of overall vessel length, but the material is prohibited on passenger

vessels in which the limiting number of passengers is exceeded.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Air transport

DOT Quantity Limitations Passenger aircraft/rail : Forbidden

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 150 kg

CFR 175.75)

SECTION 15: Regulatory information

15.1. US Federal regulations

Methylsilane (992-94-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

Methylsilane (992-94-9)

Listed on the Canadian NDSL (Non-Domestic Substances List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

10/26/2015 EN (English US) SDS ID: **SIM6515.0** 5/6

Safety Data Sheet

15.3. US State regulations

METHYLSILANE(992-94-9)	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No
Methylsilane (992-94-9)	

Methylsilane (992-94-9)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

SECTION 16: Other information

Abbreviations and acronyms

: Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

Full text of H-phrases::

Flam. Gas 1	Flammable gases Category 1
Liquefied gas	Gases under pressure Liquefied gas
H220	Extremely flammable gas
H280	Contains gas under pressure; may explode if heated

HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 4 Severe Hazard Physical : 3 Serious Hazard

Prepared by safety and environmental affairs.

Date of issue: 01/07/2015 Revision date: 10/26/2015 Version: 2.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2015 Gelest Inc. Morrisville, PA 19067

10/26/2015 EN (English US) SDS ID: **SIM6515.0** 6/6