

GELEST, INC.
 11 East Steel Rd. Morrisville, PA 19067
 Phone: (215) 547-1015

**MATERIAL SAFETY
 DATA SHEET**

**EMERGENCY TELEPHONE
 CHEMTREC: 1-800-424-9300**

NAME USED ON LABEL: SODIUM (2-FURYL)DIMETHYLSILANOLATE - SIS6980.6
 CHEMICAL NAME: SODIUM (2-FURYL)DIMETHYLSILANOLATE
 SYNONYMS: SODIUM 2-FURANYLDIMETHYLSILANOLATE
 CHEMICAL FAMILY: ORGANOSILANE
 FORMULA: C₆H₉ONaSi
 HMIS CODES HEALTH: 2 FLAMMABILITY: 1 REACTIVITY: 1

INGREDIENTS

IDENTITY	CAS NO.	%	TLV	OSHA PEL
SODIUM (2-FURYL)DIMETHYLSILANOLATE	879904-88-8	>95	not established	not established
HEXAMETHYLDISILOXANE	107-46-0	<5	not established	not established

PHYSICAL DATA

Boiling Point: NA	Melting Point: 65-80°C
Specific Gravity: not determined	Vapor Pressure: not determined
Vapor Density: NA	Solubility in water: insoluble, reacts
% volatiles NA	Evaporation rate: NA
Molecular Weight: 164.21	Other: NA
Appearance & Color: Off white to tan solid, slight odor.	

FIRE & EXPLOSION DATA

Flash Point, COC: > 65°C (>150°F) Autoignition Temp.: not determined
 Flammability Limits: not determined

Extinguishing Media: Foam, carbon dioxide, dry chemical.
 Special Fire Fighting Procedures: Avoid water spray as volatile organics will be generated. Avoid eye and skin contact. Do not breathe fumes or inhale vapors.
 Unusual Fire and Explosion Hazards: Irritating fumes and caustic vapors may develop when material is exposed to elevated temperatures or open flame.

-1-(SIS6980.6)

ENVIRONMENTAL INFORMATION

Spill response: Ventilate area. Eliminate ignition sources. Scoop material into a dry metal container and cover loosely. Take to a chemical disposal area, then flush with a copious amount of water, collecting all caustic wastewater for proper disposal.

Recommended disposal: Treat quantities of 1000 grams or less by flooding with water. Water solution will be caustic. Follow all chemical pollution control regulations. For larger quantities, mix with water, neutralize with dilute hydrochloric acid, then separate non-aqueous liquid for incineration. Alternately, combine with neutral or basic organic streams and incinerate

HEALTH HAZARD DATA

Eye Contact: Will cause immediate or delayed severe caustic burns to the eyes.

Skin contact: Will cause irritation and burns. If skin and air are dry, powder on skin may not cause irritation or burns. Worker will notice a slippery feeling on washing. However, if moisture is present, the powder can cause severe caustic burns.

Inhalation: Inhalation will cause sneezing, irritation and burns.

Oral Toxicity: not determined

Inhalation Toxicity: not determined

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes, holding eyes open. Get medical attention.

SKIN: Immediately shake or brush off any loose material, then flush with water for at least fifteen minutes.

INHALATION: Move exposed individual to fresh air. Administer oxygen if needed. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Give a demulscent such as milk, olive oil, or margarine in small amounts, up to two or three tablespoons.

REACTIVITY DATA

Stability: Stable under nitrogen or argon in sealed containers.

Conditions to avoid: Material decomposes slowly in contact with moist air and rapidly in contact with water, possibly igniting. Avoid contact with moist air, water, acids, alcohols, ketones, esters, carbon dioxide, halogens.

Hazardous decomposition products: Sodium hydroxide and caustic organic vapors.

-2-(SIS6980.6)

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, a NIOSH approved particulate filter-type respirator should be worn.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. Long-sleeved fire-resistant lab uniform or coverall is recommended. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research use only.

Storage and Handling: Store under dry nitrogen or argon in sealed containers.

TRANSPORTATION

DOT SHIPPING NAME: CORROSIVE SOLID, BASIC, ORGANIC n.o.s.
(SODIUM (2-FURYL)DIMETHYLSILANOLATE)

DOT HAZARD CLASS: 8

DOT LABELS: 6.1

DOT ID No: 3262

PG: III

Prepared by safety and environmental affairs

MSDS ISSUE DATE SIS6980.6: 3/4/13
SUPERSEDES: none

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

-3-(SIS6980.6)

© 2013 Gelest Inc. Morrisville, PA 19067