

GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067
Phone: (215) 547-1015

MATERIAL SAFETY DATA SHEET

EMERGENCY TELEPHONE
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **1,1,3,3-TETRAETHOXY-1,3-DIMETHYLDISILOXANE - SIT7095.0**
CHEMICAL NAME: 1,1,3,3-TETRAETHOXY-1,3-DIMETHYLDISILOXANE
SYNONYMS: 1,3-DIMETHYL-1,1,3,3-TETRAETHOXYDISILOXANE
CHEMICAL FAMILY: ORGANOSILANE ESTER
FORMULA: C₁₀H₂₆O₅Si₂

HMIS CODES HEALTH: 3 FLAMMABILITY: 3 REACTIVITY: 1

INGREDIENTS

IDENTITY	CAS NO.	%	TLV	OSHA PEL
1,1,3,3-TETRAETHOXY-1,3-DIMETHYLDISILOXANE	18001-60-0	>90	not established	
METHYLTRIETHOXYSILANE	2031-67-6	<5	not established	
ETHANOL	64-17-5	<2	1000ppm	

PHYSICAL DATA

Boiling Point: 205°C
Specific Gravity: 0.953
Vapor Density, air = 1: > 1
% volatiles: <10
Molecular Weight: 282.48
Appearance & Color: Clear liquid, characteristic pleasant odor.

Melting Point: <0°C
Vapor Pressure, 25°C: 6mm
Solubility in water: insoluble, reacts slowly
Evaporation rate (butyl acetate = 1): <1
Other: NA

FIRE & EXPLOSION DATA

Flash Point, TCC: 58°C (136°F)
Autoignition Temp.: 225°C
Flammability Limits: not determined

Extinguishing Media: Water spray or fog, foam, carbon dioxide, dry chemical.
Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

-1-(SIT7095.0)

ENVIRONMENTAL INFORMATION

Spill response: Sweep material and transfer to a suitable container for disposal.

Recommended Disposal: Incinerate. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: May cause immediate or delayed severe eye irritation.

Skin contact: May produce irritation or contact dermatitis. Material generates ethanol on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation may irritate the respiratory tract. Overexposure can cause lung damage - pulmonary toxin.

Note: The hydrolysis of this product produces ethanol. Overexposure to ethanol by skin absorption, inhalation or ingestion may have a narcotic effect (headache, nausea, drowsiness). Ethanol is metabolized to acetaldehyde and acetic acid which in large quantities result in metabolic acidosis, CNS depression and death due to respiratory arrest.

Oral Toxicity: not determined

Inhalation Toxicity: not determined

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Administer oxygen if needed. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. To conscious individual give one full cup of water to dilute ingested material. Get medical attention.

REACTIVITY DATA

Stability: Stable

Conditions to avoid: Material decomposes slowly in contact with moist air or with water liberating ethanol; TLV(TWA) = 1000ppm. Avoid contact with oxidizing agents..

Hazardous decomposition products: Ethanol, organic acid vapors and silicon dioxide.

-2-(SIT7095.0)

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, NIOSH approved organic vapor respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research use only.

Storage and Handling: Store in sealed containers.

Containers require grounding during use.

TRANSPORTATION

DOT SHIPPING NAME: FLAMMABLE LIQUID, N.O.S.
(1,1,3,3-TETRAETHOXY-1,3-DIMETHYLDISILOXANE)

DOT HAZARD CLASS: 3

DOT LABEL: FLAMMABLE LIQUID

DOT ID No: UN1993

PG III

ERG: 27

Prepared by safety and environmental affairs

ISSUE DATE SIT7095.0: 8/27/03

SUPERSEDES: 8/12/98

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.