

GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067 Phone: (215) 547-1015

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE

CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: 4-[2-(TRICHLOROSILYL)ETHYL]PYRIDINE, 15-20% - SIT8158.0

CHEMICAL NAME: 4-[2-(TRICHLOROSILYL)ETHYL]PYRIDINE, 15-20% in toluene

SYNONYMS: 2-(4-PYRIDYL)ETHYLTRICHLOROSILANE

CHEMICAL FAMILY: CHLOROSILANE

FORMULA: C7H8Cl3NSi

HMIS CODES HEALTH: 3 FLAMMABILITY: 4 REACTIVITY: 1

INGREDIENTS

IDENTITY CAS NO. % TLV OSHA PEL

4-[2-(TRICHLOROSILYL)ETHYL]PYRIDINE 17082-70-1 15-20 not established

TOLUENE 108-88-3 80-85 100ppm 200ppm

PHYSICAL DATA

Boiling Point: 110°C - initial (toluene) Melting Point: not determined

Specific Gravity: 0.93 Vapor Pressure: not determined

Vapor Density, air: not determined Solubility in water: reacts % volatiles: >80 Evaporation rate: NA

Molecular Weight: 240.59 Other: NA

Appearance & Color: Amber, hazy, fuming liquid with acrid odor

FIRE & EXPLOSION DATA

Flash Point, COC: 4°C (39°F) Autoignition Temp.: not determined

Flammability Limits: not determined

Extinguishing Media: Water spray or fog, foam, carbon dioxide, dry chemical.

Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale

vapors.

Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

Abbreviations: ND: Not Determined, No Data; NA: Not Applicate States and Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemcial Abstract Service Registration Number Gelest, Inc. © 2008



ENVIRONMENTAL INFORMATION

Spill response: Sweep material and transfer to a suitable container for disposal.

Recommended Disposal: Incinerate. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: Will cause immediate or delayed severe eye irritation.

Skin contact: May produce irritation or contact dermatitis. Material generates hydrochloric acid on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation may irritate the respiratory tract. Overexposure can cause lung damage - pulmonary toxin.

Oral Toxicity: not determined Inhalation Toxicity: not determined

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Administer oxygen if needed. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. To conscious individual give one full cup of water to dilute ingested material. Get medical attention.

REACTIVITY DATA

Stability: Stable

Conditions to avoid: Material decomposes in contact with moist air or with water liberating hydrochloric acid. Avoid contact with oxidizing agents.

Hazardous decomposition products: Ethanol, acid vapors and silicon dioxide.

-2-(SIT8158.0)



SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, NIOSH approved organic vapor respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency

shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store in sealed containers.

Containers require grounding during use.

TRANSPORTATION

DOT SHIPPING NAME: CHLOROSILANES, FLAMMABLE, CORROSIVE, N.O.S.

(4-[2-(TRICHLOROSILYL)ETHYL]PYRIDINE)

DOT HAZARD CLASS: 3 SUBSIDIARY: 8 DOT LABEL:FLAMMABLE LIQUID AND CORROSIVE

DOT ID No: UN2985 PG: II

Prepared by safety and environmental affairs ISSUE DATE SIT8158.0: 8/30/03

SUPERSEDES: 6/12/96

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore.

-3-(SIT8158.0)