

Safety Data Sheet SIT8180.0
Date of issue: 02/06/2015 Version: 1.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Substance
Physical state : Liquid

Substance name : TRIETHOXYFLUOROSILANE, 95%

Product code : SIT8180.0 Formula : C6H15FO3Si

Synonyms : TRIETHYLFLUOROSILICATE; FLUOROTRIETHOXYSILANE

Chemical family : ORGANOSILANE

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Chemical intermediate

For research use only

#### 1.3. Details of the supplier of the safety data sheet

#### **GELEST, INC.**

11 East Steel Road Morrisville, PA 19067

USA

T 215-547-1015 - F 215-547-2484 - (M-F): 8:00 AM - 5:30 PM EST

info@gelest.com - www.gelest.com

#### 1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300 (USA); +1 703-527-3887 (International)

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

#### **Classification (GHS-US)**

Flam. Liq. 3 H226 Skin Corr. 1C H314 Eye Dam. 1 H318

Full text of H-phrases: see section 16

#### 2.2. Label elements

### **GHS-US** labeling

Hazard pictograms (GHS-US)





GHS02

GHS05

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H226 - Flammable liquid and vapor

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

Precautionary statements (GHS-US) : P280 - Wear protective clothing, protective gloves, eye protection

P260 - Do not breathe vapors

P264 - Wash hands thoroughly after handling

P310 - Immediately call a doctor

P210 - Keep away from heat, open flames, sparks. - No smoking

P240 - Ground/bond container and receiving equipment

P242 - Use only non-sparking tools

P243 - Take precautionary measures against static discharge

P241 - Use explosion-proof electrical equipment

P370+P378 - In case of fire: Use water spray, foam, carbon dioxide, dry chemical to extinguish

P301+P330+P331 - If swallowed: rinse mouth. Do NOT induce vomiting

P303+P361+P353 - If on skin (or hair): take off immediately all contaminated clothing. rinse

skin with water/shower

P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing

P363 - Wash contaminated clothing before reuse

P233 - Keep container tightly closed

02/06/2015 EN (English US) SDS ID: **SIT8180.0** Page 1

## Safety Data Sheet

P403+P235 - Keep in a cool place

P405 - Store locked up

P501 - Dispose of contents/container to licensed waste disposal facility.

#### Other hazards

Other hazards not contributing to the classification

The hydrolysis product of this compound is ethanol. Overexposure to ethanol by skin absorption, inhalation or ingestion may have a narcotic effect (headache, nausea, drowsiness). Ethanol is metabolized to acetaldehyde and acetic acid which in large quantities result in metabolic acidosis, CNS depression and death due to respiratory arrest. This product contains ethanol which is classified as a carcinogen by IARC in alcoholic beverages.

#### 2.4. **Unknown acute toxicity (GHS-US)**

No data available

#### SECTION 3: Composition/information on ingredients

#### **Substance**

: Mono-constituent Substance type

: TRIETHOXYFLUOROSILANE, 95% Name

CAS No : 358-60-1

Name	Product identifier	%	Classification (GHS-US)
Triethoxyfluorosilane	(CAS No) 358-60-1	> 95	Flam. Liq. 3, H226 Skin Corr. 1C, H314 Eye Dam. 1, H318
Ethanol	(CAS No) 64-17-5		Flam. Liq. 2, H225 Carc. 1A, H350 STOT SE 3, H335

#### **Mixture**

Not applicable

### **SECTION 4: First aid measures**

#### **Description of first aid measures**

First-aid measures general

Remove contaminated clothing and shoes. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). If possible show this sheet; if not available show packaging or label.

First-aid measures after inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If you feel unwell, seek medical advice.

First-aid measures after skin contact

Wash with plenty of soap and water. Get immediate medical advice/attention.

First-aid measures after eye contact

: Immediately flush eyes thoroughly with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

First-aid measures after ingestion

: Never give anything by mouth to an unconscious person. Get medical advice/attention.

#### Most important symptoms and effects, both acute and delayed

Symptoms/injuries

: Causes severe skin burns and eye damage.

Symptoms/injuries after inhalation

May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache.

Nausea.

Symptoms/injuries after skin contact Symptoms/injuries after eye contact

: Causes (severe) skin burns. : Causes serious eye damage.

Symptoms/injuries after ingestion

No information available.

Chronic symptoms

On contact with water this compound liberates ethanol which is known to have a chronic effect

on the central nervous system.

#### Indication of any immediate medical attention and special treatment needed

NOTE TO PHYSICIAN: This product reacts with water in the acid contents of the stomach to form ethanol.

## **SECTION 5: Firefighting measures**

#### **Extinguishing media**

Suitable extinguishing media : Water spray. Water fog. Foam. Carbon dioxide. Dry chemical.

chemical fire.

#### Special hazards arising from the substance or mixture

Fire hazard

: Flammable liquid and vapor. Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

#### **Advice for firefighters**

Firefighting instructions

: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any

Protection during firefighting

: Do not enter fire area without proper protective equipment, including respiratory protection. Avoid all eye and skin contact and do not breathe vapor and mist.

SDS ID: SIT8180.0 02/06/2015 EN (English US) 2/8

## Safety Data Sheet

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

#### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean up any spills as soon as possible, using an absorbent material to collect it. Sweep or

shovel spills into appropriate container for disposal. Use only non-sparking tools.

#### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

#### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid all eye and skin contact and do not breathe vapor and mist. Containers must be properly

grounded before beginning transfer. Provide good ventilation in process area to prevent accumulation of vapors. Take precautionary measures against static discharge. Use only non-

sparking tools.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond

container and receiving equipment.

Storage conditions : Keep container tightly closed.

Incompatible materials : Oxidizing agent.

Storage area : Store in a well-ventilated place. Store away from heat.

#### 7.3. Specific end use(s)

No additional information available

#### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Ethanol (64-17-5)		
USA ACGIH	ACGIH STEL (ppm)	1000 ppm
USA NIOSH	NIOSH REL (TWA) (mg/m³)	1900 mg/m³
USA NIOSH	NIOSH REL (TWA) (ppm)	1000 ppm
USA OSHA	OSHA PEL (TWA) (mg/m³)	1900 mg/m³
USA OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA IDLH	US IDLH (ppm)	3300 ppm (10% LEL)

#### 8.2. Exposure controls

Appropriate engineering controls : Provide local exhaust or general room ventilation.

Personal protective equipment : Avoid all unnecessary exposure. Emergency eye wash fountains and safety showers should be

available in the immediate vicinity of any potential exposure.

Hand protection : Neoprene or nitrile rubber gloves.

Eye protection : Chemical goggles or face shield. Contact lenses should not be worn.

Skin and body protection : Wear suitable protective clothing.

Respiratory protection : NIOSH-certified combination organic vapor/acid gas (yellow cartridge) respirator.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Clear liquid.
Molecular mass : 182.27 g/mol
Color : No data available

02/06/2015 EN (English US) SDS ID: **SIT8180.0** 3/8

## Safety Data Sheet

Odor : Characteristic.

Odor threshold : No data available
Refractive index : No data available
pH : No data available
Relative evaporation rate (butyl acetate=1) : No data available
Melting point : No data available
Freezing point : < -20 °C

Freezing point : < -20 °C Boiling point : 133 - 134 °C Flash point : > 30 °C

Auto-ignition temperature : No data available Decomposition temperature : No data available

Flammability (solid, gas) : Flammable liquid and vapor

Vapor pressure : 3.3 mm Hg @ 25°C

Relative vapor density at 20 °C : > 1Relative density : 0.94VOC content : 100 %

Reacts with water. Solubility Log Pow No data available : No data available Log Kow : No data available Viscosity, kinematic Viscosity, dynamic No data available Explosive properties No data available Oxidizing properties : No data available No data available **Explosive limits** 

#### 9.2. Other information

No additional information available

#### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No additional information available

## 10.2. Chemical stability

Stable.

#### 10.3. Possibility of hazardous reactions

Material decomposes in contact with moist air or with water liberating ethanol.

#### 10.4. Conditions to avoid

Heat. Open flame. Sparks.

#### 10.5. Incompatible materials

Oxidizing agent.

#### 10.6. Hazardous decomposition products

hydrofluoric acid. Organic acid vapors. Silicon dioxide.

#### **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Acute toxicity : Not classified

124.7 mg/l/4h
: Causes severe skin burns and eye damage.
: Causes serious eye damage.
: Not classified
: Not classified
: Not classified
A related hydrolysis product, acetamide, is an experimental carcinogen, neoplastigen and teratogen.

Ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans
Reproductive toxicity	Not classified

02/06/2015 EN (English US) SDS ID: **SIT8180.0** 4/8

## Safety Data Sheet

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated

Symptoms/injuries after inhalation

exposure)

: Not classified

Aspiration hazard : Not classified

Potential Adverse human health effects and

symptoms

: Note: Hydrolysis products of silicon tetraethoxide include hydrofluoric acid and ethanol.

: May cause irritation to the respiratory tract. Overexposure may cause: Cough. Headache.

Nausea.

Symptoms/injuries after skin contact : Causes (severe) skin burns.

Symptoms/injuries after eye contact : Causes serious eye damage.

Symptoms/injuries after ingestion : No information available.

Chronic symptoms : On contact with water this compound liberates ethanol which is known to have a chronic effect

on the central nervous system.

Reason for classification : Expert judgment

### **SECTION 12: Ecological information**

#### 12.1. Toxicity

Ethanol (64-17-5)	
LC50 fish 1	12.0 - 16.0 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	9268 - 14221 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	2 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])

#### 12.2. Persistence and degradability

No additional information available

#### 12.3. Bioaccumulative potential

Ethanol (64-17-5)			
Log Pow	-0.32		

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Other adverse effects

Other adverse effects : This substance may be hazardous to the environment.

Effect on ozone layer : No additional information available

Effect on the global warming : No known ecological damage caused by this product.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste disposal recommendations : Incinerate. Dispose in a safe manner in accordance with local/national regulations. Dispose of

contents/container to licensed waste disposal facility.

Additional information : Handle empty containers with care because residual vapors are flammable.

Ecology - waste materials : Avoid release to the environment.

## **SECTION 14: Transport information**

### 14.1. UN number

UN-No.(DOT) : 2924 DOT NA no. UN2924

#### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Flammable liquids, corrosive, n.o.s.

(TRIETHOXYFLUOROSILANE)

Department of Transportation (DOT) Hazard

Classes

: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

Hazard labels (DOT) : 3 - Flammable liquid

8 - Corrosive



DOT Symbols : G - Identifies PSN requiring a technical name

02/06/2015 EN (English US) SDS ID: **SIT8180.0** 5/8

## Safety Data Sheet

Packing group (DOT) : III - Minor Danger

DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
DOT Packaging Bulk (49 CFR 173.xxx) : 242

14.3. Additional information

Other information : No supplementary information available.

Transport by sea

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

DOT Vessel Stowage Other : 40 - Stow "clear of living quarters"

Air transport

DOT Quantity Limitations Passenger aircraft/rail : 5 L

(49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 60 L

CFR 175.75)

#### **SECTION 15: Regulatory information**

#### 15.1. US Federal regulations

TRIETHOXYFLUOROSILANE, 95% (358-60-1)	
TSCA Exemption/Exclusion	CAUTION: This material is supplied for research and development purposes subject to the
	R&D exemption under TSCA, 40 CFR 720.36, and must meet the requirements of the
	exemption, including supervision by a "technically qualified individual" as defined by 40 CFR
	720.3(ee). The use of this material for "commercial purposes" as defined by 40 CFR 720.3(r)
	is not permitted in the United States.

#### Triethoxyfluorosilane (358-60-1)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

#### Ethanol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

#### 15.2. International regulations

## Ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

Listed on the AICS (Australian Inventory of Chemical Substances)

Listed on the Canadian DSL (Domestic Sustances List)

Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory

Listed on the Korean ECL (Existing Chemicals List)

Listed on NZIoC (New Zealand Inventory of Chemicals)

Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

Listed on the Canadian IDL (Ingredient Disclosure List)

## 15.3. US State regulations

TRIETHOXYFLUOROSILANE, 95%(358-60-1)	
U.S California - Proposition 65 - Carcinogens List	No
U.S California - Proposition 65 - Developmental Toxicity	No
U.S California - Proposition 65 - Reproductive Toxicity - Female	No
U.S California - Proposition 65 - Reproductive Toxicity - Male	No

# Triethoxyfluorosilane (358-60-1)

,	,			
U.S California - Proposition 65 -	No significance risk level (NSRL)			
				(NOINE)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	
		Female	Male	
No	No	No	No	
140	140	140	110	
Ethanol (64-17-5)				
U.S California -	U.S California -	U.S California -	U.S California -	No significance risk level
Proposition 65 -	Proposition 65 -	Proposition 65 -	Proposition 65 -	(NSRL)
Carcinogens List	Developmental Toxicity	Reproductive Toxicity -	Reproductive Toxicity -	

02/06/2015 EN (English US) SDS ID: **SIT8180.0** 6/8

Male

Female

## Safety Data Sheet

Triethoxyfluorosilane (358-	60-1)			
Yes	Yes	No	No	

#### Ethanol (64-17-5)

- U.S. Connecticut Hazardous Air Pollutants HLVs (30 min)
- U.S. Connecticut Hazardous Air Pollutants HLVs (8 hr)
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Acceptable Ambient Concentrations
- U.S. Idaho Non-Carcinogenic Toxic Air Pollutants Emission Levels (ELs)
- U.S. Idaho Occupational Exposure Limits TWAs
- U.S. Maine Chemicals of High Concern
- U.S. Massachusetts Allowable Ambient Limits (AALs)
- U.S. Massachusetts Allowable Threshold Concentrations (ATCs)
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 1
- U.S. Massachusetts Oil & Hazardous Material List Groundwater Reportable Concentration Reporting Category 2
- U.S. Massachusetts Oil & Hazardous Material List Reportable Quantity
- U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 1 U.S. Massachusetts Oil & Hazardous Material List Soil Reportable Concentration Reporting Category 2
- U.S. Massachusetts Right To Know List
- U.S. Massachusetts Threshold Effects Exposure Limits (TELs)
- U.S. Michigan Occupational Exposure Limits TWAs
- U.S. Minnesota Chemicals of High Concern
- U.S. Minnesota Hazardous Substance List
- U.S. Minnesota Permissible Exposure Limits TWAs
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) 24-Hour
- U.S. New Hampshire Regulated Toxic Air Pollutants Ambient Air Levels (AALs) Annual
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. New Jersey Special Health Hazards Substances List U.S. New York Occupational Exposure Limits TWAs
- U.S. North Dakota Air Pollutants Guideline Concentrations 1-Hour
- U.S. Oregon Permissible Exposure Limits TWAs
- U.S. Pennsylvania RTK (Right to Know) List
- U.S. Tennessee Occupational Exposure Limits TWAs
- U.S. Texas City of Austin Aerosol Paint and Glue Restrictions
- U.S. Texas Effects Screening Levels Long Term
- U.S. Texas Effects Screening Levels Short Term
- U.S. Vermont Permissible Exposure Limits TWAs
- U.S. Washington Permissible Exposure Limits STELs
- U.S. Washington Permissible Exposure Limits TWAs

## **SECTION 16: Other information**

Abbreviations and acronyms

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose; LC: Lethal Concentration; ATE: Acute Toxicity Estimates; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; TG: Test Guideline; NIOSH: National Institute for Occupational Safety and Health; IARC: International Agency for Research on Cancer; NTP: National Toxicology Program; HMIS: Hazardous Material Information System; CAS No.: Chemcial Abstract Service Registration Number; EC No.: European Commission Registration Number; EC Index No.: European Commission Index Number; OECD: The Organisation for Economic Co-operation and Development.

## Full text of H-phrases::

Carc. 1A	Carcinogenicity Category 1A
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Skin Corr. 1C	Skin corrosion/irritation Category 1C
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H335	May cause respiratory irritation
H350	May cause cancer

## **HMIS III Rating**

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is

given

Flammability : 3 Serious Hazard

SDS ID: SIT8180.0 02/06/2015 EN (English US) 7/8

## Safety Data Sheet

Physical : 1 Slight Hazard

Prepared by safety and environmental affairs.


Date of issue: 02/06/2015 Version: 1.0

SDS US (GHS HazCom 2012) - Custom

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

© 2014 Gelest Inc. Morrisville, PA 19067



02/06/2015 EN (English US) SDS ID: **SIT8180.0** 8/8