

GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067
Phone: (215) 547-1015

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **TRIS(DIMETHYLAMINO)SILANE, 99.9+% - SIT8714.1**
CHEMICAL NAME: TRIS(DIMETHYLAMINO)SILANE
SYNONYMS: TRIS(DIMETHYLAMIDO)SILYLHYDRIDE
CHEMICAL FAMILY: ORGANOSILANE
FORMULA: C₆H₁₉N₃Si

HMIS CODES HEALTH: 4 FLAMMABILITY: 3 REACTIVITY: 2

INGREDIENTS

| IDENTITY | CAS NO. | % | TLV |
|---------------------------|------------|-----|---|
| TRIS(DIMETHYLAMINO)SILANE | 15112-89-7 | >99 | not established (OSHA PEL for dimethylamine, TWA: 10ppm) |

PHYSICAL DATA

| | |
|---|-----------------------------|
| Boiling Point: 145-8°C | Freezing Point: -90°C |
| Specific Gravity: 0.838 | Vapor Pressure, 4°C: 16mm |
| Vapor Density (air=1): >1 | Solubility in water: reacts |
| % volatiles: NA | Evaporation rate: NA |
| Molecular Weight: 161.32 | Other: NA |
| Appearance & Color: Clear to straw liquid with acrid amine odor | |

FIRE & EXPLOSION DATA

Flash Point, COC : 25°C (77°F) Autoignition Temp.: not determined
Flammability Limits: not determined

Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical.
Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.
Unusual Fire and Explosion Hazards: Irritating fumes of dimethylamine and organic acid vapors may develop when material is exposed to water or open flame.

-1-(SIT8714.1)

ENVIRONMENTAL INFORMATION

Spill response: May be hazardous to aquatic life if released to open waters. Cover spill with absorbent material. Transfer to a suitable container for disposal.

Recommended Disposal: Hydrolyze material by mixing with water in a hood. Aqueous layer contains dimethylamine which should be neutralized with hydrochloric acid. Organic layer may be incinerated. Alternately, absorb onto clay or vermiculite and dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: Will cause immediate or delayed severe eye irritation.

Skin contact: May produce irritation or contact dermatitis which may be delayed several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation of vapors or particulates of will irritate the respiratory tract. Overexposure may produce coughing, headache and nausea.

Inhalation Toxicity - rat, LC50: 38ppm/4 hours

Oral Toxicity - rat, LD50: 595mg/kg

Chronic Toxicity: There are no known chronic effects related to this compound.

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

REACTIVITY DATA

Stability: Stable in sealed containers stored under a dry inert atmosphere.

Conditions to avoid: Combustible; avoid contact with heat, sparks or open flame.

Incompatibility (materials to avoid): Reacts with water and moisture in air liberating dimethylamine. Avoid contact with alcohols, acids, oxidizers.

Hazardous decomposition products: Organic acid vapors, dimethylamine, hydrogen.

-2-(SIT8714.1)

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV air-supplied or NIOSH approved combination organic vapor/amine gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research and industrial use only.

Storage and Handling: Store in sealed containers.

TRANSPORTATION

DOT SHIPPING NAME: TOXIC BY INHALATION, FLAMMABLE, N.O.S.
TRIS(DIMETHYLAMINO)SILANE

DOT HAZARD CLASS: 6.1 SUB: 3

DOT LABEL: TOXIC and FLAMMABLE

DOT ID No: UN 3384 PG: I

INHALATION HAZARD ZONE B

Prepared by safety and environmental affairs MSDS ISSUE DATE SIT8714.1: 9/15/16
SUPERSEDES: none

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

-3-(SIT8714.1)

© 2015 Gelest Inc. Morrisville, PA 19067