

GELEST, INC.

11 East Steel Rd. Morrisville, PA 19067
Phone: (215) 547-1015

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE
CHEMTREC: 1-800-424-9300

NAME USED ON LABEL: **DIMETHYLAMINOTRI-n-BUTYL TIN - SND3550**
 CHEMICAL NAME: DIMETHYLAMINOTRI-n-BUTYL TIN
 SYNONYMS: TRIBUTYL TINDIMETHYLAMIDE, TRIBUTYLDIMETHYLAMINOSTANNANE
 CHEMICAL FAMILY: ORGANOTIN
 FORMULA: C₁₄H₃₃NSn
 HMIS CODES HEALTH: 3 FLAMMABILITY: 1 REACTIVITY: 1

INGREDIENTS

IDENTITY	CAS NO.	%	TLV	OSHA PEL
DIMETHYLAMINOTRI-n-BUTYL TIN	1067-24-9	>95	0.1 mg/m ³ as tin	0.1 mg/m ³ as tin
OTHER ORGANOTINS		<5	0.1 mg/m ³ as tin	0.1 mg/m ³ as tin

PHYSICAL DATA

Boiling Point: 86°C at 0.1mm	Melting Point: <0°C
Specific Gravity: 1.08	Vapor Pressure: <0.01mm
Vapor Density (air=1): >1	Solubility in water: insoluble, reacts
% volatiles: NA	Evaporation rate: NA
Molecular Weight: 334.11	Other: NA.
Appearance & Color: Colorless to pale yellow liquid with characteristic odor	

FIRE & EXPLOSION DATA

Flash Point, TCC: 115°C (239°F) Autoignition Temp.: not determined
 Flammability Limits: not determined

Extinguishing Media: Water spray, foam, carbon dioxide, dry chemical.
 Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

-1-(SND3550)

ENVIRONMENTAL INFORMATION

Spill response: This material is acutely toxic to aquatic life if released to open waters. Cover spill with absorbent material. Transfer to a suitable container for disposal. This material is toxic to wildlife and fish.

Recommended Disposal: Dispose of absorbent material as solid waste. Follow all chemical pollution control regulations.

HEALTH HAZARD DATA

Eye Contact: A severe eye irritant . Will cause immediate or delayed severe eye irritation. The onset of irritation may not occur until several hours after exposure.

Skin contact: May produce irritation or contact dermatitis which may be delayed several hours. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects. Organotins may be absorbed through the skin.

Inhalation: Inhalation of vapors or particulates of organotins may irritate the respiratory tract. Overexposure may produce coughing, headache and nausea. The onset of symptoms may be delayed until several hours after exposure.

Oral Toxicity: not determined

Chronic Toxicity: There are no known chronic effects related to this compound.

SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water. *Note to physician: Application of corticosteroid creams has been effective in treating severe skin irritation. If blisters develop, they may require abrasion to promote healing.*

INHALATION: Move exposed individual to fresh air. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. Get medical attention.

REACTIVITY DATA

Stability: Stable In contact with water and moisture in air liberates dimethylamine.

Conditions to avoid: Acids and oxidizers

Incompatibility (materials to avoid): Oxidizers. Direct sunlight causes degradation to an inorganic tin salt.

Hazardous decomposition products: Organic acid vapors, tin oxides, dimethylamine.

-2-(SND3550)

SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV air-supplied or combination organic vapor acid gas respirator with dust prefilter.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

OTHER PRECAUTIONS

For research use only.

Storage and Handling: Store in sealed containers.

Keep out of reach of children.

TRANSPORTATION

DOT SHIPPING NAME: CORROSIVE LIQUID, N.O.S. (DIMETHYLAMINOTRI-n-BUTYLITIN)

DOT HAZARD CLASS: 8

DOT LABEL: CORROSIVE LIQUID

DOT ID No: UN1760

PG: III

Prepared by safety and environmental affairs

ISSUE DATE SND3550: 10/18/04

SUPERSEDES: 10/2/03

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

-3-(SND3550)

© 2004 Gelest inc. Morrisville, PA 19067