

# **GELEST, INC.**

11 East Steel Rd. Morrisville, PA 19067 Phone: (215) 547-1015

MATERIAL SAFETY
DATA SHEET

EMERGENCY TELEPHONE CHEMTREC: 1-800-424-9300

NAME ON LABEL: 1-n-DECYL-1,1,3,3,3-PENTACHLORO-1,3-DISILAPROPANE - SID2662.4

CHEMICAL NAME: 1-n-DECYL-1,1,3,3,3-PENTACHLORO-1,3-DISILAPROPANE

SYNONYMS: 1.1.1.3.3-PENTACHLORO-1.3-DISILATRIDECANE

CHEMICAL FAMILY: ORGANOCHLOROSILANE

FORMULA: C<sub>11</sub>H<sub>23</sub>Cl<sub>5</sub>Si<sub>2</sub>

HMIS CODES HEALTH: 3 FLAMMABILITY: 2 REACTIVITY: 1

# **INGREDIENTS**

IDENTITY CAS NO. % TLV OSHA PEL

1-n-DECYL-1,1,3,3,3-PENTACHLORO-1,3-DISILAPROPANE

1621184-14-2 >95 not established (ceiling for HCI: 5ppm)

## **PHYSICAL DATA**

Boiling Point: 126°C at 0.1mm Melting Point: <0°C

Specific Gravity: 1.178 Vapor Pressure, 20°: <0.01mm

Vapor Density (air = 1): >1 Solubility in water: reacts % volatiles: <10 Evaporation rate: NA

Molecular Weight: 388.73 Other: NA Appearance & Color: Clear liquid, characteristic odor

## **FIRE & EXPLOSION DATA**

Flash Point, COC: >110°C (>230°F) Autoignition Temp.: not determined

Flammability Limits: not determined

Extinguishing Media: Water spray or fog, alcohol resistant foam, carbon dioxide, dry chemical. Special Fire Fighting Procedures: Avoid eye and skin contact. Do not breathe fumes or inhale vapors.

Unusual Fire and Explosion Hazards: Irritating fumes and organic acid vapors may develop when material is exposed to elevated temperatures or open flame.

Abbreviations: ND: Not Determined, No Data; NA: Not Appīī 1 (SID2662.4) bose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemcial Abstract Service Registration Number Gelest, Inc. © 2008



### **ENVIRONMENTAL INFORMATION**

Spill response: Sweep material and transfer to a suitable container for disposal.

Recommended Disposal: Incinerate. Follow all chemical pollution control regulations.

## **HEALTH HAZARD DATA**

Eye Contact: Will cause immediate or delayed severe eye irritation. The ability of this material to react and crosslink in the presence of water indicates that contact of the eye by the liquid presents a severe eye hazard potential with the possibility of permanent damage including blindness.

Skin contact: May produce irritation or contact dermatitis. Material generates hydrogen chloride on contact with water or moisture in skin, eyes and mucous membranes and has an irritating, dehydrating effect on overexposed tissue. Prompt and thorough washing with soap and water will reduce or eliminate potential dermal effects.

Inhalation: Inhalation may irritate the respiratory tract. Overexposure can cause lung damage - pulmonary toxin.

Oral Toxicity: not determined Inhalation: not determined Eye Irritation: not determined

## SUGGESTED FIRST AID

EYES: In case of contact, immediately flush eyes with flowing water for at least 15 minutes. Get medical attention.

SKIN: Flush with water, then wash with soap and water.

INHALATION: Move exposed individual to fresh air. Administer oxygen if needed. Call a physician.

INGESTION: Never give fluids or induce vomiting if patient is unconscious or having convulsions. To conscious individual give one full cup of water to dilute ingested material. Get medical attention.



### **REACTIVITY DATA**

Stability: Stable in sealed containers.

Conditions to avoid: Material decomposes slowly in contact with moist air or with water liberating methanol. Avoid contact with oxidizing agents.

Hazardous decomposition products: Hydrogen chloride, organic acid vapors and silicon dioxide.

Hazardous polymerization: Will not occur.

## SPECIAL PROTECTION INFORMATION

Ventilation: Local exhaust is required. Mechanical is recommended.

Respiratory Protection: If exposure exceeds TLV, NIOSH certified combination organic vapor - acid gas respirator.

Eye and Face Protection: Chemical worker's goggles. Do not wear contact lenses.

Other Clothing and Equipment: Rubber, neoprene or nitrile gloves. An eyewash and emergency shower should be available. Launder clothing before reuse.

# OTHER PRECAUTIONS

For research use only.

Storage and Handling: Store in sealed containers.

#### TRANSPORTATION

DOT SHIPPING NAME: CHLOROSILANES, N.O.S.

(1-n-DECYL-1,1,3,3,3-PENTACHLORO-1,3-DISILAPROPANE)

DOT HAZARD CLASS: 8 DOT LABEL: CORROSIVE

DOT ID No: UN 2987 PG: II

Prepared by safety and environmental affairs MSDS ISSUE DATE SID2662.4: 1/28/15 SUPERSEDES: 10/28/14

The information contained in this document has been gathered from reference materials and/or Gelest, Inc. test data and is to the best knowledge and belief of Gelest, Inc. accurate and reliable. Such information is offered solely for your consideration, investigation and verification. It is not suggested or guaranteed that the hazard precautions or procedures described are the only ones which exist. Gelest, Inc. makes no warranties, express or implied, with respect to the use of such information and assumes no responsibility therefore. Information on this safety data sheet is not intended to constitute a basis for product specifications.

-3-(SID2662.4) © 2015 Gelest Inc. Morrisville, PA 19067

Abbreviations: ND: Not Determined, No Data; NA: Not Applicable; LD: Lethal Dose, LC: Lethal Concentration; H: hour; °: °C unless otherwise stated; mm: millimeters Hg, torr; PEL: permissible exposure level; TWA: time weighted average; TLV: threshold limit value; HMIS: Hazardous Material information System; CAS No.: Chemcial Abstract Service Registration Number Gelest. Inc. © 2008